Fori. 160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD Adesia FORM APPROVED OMB NO 1004-0135

Expires: July 31, 2010

Lease Serial No SUMPRY NOTICES AND REPORTS ON WELLS NINANINALO1EOO

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.				ee or Tribe Name	
SUBMIT IN TRI	PLICATE - Other instruc	tions on reverse side.	7 If Unit or CA/A	greement, Name and/or No.	
Type of Well ☐ Gas Well ☐ Other				No K BBW FEDERAL COM 2H	
Name of Operator YATES PETROLEUM CORPO	Contact. DRATIONE-Mail: tinah@yate	TINA HUERTA spetroleum.com	9 API Well No 30-015-3934	8-00-X1	
3a Address 105 SOUTH FOURTH STREET ARTESIA, NM 88210		3b Phone No. (include area code Ph: 575-748-4168 Fx: 575-748-4585) 10 Field and Pool EMPIRE	, or Exploratory	
4. Location of Well (Footage, Sec., T, R, M, or Survey Description) Sec 27 T16S R27E SESE 1100FSL 330FEL				11. County or Parish, and State EDDY COUNTY, NM	
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE OF 1	NOTICE, REPORT, OR OTI	HER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
☐ Notice of Intent Subsequent Report Final Abandonment Notice	☐ Acidize ☐ Alter Casing ☐ Casing Repair ☐ Change Plans ☐ Convert to Injection	☐ Deepen ☐ Fracture Treat ☐ New Construction ☐ Plug and Abandon ☐ Plug Back	☐ Production (Start/Resume) ☐ Reclamation ☐ Recomplete ☐ Temporarily Abandon ☐ Water Disposal	Water Shut-Off ☐ Well Integrity ☑ Other Drilling Operations	
13 Describe Proposed or Completed Op If the proposal is to deepen direction. Attach the Bond under which the wo following completion of the involved testing has been completed. Final Aldetermined that the site is ready for f 10/21/11 - Resumed drilling a 10/23/11 - TD 17-1/2" hole to Cemented with 500 sx Class Cement did not circulate. Rai cement + 2% S1 (vld 1.32, wt	ally or recomplete horizontally, rk will be performed or provide operations. If the operation resondonment Notices shall be filtinal inspection.) t 8:30 PM. 428' at 1:30 AM. Set 13-10" + 0.125#/sx D130 + 300 temperature survey and	give subsurface locations and measing the Bond No. on file with BLM/BL sults in a multiple completion or reced only after all requirements, included with the substitution of the substitu	ured and true vertical depths of all p A Required subsequent reports sha completion in a new interval, a Form ding reclamation, have been comple and at 428'. 1.34, wt 14.8). 1.25 sx Class "C"	ertinent markers and zones. Il be filed within 30 days 3160-4 shall be filed once	

25 sx Class "C" cement + 2% S1 (yld 1.32, wt 14.8) with no returns. WOC. RIH with 1" and tagged at 6b'. Pumped 25 sx Class "C" cement + 2% S1 (yld 1.32, wt 14.8) with returns but no cement to surface. WOC. RIH with 1" and tagged at 47'. Pumped 25 sx Class "C" cement + 2% S1 (yld 1.32, wt 14.8). Good returns. Circulated 5 sx cement to surface. WOC. Tested casing to 1200 psi for 30 min, Ok. WOC 39 hrs 30 min. Reduced hole to 12-1/4" and resumed drilling. NOTE: BLM Ok'd to run a cement bond log after we TD 12-1/4" hole and before we run 9-5/8" casing. 10/26/11 - TD 12-1/4" hole to 1543'. Set 9-5/8" 36# K-55 LT&C casing at 1543'. Cemented with 150 sx RFC + 10% D053 + 1% S1 (yld 1.61, wt 14.2) and 570 sx Class "C" + 3#/sx D042 + 0.125#/sx D130 +

NOV 1.6 2011 NMOCD ARTES

Accepted for record

NMOCD		
ORÁTION, sent to the Carlsbad		
Title REG COMPLIANCE SUPERVISOR		
Date 11/08/2011		
AL OR STATE OFFICE USE		
JAMES A AMOS TitleSUPERVISOR EPS	Date 11/11/2011	
Office Carlsbad		
	d by the BLM Well Information System ORATION, sent to the Carlsbad RT SIMMONS on 11/09/2011 (12KMS0278SE) Title REG COMPLIANCE SUPERVISOR Date 11/08/2011 AL OR STATE OFFICE USE JAMES A AMOS Title SUPERVISOR EPS	

Additional data for EC transaction #122461 that would not fit on the form

32. Additional remarks, continued

2% S1 + 0.2% D46 + 4% D020 (yld 1.99, wt 12.9). Tailed in with 200 sx Class "C" + 0.2% D046 + 0.2% D201 (yld 1.33, wt 14.8). Circulated 280 sx to pit. NOTE: Cement fell back 20'. Notified BLM engineer, Wesley Ingram, at 6:00 PM 10/27/11. Ok to do redi-mix. Tested casing to 1500 psi for 30 min, Ok. WOC 38 hrs 15 min. Reduced hole to 8-3/4" and resumed drilling.