

OCD-ARTESIA

Form 3160-5
(April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator **NADEL AND GUSSMAN HEYCO, LLC**

3a. Address
PO BOX 1936 ~ ROSWELL NM 88202-1936

3b. Phone No. (include area code)
575/623/6601

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
400' FNL & 380' FEL, Sec. 12: T18S, R31E

5. Lease Serial No.

NMNM-106718

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No

8. Well Name and No

TAYLOR DEEP 12 FED #10

9. API Well No.

30-025-39468

10. Field and Pool, or Exploratory Area

Delaware; Young North

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other Production Csg and Cmt Sundry
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomple horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

BLM Bond No. NMB00520
Surety Bond No. B004230

11/1/11 TD, Hole Size 7 7/8" hole, run 129 Jts, 5 1/2" J-55 17# . Depth 5500', Cmt Lead-800 sks Class "C" 50/50+10% Bentonite+.3%FL-10+5% Salt(BWOW)+.25%R-38. Tail-200 sks Starbond C+.3%FL-10+.1%C-20+.25%R-38. Plug dn @ 12:30 am 10/29/11. did not Circ cmt.

To C ?

Accepted for record
 NMOCD
 105
 DEC 02 2011

RECEIVED
 NOV 22 2011
 NMOCD ARTESIA

14. I hereby certify that the foregoing is true and correct
 Name (Printed/Typed)

Tammy R Link

Title **Production Tech**

Signature

Date

ACCEPTED FOR RECORD
 11/03/2011

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

NOV 16 2011
 Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

BUREAU OF LAND MANAGEMENT

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

SUMMARY CASING AND CEMENTING REPORT

STRING: PRIMARY

DATE: 11/1/2011

OPERATOR: NADEL & GUSSMAN HEYCO WELL: TAYLOR 12 FED #10
CONTRACTOR: PATRIOT RIG: #1
REP: KEITH CANNON

CASING DETAIL

HOLE SIZE:	7.875"	DEPTH:	5500	
5.5" HOLE				5500.00
5.5" FLOAT SHOE				<u>0.90</u>
				5499.10
2 JT. 5.5" J-55 17 # CASING				<u>84.34</u>
				5414.76
5.5" FLOAT COLLAR				<u>0.80</u>
				5413.96
127 JTS 5.5"J-55 17# CASING				<u>5403.10</u>
				10.86
KB TO GL				<u>18.00</u>

CENTRALIZERS PLACED @ 1 ON EACH SHOE JT. NEXT 23 EVERY OTHER JT.

REMARKS:

TOTAL CASING DELIVERED....132 JTS (5617.51) 5 1/2" 17# J-55 LTC
ALL CASING WAS DRIFTED, CLEANED, & VISUALLY INSPECTED ON LOCATION.

. CIRCULATED CAPACITY & ANNULAR VOLUME

EXCESS CASING

CASING NOT USED3 JTS. 126.57' 5 1/2" 17# J-55 LTC
DISPOSITION GYS YARD

CEMENTING DATA

COMPANY: RISING STAR

DISTRICT: HOBBS

1ST STAGE:

PREFLUSH: 20bbls F/W SPACER

LEAD: 800 SKS CLASS "C" 50/50+10%BENTONITE+.3%FL-10+5%SALT(BWOW)+.25%R-38

TAIL: 200 SKS STARBOND C+.3%FL-10+.1%C-20+.25%R-38

SUMMARY CASING AND CEMENTING REPORT

NOTE:

Plug down @ 12:30am 10/29/2011. Did not circulate cement. Had 1700 psi of lift just before plug was seated w/ 123 bbls