3160-5 ril 2004)

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)

which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease

Approved by

## UNITED STATES DEPARTMENT OF THE INTERIOR OF CONS. DIV-DIS BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires March 31, 2007

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS	a waeul
Do not use this form for proposals to drill or to be still can NW	88210
shandaned well. Hee Form 2160 2 (ABD) for such proposels	002.10

abandoned well. Use Form 3160-3 (APD) for such proposals.

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on reverse side		7. If Unit or CA/Agreement, Name and/or No.			
1. Type of Well Oil Well X Gas Well Other  2. Name of Operator Marathon Oil Company  3a. Address P.O. Box 3487 Houston, TX 77253-3487  4. Location of Well (Footage, Sec., T., R., M., or Survey Des SHL UL "M", Sec 11, T-21-S, R-23-E, HHL UL "N", Sec 11, T-21-S, R-23-E,	760' FSL & 990		1 2005	8. Well Name and No. North Indian Basin Unit No. 22 9. API Well No. 30-015-28583 10. Field and Pool, or Exploratory Area South Dagger Draw Upper Penn 11. County or Parish, State	
12. CHECK APPROPRIATE B	BOX(ES) TO INC	DICATE NATURE OF N	IQTICE, REP	ORT, OR OTHE	R DATA
TYPE OF SUBMISSION		TYP	E OF ACTION		
Notice of Intent    X   Subsequent Report	Alter Casing Casing Repair Change Plans Convert to Injectic tate all pertinent detaine horizontally, give surmed or provide the line operation results in tices shall be filed on on.)  coperations to cion liner. These see attachs	New Construction Plug and Abandon Plug Back  Ils, including estimated startin absurface locations and meas Bond No. on file with BLM/ a multiple completion or re by after all requirements, includes  deepen the North I he well was directinent for daily deta	Reclamation Recomplet Recomplet Temporari Water Disp ag date of any produced and true ver BIA. Required so completion in a reluding reclamation Condian Basin conal drille	by Abandon  posal  poposed work and an actical depths of all pubsequent reports arew interval, a Form, have been compared with a 6 /	pertinent markers and zones. shall be filed within 30 days in 3160-4 shall be filed once pleted, and the operator has to the Morrow 118" bit from
	्रक्षा स्थापना स्थापना स्थापना स्थापना स्थापन स्थापना स्थापना स्थापन	ALE	APR 19 20 EXIS C. SWORDLEUM ENG	005 005 BODA	

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Title

Date

Title

Office

Engineering Technician

Date

04/07/2005

## North Indian Basin Unit No. 22 Deepen to Morrow Drilling Operations / Set Liner

04/29/2004	Trip in to Plug back TD @ 7964'. Drill cement 7964 to 8049'. Drill out float shoe @ 8050. Drill open hole 8050' to 8070' with 6 1/8" bit.
	POOH to run directional tools.
04/30/2004	Directional drilled and surveyed from 8070' to 8221'.
05/01/2004	Directional drilled and surveyed from 8221' to 8768'.
05/02/2004	Directional drilled and surveyed from 8768' to 8980'. Trip for motor and MWD. Directional drilled and surveyed from 8980' to 9047'.
05/003/2004	Directional drilled and surveyed from 9047' to 9580'.
05/04/2004	Directional drilled and surveyed from 9580' to TD @ 9750'. Circulated hole clean, and made short trip. Circulate and tripped out of hole. Ran Triple Combo log stuck tool on bottom @ 9747'. Pulled free after working for 30 minutes.
05/05/2004	Ran 60 joints $4\frac{1}{2}$ " 11.6 # L80 LTC liner to 9750'. (Float shoe @ 9750', Float collar @ 9707', Top of liner @ 6989') Circulated hole clean. Rigged up Haliburton. Set Baker liner hanger. Cement w/ 200 sks Modified Super H + 0.5% Halad344 + 0.4% CFR3 + 1 # sk Salt + 0.2% HR7 mixed at 13.0 ppg with 1.66 yield. Dropped wiper dart and Displaced cement. Bumped plug w/ 2000 psi. Set Packer pulled up and reversed out 20 sks cement. Layed down drill pipe.

Nippled up BOP, rigged down, and released rig.

05/06/2004