

Submit 1 Copy To Appropriate District Office  
District I – (575) 393-6161  
1625 N French Dr., Hobbs, NM 88240  
District II – (575) 748-1283  
811 S First St, Artesia, NM 88210  
District III – (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV – (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised August 1, 2011

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-40188

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

RDX 16

8. Well Number  
11

9. OGRID Number  
246289

10. Pool name or Wildcat  
Brushy Draw-Delaware East

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
RKI Exploration & Production, LLC

3. Address of Operator  
3817 NW Expressway, Suite 950, Oklahoma City, OK 73112

4. Well Location

Unit Letter E : 1650 feet from the North line and 330 feet from the West line  
Section 16 Township 26S Range 30E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3084 feet GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.


On 7/09/2012, drilled 12-1/4 inch hole to 3485 feet. Ran 82 joints of 9-5/8 inch 40# K-55 LTC casing with FS @ 3478.97 feet. FC @ 3434.5 feet.

Cementing:

Lead: 1100 sks of 35/65 Poz C Yield = 2.06, Density = 12.6 ppg.  
Tail: 200 sks of Class C. Density = 14.8 ppg, yield = 1.32

Circulated 100 bbls/271 sks to surface. On 7/11/2012, tested intermediate casing to 1500 psi = OK

Drilled out cement 27.5 hours after cementing



Spud Date: 7/04/2012

Rig Release Date: 7/15/2012

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Charles K. Ahn TITLE EH&S/Regulatory Manager DATE 8/09/2012

Type or print name Charles K. Ahn E-mail address: cahn@rkixp.com PHONE: 405-996-5771  
For State Use Only

APPROVED BY: JD Wade TITLE Dist. PS Supervisor DATE 8/16/12  
Conditions of Approval (if any):