

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED
OMB NO. 1004-0135
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

5. Lease Serial No.
NMNM102917

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No

SUBMIT IN TRIPLICATE - Other instructions on reverse side.

1. Type of Well
 Oil Well Gas Well Other

8. Well Name and No
RDX FEDERAL 21 33

2. Name of Operator
RKI EXPLORATION & PROD LLC Contact: CHARLES K AHN
E-Mail: cahn@rkixp.com

9. API Well No
30-015-39940-00-X1

3a. Address
3817 NW EXPRESSWAY SUITE 950
OKLAHOMA CITY, OK 73112

3b. Phone No (include area code)
Ph: 405-996-5771
Fx: 405-996-5772

10. Field and Pool, or Exploratory
BRUSHY DRAW

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Sec 21 T26S R30E NWSE 2310FSL 2210FEL

11. County or Parish, and State
EDDY COUNTY, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize <input type="checkbox"/> Deepen <input type="checkbox"/> Production (Start/Resume) <input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing <input type="checkbox"/> Fracture Treat <input type="checkbox"/> Reclamation <input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair <input type="checkbox"/> New Construction <input type="checkbox"/> Recomplete <input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans <input checked="" type="checkbox"/> Plug and Abandon <input type="checkbox"/> Temporarily Abandon
	<input type="checkbox"/> Convert to Injection <input type="checkbox"/> Plug Back <input type="checkbox"/> Water Disposal

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

While drilling the 17 ? inch surface hole at 653 feet, returns were lost. While attempting to regain circulation, the pipe became stuck and could not be recovered. Top of the the fish is at 418 feet, bottom of fish is at 600 feet.

It is proposed to spot 1,000 sx at the top of the fish in two 500 sx increments. The first plug will be tagged before spotting the second plug. A surface plug will also be placed.

REFER TO ATTACHED DIAGRAM (WELL BORE).



14. I hereby certify that the foregoing is true and correct.

**Electronic Submission #138755 verified by the BLM Well Information System
For RKI EXPLORATION & PROD LLC, sent to the Carlsbad
Committed to AFMSS for processing by KURT SIMMONS on 05/24/2012 (12KMS2113SE)**

Name (Printed/Typed) CHARLES K AHN	Title HS&E/REGULATORY MANAGER
Signature (Electronic Submission)	Date 05/22/2012

THIS SPACE FOR FEDERAL OR STATE OFFICE USE


Approved By <u>WESLEY INGRAM</u>	Title <u>PETROLEUM ENGINEER</u>	Date <u>10/13/2012</u>
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		Office <u>Carlsbad</u>

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

At 10/17/2012

Accepted for record
NMOCD

FOOTAGE TVD	418'	17 1/2" HOLE		WELL	RDX FED 21-33	LOCATION	SURF 2.210' FEL & 2.310' FSL SECTION 1-23S-29E EDDY COUNTY, NM																																																																
				600'	TD	<table border="1"> <thead> <tr> <th colspan="6">SURFACE CASING</th> </tr> <tr> <th>ITEM</th> <th>SET AT</th> <th></th> <th></th> <th>WT</th> <th>GRD THRD</th> </tr> </thead> <tbody> <tr> <td colspan="6">CEMENTED TO SURFACE</td> </tr> <tr> <th colspan="6">INTERMEDIATE CASING</th> </tr> <tr> <th>ITEM</th> <th>SET AT</th> <th></th> <th></th> <th>WT</th> <th>GRD THRD</th> </tr> <tr> <td colspan="6">INTERMEDIATE CASING</td> </tr> <tr> <th>ITEM</th> <th>SET AT</th> <th>TOP AT</th> <th></th> <th>WT</th> <th>GRD THRD</th> </tr> <tr> <td colspan="6">LINER</td> </tr> <tr> <th>ITEM</th> <th>SET AT</th> <th></th> <th></th> <th>WT</th> <th>GRD THRD</th> </tr> <tr> <td colspan="6">TUBING</td> </tr> <tr> <th>ITEM</th> <th>SET AT</th> <th></th> <th></th> <th>WT</th> <th>GRD THRD</th> </tr> </tbody> </table>				SURFACE CASING						ITEM	SET AT			WT	GRD THRD	CEMENTED TO SURFACE						INTERMEDIATE CASING						ITEM	SET AT			WT	GRD THRD	INTERMEDIATE CASING						ITEM	SET AT	TOP AT		WT	GRD THRD	LINER						ITEM	SET AT			WT	GRD THRD	TUBING						ITEM	SET AT
SURFACE CASING																																																																							
ITEM	SET AT			WT	GRD THRD																																																																		
CEMENTED TO SURFACE																																																																							
INTERMEDIATE CASING																																																																							
ITEM	SET AT			WT	GRD THRD																																																																		
INTERMEDIATE CASING																																																																							
ITEM	SET AT	TOP AT		WT	GRD THRD																																																																		
LINER																																																																							
ITEM	SET AT			WT	GRD THRD																																																																		
TUBING																																																																							
ITEM	SET AT			WT	GRD THRD																																																																		
653'				<p>20" CONDUCTOR SET AT 60'</p> <p>FISH CONSIST OF THE FOLLOWING.</p> <table> <tr> <td>TOP OF FISH IS AT</td> <td>418'</td> </tr> <tr> <td>BOTTOM OF FISH IS AT</td> <td>600'</td> </tr> <tr> <td>2 - 6" DC'S</td> <td>61 95</td> </tr> <tr> <td>X-OVER</td> <td>3 15</td> </tr> <tr> <td>2 - 8" DC'S</td> <td>60 94</td> </tr> <tr> <td>ROLLER REAMER</td> <td>9 00</td> </tr> <tr> <td>SHOCK SUB</td> <td>12 87</td> </tr> <tr> <td>DRILLING MOTOR</td> <td>30 88</td> </tr> <tr> <td>SUB</td> <td>1 54</td> </tr> <tr> <td>BIT</td> <td>2 00</td> </tr> <tr> <td>TOTAL</td> <td>182 33</td> </tr> </table>				TOP OF FISH IS AT	418'	BOTTOM OF FISH IS AT	600'	2 - 6" DC'S	61 95	X-OVER	3 15	2 - 8" DC'S	60 94	ROLLER REAMER	9 00	SHOCK SUB	12 87	DRILLING MOTOR	30 88	SUB	1 54	BIT	2 00	TOTAL	182 33																																										
TOP OF FISH IS AT	418'																																																																						
BOTTOM OF FISH IS AT	600'																																																																						
2 - 6" DC'S	61 95																																																																						
X-OVER	3 15																																																																						
2 - 8" DC'S	60 94																																																																						
ROLLER REAMER	9 00																																																																						
SHOCK SUB	12 87																																																																						
DRILLING MOTOR	30 88																																																																						
SUB	1 54																																																																						
BIT	2 00																																																																						
TOTAL	182 33																																																																						