

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED OMB NO 1004-0135 Expires. July 31, 2010

Lease Serial No NMNM2748

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					NMNM2748 6. If Indian, Allottee or Tribe Name			
								SUBMIT IN TRIPLICATE - Other instructions on reverse side.
1. Type of Well					8. Well Name and No.			
Oil Well Gas Well Other					GISSLER B 70			
2 Name of Operator Contact. LESLIE M GARVIS BURNETT OIL COMPANY INC E-Mail: lgarvis@burnettoil.com					9. API Well No 30-015-39209-00-S1			
3a Address 3b. Phone No. (include area code) 801 CHERRY STREET UNIT 9 Ph: 817-332-5108 Ext: 6326 FORT WORTH, TX. 76102-6881 Ph: 817-332-5108 Ext: 6326					10. Field and Pool, or Exploratory LOCO HILLS			
4. Location of Well (Footage, Sec., T., R, M., or Survey Description)					11 County or Parish, and State			
Sec 11 T17S R30E NESW Lot K 2210FSL 1750FWL					EDDY COUNTY, NM			
12. CHECK APPR	ROPRIATE BOX(ES) TO	INDICATE	NATURE OF	NOTICE, RE	EPORT, OR OTH	ER DATA	A	
TYPE OF SUBMISSION TYPE OF ACTION					'			
☐ Notice of Intent	□ Acidize	□ Deep	□ Deepen		□ Production (Start/Resume)		☐ Water Shut-Off	
_	☐ Alter Casing	. 🛮 Frac	Fracture Treat		☐ Reclamation		ell Integrity	
Subsequent Report	☐ Casing Repair	□ New	□ New Construction □ Reco		nplete		her	
☐ Final Abandonment Notice	☐ Change Plans ☐ P		and Abandon	☐ Tempora	☐ Temporarily Abandon			
	Convert to Injection		Back	k Water Disposal				
testing has been completed. Final Abdetermined that the site is ready for fi 6/6/12 - PERFORATE 23 INTE 5080', 5088', 5092', 5107', 512 6/7/12 - SPOT 250 GAL 15% NEFE & 46 BALLSEALERS.	inal inspection.) ERVALS 2 SPF @ 4934', 20', 5129', 5141', 5144', 51	4974', 4978', 148', 5157', 5	4981', 4993', 4 160', 5172', 51	1997', 5015', <u>!</u> 75', 5177'.	5076',		perator nas	
6/8/12 - SLICKWATER FRAC W 754,908 GALS SLICKWATER, 22,021# 100 MESH, 212,240#					40/70 SN.	REC	EIVED	
6/12/12 - INSTALLED 152 JTS 2 7/8" J-55 4808', SN 4809', ESP 4861', DESANDER 4865', J-55 4929', RDMO 23 BO, 1034 BLW, 94 MCF, 895 BHP, 1952 FLAP, 0# CSG, 250# TBG,					65 BLWTR 17	NOV	1 3 2012	
			10 rede 11/15/	r MMOCI		MOC	D ARTES!	
14. Thereby certify that the foregoing is Com Name (Printed/Typed) LESLIE M	#1 Electronic Submission For BURNETT (Imitted to AFMSS for proce	OIL COMPAN	Y IŃC, sent to ti RT SIMMONS on	he Carlsbad 10/29/2012 (1	•			
Traine(17)mea Typeay ELOCIE IV	IOARVIO		THE KEGO	LATORT CO	ORDINATOR			
Signature (Electronic S	Submission)		Date 10/23/2	2012)		
, '	THIS SPACE FO	R FEDERA	L OR STATE	OFFICE US	SE			
Approved By ACCEPTED			JAMES A TitleSUPERV				Date 11/10/2012	
Conditions of approval, if any, are attaches certify that the applicant holds legal or equivalent would entitle the applicant to condu	Office Carlsba			•				
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s	U.S.C. Section 1212, make it a statements or representations as	crime for any pe to any matter w	erson knowingly ar	nd willfully to m	ake to any department	or agency of	of the United	

Additional data for EC transaction #156088 that would not fit on the form

32. Additional remarks, continued

HR TEST

6/25/12 - 24 HR TEST: 145 BO, 950 BLW, 210 MCF, 271 BHP, 510' FLAP, 50# CSG, 250# TBG, 4,095 BLWTR.

8/2/12 - PERFORATE 12 INTERVALS 2 SPF @ 4555', 4564', 4576', 4583', 4592', 4597', 4802', 4807', 4813', 4833', 4839', 4861'. PERFORATE 18 INTERVALS 1 SPF @ 4614' ,4623', 4632', 4653', 4662', 4672', 4692', 4702', 4717', 4726', 4738', 4745', 4753', 4761', 4769', 4779', 4791', 4796'.

8/3/12 - SPOT 250 GAL OF 15% NEFE ACID ACROSS PERFS, PULL PKR ABOVE PERFS, SET PKR @ 4439', ACIDIZE W 2500 GAL 15% NEFE & 84 BALL SEALERS.

8/6/12 - ARR ON LCTN & RU CUDD, OPEN UP FRAC VALVE & CSG HAS 0 PSI, FRAC DN 7", 23#,J55 CSG W 796,236 GAL OF SLICKWATER, 19,918# 100 MESH, 233,429# 40/70 SN.

8/8/12 - INSTALLED: 140 JTS 2 7/8" J-55 TBG 4430', SN 4431', ESP 4483', DESANDER 4487', 2 JTS 2 7/8" TAILPIPE 4550'. 0 BO, 535 BLW, 0 MCF, 698 BHP, 1612' FLAP, 18,223 BLWTR, 0# CSG, 17 HR TEST.

8/10/12 - 55 BO, 890 BLW, 85 MCF, 586 BHP, 1168' FLAP, 16.452 BLWTR, 80# CSG, 250# TBG, 58 HZ,

8/23/12 185 BO, 957 BLW, 258 MCF, 203 BHP, 284' FLAP, 863 BLWTR, 80# CSG, 250# TBG, 58 HZ.