

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. DIV-Dist. 2
1311 W. Grand Avenue
Albuquerque, NM 88210

FORM APPROVED
OMB NO. 1004-0137
Expires March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on reverse side

RECEIVED

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Stephens & Johnson Operating Co.

3a. Address

P.O. Box 2249 Wichita Falls TX 76307-2249

3b. Phone No. (include area code)

(940) 723-2166

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec. 13, T19S, R28E
330' FSL & 1291' FWL

5. Lease Serial No.

LC-069107 STATE

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8910169240

East Millman Pool Unit

8. Well Name and No.

East Millman Tr 4 #16

Pool Unit

9. API Well No.

30-015-33944

10. Field and Pool, or Exploratory Area

Millman ON-GB-SA, East

11. County or Parish, State

Eddy NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- | | | | |
|---|---|--|--|
| <input type="checkbox"/> Acidize | <input type="checkbox"/> Deepen | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off |
| <input type="checkbox"/> Alter Casing | <input type="checkbox"/> Fracture Treat | <input type="checkbox"/> Reclamation | <input type="checkbox"/> Well Integrity |
| <input type="checkbox"/> Casing Repair | <input type="checkbox"/> New Construction | <input type="checkbox"/> Recomplete | <input type="checkbox"/> Other <u>New Well</u> |
| <input type="checkbox"/> Change Plans | <input type="checkbox"/> Plug and Abandon | <input type="checkbox"/> Temporarily Abandon | <u>Apr 2005 (State)</u> |
| <input type="checkbox"/> Convert to Injection | <input type="checkbox"/> Plug Back | <input type="checkbox"/> Water Disposal | |

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

SEE ATTACHED

Note: Well is a State well; however, Tract 6 is Federal. Therefore, we request BLM update their database to include this well.

ACCEPTED FOR RECORD

MAY 12 2005

ALEXIS C. SWOBODA
PETROLEUM ENGINEER

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Devire D. Crabb

Title

Production Analyst

Date May 2, 2005

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

East Millman Pool Unit Tr 4 #16

API # 30-015-33944

Eddy County, New Mexico

1. Spudded 12 1/4" hole 2:00 PM 3-21-05. Drilled to 330' KB & ran 7 jts 8 5/8" 24#/ft. surface csg and cemented w/250 sx of cement. Cement circulated to surface (circulate 75 sx to pit). WOC - 18 hrs. Pressure test BOP and 8 5/8" surface casing to 1,000 psig for 30 minutes. Held OK.
2. Drilled 7 7/8" hole to 2673'. Ran 68 jts 5 1/2", 15.50#/ft. csg, set @ 2664' KB. Cemented w/800 sx of cement. Plug down @ 6:10 AM 3-27-05. Cement circulated to surface (circulate 175 sx to pit).
3. Test 5 1/2" production casing to 1,500 psig for 30 minutes. Held OK. Perforated Grayburg formation one shot at each of the following depths: 2342', 2346', 2350', 2354', 2380', 2385', 2389', 2395', 2399', 2403', 2407', 2411', 2415', 2419', 2442', 2445', 2448', 2531', 2534', 2537', 2612', 2615', 2618', 2621' and 2626'.
4. On 4-5-05 acidized perforations w/3,000 gals 15% NEFE.
5. On 4-6-05 sand fraced perforations w/103,500 gals 10 lb brine water, 20,000 lbs of BJ LiteProp 125, and 5,000 lbs Super LC 16/30 sand.