

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-40522
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Devon Energy Production Company, L.P.		6. State Oil & Gas Lease No.
3. Address of Operator 333 W. Sheridan, Oklahoma City, OK 73102 (405) 552-7970		7. Lease Name or Unit Agreement Name Lone Tree Draw 13 State Com
4. Well Location Unit Letter <u>B</u> : <u>150</u> feet from the <u>North</u> line and <u>2390</u> feet from the <u>East</u> line Section <u>13</u> Township <u>21S</u> Range <u>27E</u> NMPM Eddy, County		8. Well Number 4H
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 6137
		10. Pool name or Wildcat Carlsbad, Delaware

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Change to original APD ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Devon Energy Production Company, LP respectfully requests to add a pilot hole to the subject well (attached drilling plan).

Thank You!

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Erin Workman TITLE: Regulatory Compliance Associate DATE: 11/28/12

Type or print name: Erin Workman E-mail address: Erin.workman@dvn.com PHONE: 405-552-7970

For State Use Only

APPROVED BY: T.C. Shivers TITLE: Geologist DATE: 12/4/2012

Conditions of Approval (if any):

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-40522
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Lone Tree Draw 13 State Com
8. Well Number 4H
9. OGRID Number 6137
10. Pool name or Wildcat Carlsbad, Delaware

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Devon Energy Production Company, L.P.	
3. Address of Operator 333 W. Sheridan, Oklahoma City, OK 73102 (405) 552-7970	
4. Well Location Unit Letter <u>B</u> : <u>150</u> feet from the <u>North</u> line and <u>2390</u> feet from the <u>East</u> line Section <u>13</u> Township <u>21S</u> Range <u>27E</u> NMPM Eddy, County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3299'GL	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Per NMOCD request for previous sundry:

DATED 11/28/2012 REQUESTING PLOT HOLD.

20 inch conductor to 80 feet depth setting.

CMT TO SURFACE

CSG PROGRAM:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Erin Workman TITLE: Regulatory Compliance Associate DATE: 12-2-12
Type or print name: Erin Workman E-mail address: Erin.workman@dvn.com PHONE: 405-552-7970

For State Use Only
APPROVED BY: T. C. Shepard TITLE: Geologist DATE: 12/4/2012
Conditions of Approval (if any):

Lone Tree Draw 13 State 4H- APD DRILLING PLAN
JSL 11-28-12

Casing Program

<u>Hole Size</u>	<u>Hole Interval</u>	<u>OD Csg</u>	<u>Casing Interval</u>	<u>Weight</u>	<u>Collar</u>	<u>Grade</u>
17-1/2"	0 – 350	13-3/8"	0 – 300	48#	STC	H-40
12-1/4"	350 – 2,600	9-5/8"	0 – 2,600	40#	LTC	J-55
8-3/4"	2,600 – 4,200	5-1/2"	0 – 4,200	17#	LTC	HCP-110
8-3/4"	4,200 – 9,568	5-1/2"	4,200 – 9,568	17#	BTC	HCP-110

Pilot hole TD: 7,950'

Max TVD in lateral: 5,002'

Mud Program:

<u>Depth</u>	<u>Mud Wt.</u>	<u>Visc.</u>	<u>Fluid Loss</u>	<u>Type System</u>
0 – 350	8.4 – 9.0	30 – 34	N/C	FW
350 – 2,600	9.6 – 10.0	28 – 32	N/C	Brine
2,600 – 9,568	8.6 – 9.0	28 – 32	N/C-12	FW

Pressure Control Equipment:

The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the surface casing shoe.

The BOP system used to drill the production hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the intermediate casing shoe.

The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.

Cementing Program

13-3/8" Surface Casing

FLUID SPECIFICATIONS

Spacer

20.0 bbls Fresh Water @ 8.34 ppg

<u>FLUID</u>	<u>VOLUME CU-FT</u>	<u>VOLUME FACTOR</u>	<u>AMOUNT AND TYPE OF CEMENT</u>
Lead Slurry	2036	1.97	= 1035 sacks (35:65) Poz (Fly Ash) Class C Cement + 5% bwow Sodium Chloride + 0.125 lbs/sack Cello Flake + 4% bwoc Bentonite + 1% bwoc Sodium Metasilicate + 5% bwoc MPA-5 + 101.3% Fresh Water
Tail Slurry	534	1.34	= 400 sacks Class C Cement + 1% bwoc Calcium Chloride + 0.125 lbs/sack Cello Flake + 56.2% Fresh Water

Displacement

280.3 bbls Mud @ 9 ppg

CEMENT PROPERTIES

	<u>SLURRY NO.1</u>	<u>SLURRY NO.2</u>
Slurry Weight (ppg)	12.80	14.80
Slurry Yield (cf/sack)	1.97	1.34
Amount of Mix Water (gps)	10.56	6.34
Estimated Pumping Time - 70 BC (HH:MM)	3:30	2:30

COMPRESSIVE STRENGTH

72 hrs @ 80 ° F (psi)		2700
7 hrs @ 93 ° F (psi)		500
12 hrs @ 93 ° F (psi)	350	1000
17 hrs @ 93 ° F (psi)	500	
24 hrs @ 93 ° F (psi)	750	1600

ACTUAL CEMENT VOLUMES MAY VARY BASED ON FLUID CALIPER.

9-5/8" Intermediate

FLUID SPECIFICATIONS

Spacer

20.0 bbls Fresh Water @ 8.34 ppg

<u>FLUID</u>	<u>VOLUME CU-FT</u>	<u>VOLUME FACTOR</u>	<u>AMOUNT AND TYPE OF CEMENT</u>
Lead Slurry	1239	/ 1.73	= 715 sacks (60:40) Poz (Fly Ash):Class C Cement + 5% bwow Sodium Chloride + 0.125 lbs/sack Cello Flake + 3 lbs/sack LCM-1 + 1% bwoc Sodium Metasilicate + 89.7% Fresh Water
Tail Slurry	413	/ 1.38	= 300 sacks (60:40) Poz (Fly Ash):Class C Cement + 5% bwow Sodium Chloride + 0.125 lbs/sack Cello Flake + 0.4% bwoc Sodium Metasilicate + 4% bwoc MPA-5 + 65.5% Fresh Water

Displacement

239.6 bbls Mud @ 10 ppg

CEMENT PROPERTIES

	<u>SLURRY NO.1</u>	<u>SLURRY NO.2</u>
Slurry Weight (ppg)	12.60	13.80
Slurry Yield (cf/sack)	1.73	1.38
Amount of Mix Water (gps)	8.82	6.44
Estimated Pumping Time - 70 BC (HH:MM)	3:30	2:30
<u>COMPRESSIVE STRENGTH</u>		
12 hrs @ 90 ° F (psi)	275	
24 hrs @ 90 ° F (psi)	875	
72 hrs @ 90 ° F (psi)	1600	
8 hrs @ 112 ° F (psi)		500
12 hrs @ 112 ° F (psi)		1400
24 hrs @ 112 ° F (psi)		2400

ACTUAL CEMENT VOLUMES MAY VARY BASED ON CALIPER.

5-1/2" Production-Single Stage

FLUID SPECIFICATIONS

Spacer	50.0 bbls Fresh Water @ 8.34 ppg
Spacer	1,500.0 gals Mud Clean II @ 8.45 ppg
Spacer	10.0 bbls Fresh Water @ 8.34 ppg
Spacer	40.0 bbls SealBond @ 8.75 ppg

<u>FLUID</u>	<u>VOLUME CU-FT</u>	<u>VOLUME FACTOR</u>	<u>AMOUNT AND TYPE OF CEMENT</u>
1st Lead Slurry	1798	1 2.3	= 785 sacks (50:50) Poz (Fly Ash):Class H Cement + 0.5% bwoc FL-52 + 0.3% bwoc ASA-301 + 10% bwoc Bentonite + 0.1% bwoc R-21 + 130.7% Fresh Water
Lead Slurry	1377	1 2	= 690 sacks (35:65) Poz (Fly Ash):Class H Cement + 3% bwow Sodium Chloride + 0.125 lbs/sack Cello Flake + 0.7% bwoc FL-52 + 6% bwoc Bentonite + 105.4% Fresh Water
Tail Slurry	1674	1 1.28	= 1310 sacks (50:50) Poz (Fly Ash):Class H Cement + 5% bwow Sodium Chloride + 0.3% bwoc CD-32 + 0.5% bwoc FL-25 + 0.5% bwoc FL-52 + 0.4% bwoc Sodium Metasilicate + 57.2% Fresh Water
Displacement			331.7 bbls Displacement Fluid

CEMENT PROPERTIES

	<u>SLURRY NO.1</u>	<u>SLURRY NO.2</u>	<u>SLURRY NO.3</u>
Slurry Weight (ppg)	11.80	12.50	14.20
Slurry Yield (cf/sack)	2.30	2.00	1.28
Amount of Mix Water (gps)	13.16	10.99	5.76
Estimated Pumping Time - 70 BC (HH:MM)	4:00	5:00	3:30
Free Water (mls) @ ° F @ 90 ° Angle			0.0
Fluid Loss (cc/30min) at 1000 psi and ° F			50.0

COMPRESSIVE STRENGTH

12 hrs @ 130 ° F (psi)	150		
24 hrs @ 130 ° F (psi)	250		
72 hrs @ 130 ° F (psi)	350		
12 hrs @ 140 ° F (psi)		175	
24 hrs @ 140 ° F (psi)		250	
72 hrs @ 140 ° F (psi)		700	
12 hrs @ 150 ° F (psi)			250
24 hrs @ 150 ° F (psi)			1500
72 hrs @ 150 ° F (psi)			2000

TOC for All Strings:

Surface:	0'
Intermediate:	0'
Production:	2,100'

ACTUAL CEMENT VOLUMES WILL BE ADJUSTED BASED ON FLUID CALIPER AND CALIPER LOG DATA