Office State of New Mexico	Form C-103
District I Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240	October 13, 2009 WELL API NO.
District II 1301 W. Grand Ave., Artesia, NM 88210 BBS OGIL CONSERVATION DIVISION	30-015-10843
District III 1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 0-6 2013 Santa Ea NIM 87505	STATE FEE 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	6. State Oil & Gas Lease No.
SUNDRY NOTICESIAND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	Cotton Draw Unit
1. Type of Well: Oil Well Gas Well Other SWD_699	8. Well Number 65
2. Name of Operator DEVON ENERGY PRODUCTION CO. LP	9. OGRID Number 6137
3. Address of Operator PO BOX 250, ARTESIA, NM 88211	10. Pool name or Wildcat  RADUCA Cherry Cym
4. Well Location	V 0
Unit Letter: G; 1980 feet from the NORTH line and 1980 feet from the EAST line Eddy Section 2 Township 25S Range 31E NMPM County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3475' GL	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	<del>_</del>
TEMPORARILY ABANDON	<del></del>
DOWNHOLE COMMINGLE	
	,
OTHER: REPAIR TOP JOINT TUBING OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
Devon energy respectfully request permission to perform the following work:	
Move in rig up well service unit     Nigels down wellbood Nigels up bleve out asserter.	
<ul> <li>Nipple down wellhead. Nipple up blow out preventer</li> <li>Pull and replace top joint of 3-1/2" IPC (Internally Plastic Coated tbg.)</li> </ul>	
<ul> <li>Pull and replace top joint of 3-1/2" IPC (Internally Plastic Coated tbg.)</li> <li>Latch back onto on-off tool</li> </ul>	
Nipple down Blow out preventer. Nipple up wellhead	
• Load annulus w/2% KCL containing packer fluid	
<ul> <li>MIT annulus to 500 psi for 30 min with chart recorder and NMOCD witness</li> <li>Rig down well service unit</li> </ul>	
Upon NMOCD approval, return well to injection	
	•
Spud Date: Rig Release Date:	
I hereby certify that the information above is true and complete to the best of my knowledge	e and belief.
SIGNATURE SIGNATURE FIELD ADM. SUPPORT	
DATE: 01/23/2013	•
Type or print name: Gracie Bustamante E-mail address: Gracie.Bustamante@dvn	.com PHONE: 575-746-5561
For State Use Only	21131121 373 F1013301
ADDROVED DV. D. MARIA LASTA	34.00
APPROVED BY: Luffer / New TITLE COMPUTANCE OF	7.CE/C DATE &//3/13 11 12 12 12 12 12 12 12 12 12 12 12 12
The state of the s	international de la companya de la La companya de la co