

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised June 10, 2003

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-29294
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. K-952
7. Lease Name or Unit Agreement Name Todd 36A State
8. Well Number 16
9. OGRID Number 6137
10. Pool name or Wildcat Ingle Wells (Delaware)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Devon Energy Production Company, LP	
3. Address of Operator 20 North Broadway, Suite 1500, Oklahoma City, Oklahoma 73102	
4. Well Location Unit Letter <u>A</u> : 660' feet from the <u>North</u> line and 660' feet from the <u>East</u> line Section <u>36</u> Township <u>23S</u> Range <u>31E</u> Eddy County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3546' GL	

RECEIVED

SEP 21 2005

ARTESIA

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spot 280' cement plug. 6520'-6780' WCC TUG.

1. Set CIP at 6650'. Spot 50' cement on top. (note: see attached schemat for casing damage & fish in hole details)
2. Circulate hole with 9 ppg mud. 4185'
3. Spot 100' cement plug from 4350' to 4450'. (8-5/8" casing shoe at 4400')
4. Cut 5-1/2" casing at 3363'. POOH and lay down 5-1/2" casing. (note: TOC on 5-1/2" casing at 3463' by CBL)
5. Spot 150' cement plug from 3288' to 3438'.
6. Spot 100' cement plug from 806' to 906'. (13-3/8" casing shoe at 856') * 100' cement plug @ 1170'-1270' WCC TUG
7. Spot 60' cement plug to surface. Cut casings off 3' BGL and set dry hole marker. Clean location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronnie Slack

TITLE: Engineering Technician

DATE 9/19/05

Type or print name Ronnie G. Slack

E-mail address: Ronnie.Slack@dvn.com

Telephone No. 405-552-4615

(This space for State use)

APPROVED BY Phil Hawkins

TITLE Field Sup

DATE 9/29/05

Conditions of approval, if any:

If this work requires an earthen pit, a permit must be approved prior to construction of the pit(s).

Notify OCD 24 hrs. prior to any work done.

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: TODD 36A STATE #16

Field: INGLE WELLS

Location: 660 FNL & 660' FEL; SEC 36-T23S-R31E

County: EDDY

State: NM

Elevation: 3546' GL

Spud Date: 8/18/1997

Compl Date: 9/25/1997

API#: 30-015-29294

Prepared by: Ronnie Slack

Date: 09/19/05

Rev:

PROPOSED PLUG & ABANDONMENT

17-1/2" hole

13-3/8", 48#, H40, ST&C, @ 856'

Cmt'd w/700 sx

Formation Tops:

Rustler 890'

Salado 1223'

Delaware 4518'

Cherry Canyon 5412'

Bone Spring 8374'

TOC @ 3463' (CBL)

11" hole

8-5/8", 32#, J55, ST&C, @ 4400'

Cmt'd w/1240 sx

Reduced ID 4-3/4". A true 4-3/4" swage will go but drags in & out at 6685'

There was a 12' piece of 5-1/2" casing cut with shoe & recovered 6712' - 6724' (??)

Top of 2-7/8" tubing fish @ 6727' with split tubing. Also possible slivers of casing. 28' of tubing to next collar. Last thing in hole was a 4-1/2" shoe, dressed 4-3/4" smooth with 2-7/8" ID. Wad at top of fish.

DELAWARE

(Cmplt'd 9/25/97)

8151' - 8158'

8200' - 8216'

8261' - 8288'

7-7/8" Hole

5-1/2", 15.5# & 17#, J55, LT&C, @ 8677'

Cmt'd w/600sx

9 ppg mud

9 ppg mud

9 ppg mud

9 ppg mud

Proposed:

Spot 60' surface cement plug

Proposed:

Spot 100' cement plug from 806' - 906' WOC & Tag

Proposed:

Cut 5-1/2" casing @ 3363'. POOH w/casing
Spot 150' cement plug from 3288' - 3438' WOC & Tag

Proposed:

Spot 100' cement plug from 4350' - 4450' WOC & Tag

Proposed:

Set CIBP @ 6650'
Cap w/50' cement on top. WOC & Tag.

Spot 280' cement plug from 6520' - 6780' WOC TAG

Freepoint: Tubing stuck at 6735'. 1-16-01

Tubing cut @ 7937'

Tubing anchor @ 7954'

SN @ 8350'
EOT @ 8413'

PBTD @ 8613'

TD @ 8700'

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: TODD 36A STATE #16		Field: INGLE WELLS	
Location: 660 FNL & 660' FEL; SEC 36-T23S-R31E		County: EDDY	State: NM
Elevation: 3546' GL		Spud Date: 8/18/1997	Compl Date: 9/25/1997
API#: 30-015-29294	Prepared by: Ronnie Slack	Date: 09/06/05	Rev:

■ CURRENT

17-1/2" hole
13-3/8", 48#, H40, ST&C, @ 856'
 Cmt'd w/700 sx

TOC @ 3463' (CBL)

11" hole
8-5/8", 32#, J55, ST&C, @ 4400'
 Cmt'd w/1240 sx

1-9-01: RIH w/202 Jts 2-7/8" tubing and 3', 2-7/8" perf'd sub. EOT @ 6331'

Reduced ID 4-3/4". A true 4-3/4" swage will go but drags in & out at 6685'

Top of 2-7/8" tubing fish @ 6727' with split tubing. Also possible slivers of casing. 28' of tubing to next collar. Last thing in hole was a 4-1/2" shoe, dressed 4-3/4" smooth with 2-7/8" ID. Wad at top of fish.

There was a 12' piece of 5-1/2" casing cut with shoe & recovered 6712' - 6724' (??)

Freepoint: Tubing stuck at 6735'. 1-16-01

Tubing cut @ 7937'

Tubing anchor @ 7954'

DELAWARE

(Cmt'd 9/25/97)

8151'- 8158'
 8200'- 8216'
 8261'- 8288'

SN @ 8350'
 EOT @ 8413'

7-7/8" Hole
5-1/2", 15.5# & 17#, J55, LT&C, @ 8677'
 Cmt'd w/600sx

PBTD @ 8613'

TD @ 8700'

