

Submit 1 Copy To Appropriate District Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-38292

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

RDX 16

8. Well Number
10H

9. OGRID Number
246289

10. Pool name or Wildcat
Wildcat (Bone Spring)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
RKI Exploration & Production, LLC

3. Address of Operator
210 Park Avenue, Suite 900, Oklahoma City, OK 73102

4. Well Location

Unit Letter B : 330 feet from the North line and 2110 feet from the East line
Section 16 Township 26S Range 30E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3094 feet GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spudded the well on 9/17/2012. On 9/18/2012, drilled 17-1/2 inch hole to 921 feet. Ran 21 joints of 13-3/8 inch 54.5# J-55 STC casing with FS @ 900 feet. FC @ 856 feet.

Cementing:

Lead: 675 sks of Class C (C+4%PF20+2%PF1+0.125#/SKPF29+0.25#/SKPF46). Yield = 1.75, Density = 13.5 ppg.
Tail: 200 sks of Class C (C-NEAT). Density = 14.8 ppg, yield = 1.34

Circulated 75 bbls/240 sks to surface. On 9/20/2012, tested surface casing to 1500 psi = OK

Drilled out cement 32 hours after cementing

Spud Date: 9/17/2012

Rig Release Date: 10/09/2012

RECEIVED

FEB 14 2013

NM OGD ARTESIA

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE EH&S/Regulatory Manager

DATE 2/12/2013

Type or print name Charles K. Ahn

E-mail address: cahn@rkixp.com


PHONE: 405-996-5771

For State Use Only

APPROVED BY



TITLE



DATE

2/14/13

Conditions of Approval (if any):

gmo