

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-39525
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Mewbourne Oil Company		6. State Oil & Gas Lease No.
3. Address of Operator PO Box 5270 Hobbs, NM 88241		7. Lease Name or Unit Agreement Name State B 33 EH Com
4. Well Location Unit Letter E : 2260 feet from the North line and 330 feet from the West line Section 33 Township 19S Range 25E NMPM Eddy County.		8. Well Number 1H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3495 GL		9. OGRID Number 14744
		10. Pool name or Wildcat North Seven Rivers Glorieta; Yeso 97565

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒


OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

02/22/13 TD'd 8 3/4" hole @ 2784'. Ran 2784' of 7" 26# J55 BT&C & LT&C Csg. Cemented with 150 sks BJ Lite Class C (35:65:6) with additives. Mixed @ 12.5 /g w/ 2.05 yd. Tail with 300 sks Class C w/1% CaCl₂. Mixed @ 12.5 #/g w/ 2.05 yd. Plug down @ 12:15 PM 02/22/13. Circ 82 sks of cmt to the pit. At 3:00 A.M. 02/23/13, tested BOPE & csg to 1500# for 30 min, held OK. Drilled out with 6 1/8" bit.

Spud Date: 02/16/2013

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 02/26/13

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: [Signature] TITLE Dr. J. Spen DATE 3/6/13
Conditions of Approval (if any):