Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED |
APR 1.6 2013 | \

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-entertail OCD ARTES abandoned well. Use form 3160-3 (APD) for such proposals.					NMLC061634B 6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No.	
					0.11/11/11	
1. Type of Well Soil Well Gas Well Other					8. Well Name and No. PLU PHANTOM BANKS 20-25-31 1H	
2. Name of Operator Contact: KATY HOLSTER BOPCO LP E-Mail: keholster@basspet.com					9. API Well No. 30-015-40764	
3a. Address	o. (include area code)	· · · · · · · · · · · · · · · · · · ·	10. Field and Pool, or Exploratory			
PO BOX 2760 Ph: 432 MIDLAND, TX 79702					NMNM71076X	Exploratory
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, and State	
Sec 20 T25S R31E Mer NMP 32.122625 N Lat, 103.806089		_	EDDY COUNTY COUNTY, NM			
12. CHECK APPI	ROPRIATE BOX(ES) TO	O INDICATE	E NATURE OF N	NOTICE, R	EPORT, OR OTHE	R DATA
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent	☐ Acidize	Deepen □		☐ Product	tion (Start/Resume)	☐ Water Shut-Off
_	☐ Alter Casing	□ Frac	cture Treat		ation	☐ Well Integrity
☐ Subsequent Report	□ Casing Repair	_	v Construction	□ Recomple		☐ Other
☐ Final Abandonment Notice	☐ Change Plans ☐ Convert to Injection	Plug and Abandon			Temporarily Abandon	
10 D 1 D 1 O 1 O 1 O 1 O	Plug Back Water					
If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi	ally or recomplete horizontally, it will be performed or provide operations. If the operation re bandonment Notices shall be fil	give subsurface the Bond No. o sults in a multip	locations and measu n file with BLM/BIA le completion or reco	ared and true vo A. Required su completion in a	ertical depths of all perting bsequent reports shall be new interval, a Form 316	ent markers and zones. filed within 30 days 0-4 shall be filed once
BOPCO, L.P. requests to make the following changes to the above captioned well:						
Deepen the 7-7/8" pilot hole to a depth of 11,000'. This will take us to the base of the 2nd Bone Spring at 10,960' plus 40' of rat hole for logging tools. A Smith Trackmaster openhole whipstock will not be used. A balanced cement plug will be pumped and set from 11,000' - 10,500'. Final cement volumes will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives @ 15.6 ppg, 1.18 cu ft/sk, 5.219 gal H20/sk. A second balanced cement plug will be set from 9,079' - 8,579' with a planned KOP of 8,979'. Final cement volumes will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives will be class "H" + additives will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives will be class "H" + additives will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives will be cla						
A second balanced cement plug will be set from 9,079' - 8,579' with a planned KOP of 8,979'. Final cement volumes will be based on no less than 30% over gauge hole. This plug will be Class "H" + additives @ 17.5 ppg, 0.94 cu ft/sk, 3.363 gal H20/sk.						
cement volumes will be based on no less than 30% over gauge hole. This plug will be Class "H" + 4/12/13 Or Si Nol Coffs Sill Sand: Accepted for record NMISCO CRIDGE 4/17/13						
14. I hereby certify that the foregoing is	Electronic Submission #	203673 verifie	d by the BLM Wel	II Informatio		
For BOPCO LP, sent to the Carlsbad Committed to AFMSS for processing by KURT SIMMONS				a NS on 04/08	/2013 ()	
Name(Printed/Typed) CHRISTOPHER W GIESE			Title DRILLIN	NG ENGINE	ER ADDOC	WED
Signature (Electronic Submission)			Date 04/05/20	013	APPRU	IVED
THIS SPACE FOR FEDERAL OR STATE OFFICE USE APR 1 2 2013						
					Dance 7	40000
Approved By	Title		BUREAU OF LAND	MANAGEMENT		
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to condu	Office	L	CARLSBAD FIE	LD OFFICE		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.