

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88249
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6111
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

RECEIVED

APR 29 2013

MOCD ARTESIA

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-38259

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
VB-835

7. Lease Name or Unit Agreement Name
Oscuro BBC State Com

8. Well Number
1H

9. OGRID Number
025575

10. Pool name or Wildcat
Willow Lake; Bone Spring, West

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location
Unit Letter E : 1980 feet from the North line and 330 feet from the West line
Unit Letter H : 1987 feet from the North line and 330 feet from the East line
Section 12 Township 25S Range 27E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3100'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETIONS ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Completion Operations ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/25/13 - NU BOP.

3/26/13 - Tagged DV tool at 4998', drilled out. Circulated hole clean. Tested casing to 3000 psi for 30 min, good. RIH to PBTD at 12,180'. Circulated and displaced hole with 285 bbls 3% KCL with corrosion inhibitor and scavengers.

3/27/13 - Ran CBL/GR/CCL from 8052' up to 1350' with 1000 psi.

3/31/13-4/9/13 - Perforated Bone Spring 8218'-12,170' (324). Acidized with 47,000g 15% HCL acid, frac with 3,327,051# 20/40 Premium White and 20/40 CRC.

4/12/13 - Cleaned out well down to 12,180'. 2-7/8" 6.4# L-80 tubing at 7106'.

Spud Date:

12/30/10

Rig Release Date:

3/10/13

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE Regulatory Reporting Supervisor DATE April 25, 2013

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED

BY:  TITLE Dr. J. E. Spence

DATE 4/25/2013

Conditions of Approval (if any):