· Form 3160-5 (November 1994)

M.M. C/i Cons. DIV-Dist. 2

UNITED STATES AND GRAND AVOITUE DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENTS AND 88210

FORM APPROVED OMB No. 1004-0135 Expires July 31, 1996

SUNDRY NOTICES AND REPORTS ON WELLS					NMLC 065347		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name			
SUBMIT IN TI	RIPLICATE - Other Instr	uctions on reverse	MECEIVED	7. If Unit or	CA/Agreement, Name	and/or No.	
1. Type of Well Oil Well Gas Well	[] Orber	OCT 0 5 2005		8. Well Name and No.			
	9	SOUNTESIA		Estill AD Federal No. 3			
2. Name of Operator		_		9. API Well			
Gruy Petroleum Management Co. 3a. Address		3b. Phone No. (include area code)		30-015-34162			
	972.401.3111		10. Field and Pool, or Exploratory Area				
P.O. Box 140907 Irving, TX 75014-0907 972.401.3111 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				White City Penn; (Gas)			
SHL: 1470' FSL & 1939' FEL Sec 19-T24S-R26E					11. County or Parish, State		
BHL: 1670' FNL & 1900'	FEL Sec 19-T24S-R26E			Eddy (County, NM		
12. CHECK A	PPROPRIATE BOX(ES) T	O INDICATE NATUI	RE OF NOTICE, RI	EPORT, OR	OTHER DATA		
TYPE OF SUBMISSION	SUBMISSION TYPE OF ACTION						
	Acidize	Deepen Deepen	Production (Start	/Resume)	☐ Water Shut-Off		
Notice of Intent	Alter Casing	Fracture Treat	Reclamation	,110001110,	☐ Well Integrity		
Subsequent Report	Casing Repair	New Construction	Recomplete		Other set surface	e &	
_	Change Plans	Plug and Abandon	Temporarily Ab	andon	intermediate c		
☐ Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal	anuon			
Class C + 2% Ca 09-11-05 Testes casing to 09-18-05 Reached TD of 1 CalSeal + 10#/b Ran temperature	Drilled 17-1/2" hole to 133'. aCl. Circulated 100sx to res o 1000psi for 15 minutes. 12-1/4" hole. Ran 50jts 9-5, bbl Gilsonite + 2% CaCl + 1/2 re survey to find TOC at 1300 310'. Pumped 200sx Premius	erve pit. WOC 18 hou: /8" 40# J-55 LTC casin 2#/bbl Flocele. Cemen D'. Pumped 200sx Pren	rs. g to 1920'. Cemento ted tail with 200sx I nium + 2% CaCl dow	ed with lead Premium Plu on backside o	1200sx Interfill C + as. No returns throu of 9-5/8", no return	10#/bbl ghout job s.	
	backside of 9-5/8" casing. F						
09-20-05 WOC 32 hours.	Tested 9-5/8" casing to 100	Opsi for 15 minutes.		ACCEP	OTEO FOR REC	:ORD	
14. I hereby certify that the foregoin Name (Printed/Typed)	ng is true and correct	Title					
Natalie Krueger		Reg Te	Reg Tech		OCT - 4 2005		
Signature	Karre	Date			001 - 4 <u>ce</u>oo		
<u> Natan</u>	THIS SOACE E	FOR FEDERAL OR ST	mber 29, 2005	 	LES BABYAK	ED.	
Approved by	inio grace r	Tid		- 	ROLEUM ENGINE	CK	
Conditions of approval, if any, are certify that the applicant holds lega which would entitle the applicant to a	al or equitable title to those right		fice				