

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-24761
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name CAVE POOL UNIT
8. Well Number #62
9. OGRID Number 14070
10. Pool name or Wildcat CAVE GB/SA
11. Elevation (Show whether DR, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
STATE OF NM formerly MARKS & GARNER

3. Address of Operator
811 S. FIRST ST. ARTESIA NM 88210

4. Well Location
Unit Letter **P** : **330** feet from the **SOUTH** line and **330** feet from the **EAST** line
Section **5** Township **17S** Range **29E** NMPM County **EDDY**

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL. ☐	CASING/CEMENT JOB ☐	
DOWNHOLE COMMINGLE ☐			
OTHER: ☐		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHED PLUGGING PROCEDURE

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Maley Brown

TITLE

Compliance Officer

DATE

3/22/2013

Type or print name
or State Use Only

E-mail address:

PHONE:

APPROVED BY:

TITLE

DATE

Conditions of Approval (if any):

JUN 18 2013

State of New Mexico formerly MARKS & GARNER PRODUCTION LTD CO.

LEASE NAME CAVE POOL UNIT # 62 API 30-0 15 - 24761

U.L. P Section 5 -T 17 S-R 29 E FROM 330 ~~N~~ / S L, 330 E / ~~N~~ L.

SPECIAL NOTE—Mud Laden Fluid will consist of 9.5# brine with 12.5# Salt Gel per BBL (25 sacks of gel/ per 100 BBLS Brine). All cement plugs will be 25 sacks of cement or 100', whichever is greater. **Unless otherwise specified in the approved procedure**, cement plugs shall consist of class "C" for depths to 7500'. Class "H" will be used for plugs deeper than 7500'.

1. MIRU plugging unit. Lay down production equipment.
2. Set CIBP @ 2282'. Circulate MLF. Spot 25 sxs cmt on CIBP.
3. ~~Perf~~/Spot 25 sxs cmt @ 1900'. If perf. ~~WOC & TAG~~.
4. ~~Perf~~/Spot @ 386'. ~~Set~~/Spot 40 sxs cmt or w/ sufficient volume to circ cmt to surface inside/~~outside~~ of csg strings.
5. Cutoff wellhead and anchors, install marker.

-----SPECIAL NOTES-----

3/31/1984 1/2 bph WATER FLOW @ 1852'

PLUGGING & ABANDONMENT WORKSHEET

OPERATOR STATE OF NM formerly MARKS: GARNER
LEASENAME CAVE POOL UNIT

WELL # 62
SECT 5 TWN 17S RNG 29E
FROM 330 W/S/L 330 E/W/L
TD: 2700' FORMATION @ TD
PBSD: FORMATION @ PBSD

	SIZE	SET @	TOC	TOC DETERMINED BY	
SURFACE	8 5/8	336	SURF		
INTMED 1					
INTMED 2					
PROD	5 1/2	2700	SURF.		
	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					
CUT & PULL @				TOP - BOTTOM	
INTMED 1			PERFS		-
INTMED 2			OPENHOLE		-
PROD					

* REQUIRED PLUGS DISTRICT I *

RUSTLER (ANYTD)	
YATES	
QUEEN	
GRAYBURG	
SAN ANDRES	
CAPTAN REEF	
DELAWARE	
BELL CANYON	
CHEERY CANYON	
BELSHY CANYON	
BONE SPRING	
OLORIETA	
BLINERY	
TUBS	
DRINKARD	
LABO	
WC	
PENN	
STRAWN	
ATOKA	
MOORELOW	
ADRI	
DEVONIAN	

PLUG	TYPE	SACKS	DEPTH
PLUG	PLUG	CMNT	
EXAMPLES			
PLUG #1	OH	25 SXS	9850'
PLUG #2	SHOE	50 SXS	8700'-8800'
PLUG #3	CIBP/35'		5300'
PLUG #4	CIBP	25 SXS	5300'
PLUG #5	STUB	50 SXS	4600'-4700'
PLUG #6	REINR SOZ	200 SXS	400'
PLUG #7	SURF	10 SXS	0-10'
PLUG #8			
PLUG #9			
PLUG #10			
PLUG #11			
PLUG #12			
PLUG #13			
PLUG #14			
PLUG #15			
PLUG #16			
PLUG #17			
PLUG #18			
PLUG #19			
PLUG #20			

12 1/4" hole

8 5/8 24
@ 336'
TOC SURF.

25 SXS @
1900'

CIBP @ 2282'

2382' - 2510'

2556' - 2638'

5 1/2 15.5
@ 2700'
TOC SURF.

TD 2700'