	Submit I Copy To Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-103		
	District 1 - (575) 393-6161				evised August 1, 2011	
	1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283			WELL API NO. 30-015-31650		
	811 S. First St., Artesia, NM 88210			5. Indicate Type of Lea	00	
	<u>District III</u> – (505) 334-6178			STATE	FEE	
	1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3460			6. State Oil & Gas Leas		
	1220 S. St. Francis Dr., Santa Fe, NM 87505				, 6 1 16.	
	SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit	Agreement Name	
	(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A					
	DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			LITTLE BOX STATE		
	1. Type of Well: Oil Well Gas Well Other			8. Well Number 5		
	2. Name of Operator			9. OGRID Number		
	NADEL AND GUSSMAN PERMIAN 3. Address of Operator			155615 10. Pool name or Wildcat		
	601 N. MARIENFELD, SUITE 508, MIDLAND TEXAS 79701			LITTLE BOX CANYON; MORROW		
	4. Well Location					
	Unit Letter G : 1980_feet from the NORTH line and 1980_feet from the EAST_line Section 36 Township 20S Range 21E NMPM County EDDY					
		11. Elevation (Show whether DR,	RKB, RT, GR, etc.			
	4382' GR					
	12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
	•	•	·	•		
	NOTICE OF IN	SEQUENT REPOR				
	PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ REMEDIAL WOR TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DR			· 	ERING CASING 🗍	
	TEMPORARILY ABANDON					
	DOWNHOLE COMMINGLE					
	OTHER:	П	OTHER:			
	13. Describe proposed or comp		d give pertinent dates, inc	luding estimated date		
	of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of					
	proposed completion or recompletion.					
01	WELLBORE DIAGRAM IS A	TTACHED.		RE	CEIVED	
ug-	1. CUT AND PULL 5-1/2" CASING AT 5,600FT.			1	•	
7	1. CUT AND PULL 5-1/2" CASING AT 5,600FT. 2. CIRCULATE GEL, SPOT 25 SACK PLUG ON CASING STUB. 3. SPOT 25 SACK 100FT PLUG AT 4700ft 4. SPOT 25 SACK 100FT PLUG AT 3490. 5. SPOT 25 SACK PLUG FROM 1380'-1480' FOR CASING SHOE/GLORIETA PLUG. TAG. 6. SPOT SURFACE PLUG FROM 0-60 FT FILL TO SURFACE. REMOVE WELCHEAD, INSTALL DRY HOLE MARKER.					
•						
,						
	· ·	•				
			1			
•	Spud Date:	Rig Release Da	te:			
	Lhereby certify that the information	as and baliaf				
	I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE					
,						
	Type or print name_JASON GOSS	Type or print name_JASON GOSS E-mail address: JGOSS@NAGUSS.COM PHONE: _432-682-4429				
	APPROVED BY: DATE 8/27/13 Conditions of Approval (if any):					
	İ					
	0 000	At. 70 0	0000			
	original COA's still in place					
	O		•			

