

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-41162
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator COG Operating LLC		6. State Oil & Gas Lease No.
3. Address of Operator One Concho Center, 600 W. Illinois Avenue, Midland, TX 79701		7. Lease Name or Unit Agreement Name Bradley 8 Fee
4. Well Location Unit Letter <u>M</u> : <u>150</u> feet from the <u>South</u> line and <u>330</u> feet from the <u>West</u> line Section <u>8</u> Township <u>19S</u> Range <u>26E</u> NMPM County <u>Eddy</u>		8. Well Number: <u>1H</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3377' GR		9. OGRID Number: <u>229137</u>
		10. Pool name or Wildcat WILDCAT G-01 S192617K;GLOR-YESO 97788

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/9/13 Test csg to 7500# for 30min, ok. Spot 3000 gals 15% HCL to clean casing. Set plug @ 7490.
6/18/13 Perforate 9 stages, 3264 - 7450. See attachment.
7/2/13 Drilled out plugs. Wash down to PBTD @ 7487.
7/8/13 TIH w/74jts 2-7/8" J55 6.5# tbg. EOT @ 2587.
7/9/13 RIH w/rods and ESP pump. Hang on.



Spud Date: 5/10/13

Rig Release Date: 5/22/13

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Chasity Jackson TITLE Regulatory Analyst DATE 10/21/13

Type or print name Chasity Jackson E-mail address: cjackson@concho.com PHONE: 432-686-3087

For State Use Only

APPROVED BY: [Signature] TITLE Director DATE 10/30/2013
Conditions of Approval (if any)

Perf @ 7128-7450, 6 SPF, 36 holes. Acidize w/2012 gals 15% HCL. Frac w/160,259 gals gel, 25,325 gals WF, 11,500 gals slick water, 218,094# 20/40 Brown sand, 5,269# 100 mesh, 36,767# 16/30 CRC. Set plug @ 7048.

Perf @ 6645 - 6967, 6 SPF, 36 holes. Acidize w/3988 gals 15% HCL. Frac w/159,139 gals gel, 26,596 gals WF, 20,748 gals slick water, 215,344# 20/40 Brown sand, 5,008# 100 mesh, 41,640# 16/30 CRC. Set plug @ 6570.

Perf @ 6153 - 6484, 6 SPF, 36 holes. Acidize w/3981 gals 15% HCL. Frac w/157,628 gals gel, 23,264 gals WF, 32,126 gals slick water, 219,098# 20/40 Brown sand, 5,277# 100 mesh, 38,760# 16/30 CRC. Set plug @ 6082.

Perf @ 5679 - 6001, 6 SPF, 36 holes. Acidize w/3955 gals 15% HCL. Frac w/160,000 gals gel, 23,946 gals WF, 20,060 gals slick water, 220,017# 20/40 Brown sand, 5,762# 100 mesh, 37,813# 16/30 CRC. Set plug @ 5599.

Perf @ 5196 - 5518 6 SPF, 36 holes. Acidize w/3885 gals 15% HCL. Frac w/160,049 gals gel, 22,906 gals WF, 16,836 gals slick water, 219,286# 20/40 Brown sand, 5,224# 100 mesh, 37,557# 16/30 CRC. Set plug @ 5116.

Perf @ 4713 - 5035, 6 SPF, 36 holes. Acidize w/3990 gals 15% HCL. Frac w/150,029 gals gel, 32,572 gals WF, 16,776 gals slick water, 217,708# 20/40 Brown sand, 5,110# 100 mesh, 41,474# 16/30 CRC. Set plug @ 4633.

Perf @ 4230 - 4552, 6 SPF, 36 holes. Acidize w/4013 gals 15% HCL. Frac w/158,029 gals gel, 22,458 gals WF, 17,181 gals slick water, 220,822# 20/40 Brown sand, 5,006# 100 mesh, 36,697# 16/30 CRC. Set plug @ 4150.

Perf @ 3747 - 4069, 6 SPF, 36 holes. Acidize w/3965 gals 15% HCL. Frac w/157,625 gals gel, 20,625 gals WF, 16,328 gals slick water, 218,750# 20/40 Brown sand, 4,319# 100 mesh, 39,032# 16/30 CRC. Set plug @ 3667.

Perf @ 3264 - 3586, 6 SPF, 36 holes. Acidize w/5006 gals 15% HCL. Frac w/154,901 gals gel, 22,944 gals WF, 16,356 gals slick water, 254,261# 20/40 Brown sand, 5,307# 100 mesh, 38,977# 16/30 CRC.