Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

F	-	C	VA.	and the same		Ē)
				•	 7 10400	-	

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

OCT 28 2013 SUNDRY NOTICES AND REPORTS ON WELLS

Lease Serial No. NMLC029395A

abandoned we	is form for proposals to d II. Use form 3160-3 (APD)	ifill of to re-enter an) for such proposals CD	ARTES 6 If Indian, Allotted	e or Tribe Name
	PLICATE - Other instruct			reement, Name and/or No.
1. Type of Well			8. Well Name and N	0.
☑ Oil Well ☐ Gas Well ☐ Oth	ner		TURNER A 34	
Name of Operator LINN OPERATING INC	9. API Well No. 30-015-05232			
3a. Address 600 TRAVIS STREET, SUITE HOUSTON, TX 77002		3b. Phone No. (include area code Ph: 281-840-4272		or Exploratory JACKSON;SR-Q-G-S
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)		11. County or Parisl	n, and State
Sec 18 T17S R31E Mer NMP 32.831796 N Lat, 103.914509			EDDY COUN	TY, NM
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATE NATURE OF	NOTICE, REPORT, OR OTH	ER DATA
TYPE OF SUBMISSION		ТҮРЕ О	F ACTION	
Notice of Intent	☐ Acidize	□ Deepen	☐ Production (Start/Resume)	■ Water Shut-Off
	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation	■ Well Integrity
☐ Subsequent Report	□ Casing Repair	■ New Construction	☐ Recomplete	Other
☐ Final Abandonment Notice	□ Change Plans	Plug and Abandon	□ Temporarily Abandon	
	Convert to Injection	Plug Back	■ Water Disposal	
testing has been completed. Final Aldetermined that the site is ready for final PROPOSED P&A PROCEDU 1. MIRU P&A RIG. RIG W/ TI 2. SPOT-30-SXS-CMT-@ 134 3. PERF 7" CSG @ 619'. CIR 4. CUT OFF WELLHEAD. IN:	pandonment Notices shall be filed in all inspection.) RES: BG: TAG CMT @ 1520' +/- B': WOC & TAG. Park for C CMT TO SURFACE INSECTABLE DRY HOLE MARKE	only after all requirements, inclu CIRC MUD LADEN FLUI	CONDITIONS OF D. Must be wither to CONDITIONS OF D. Must be wither to Condition of the Cond	APPROVAL
CURRENT AND PROPOSED	WELLBORE DIAGRAMS	ATTACHED. May	be néeded.	
14. Thereby, certify that the foregoing of the state of the section of the sectio	Electronic Submission #22 For LINN OP Committed to AFMSS for pr	1252 verified by the BLM We ERATING INC, sent to the Cocessing by JOHNNY DICKE Title REG C	arisbaa	AMATION PROCEDURE ATTACHED
Signature (Electronic S	Submission)	Date 09/26/2		and for record/ MOCD 10/29/2013
	THIS SPACE FOR	R FEDERAL OR STATE	OFFICE USE	
Approved By Ames (2) onditions of approval, if any, are attached	d. Approval of this notice does no	Title SE	105	Date 10-22-1
ertify that the applicant holds legal or equ high would entitle the applicant to condu	ntable title to those rights in the s act operations thereon.	ubject lease Office CH	D.	

Tile 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States are false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Well Heme:	Turner A #34							
-		1						Tumer A #34"
Lecation	tecation:		14	Current Velibore Diagra			API No:	10-015-05732
Section:	T; 173 R; \$1E Sec; 18		Ť	THE STREET	<u> </u>		loud Date: WED Update:	9/17/1913 9/18/2018 R. Van House
(Block:			8	1			1.4	** C
Sovern	Liddy						Hole Size:	12:1/2
Lations:			200				Syd_CHE Corners Bland	9/5/97, 329, 9-55 50 cc."
I lobd:	Fren Grayburg lackson Elevations		8				Depthe	563°
6t:	376Z						100	N/A
01,					200		Hole Site:	9
ra-or care ca w/log):					S5/8", 38) n	1:11 Sass	7", 20v, 1-55
(12 11) 12			_ a ş		201 6 161	,		
Licenter Persyl	mirte.		3				Cement Blendt	50 122
ĺ							Zisuma:	
<u> </u>				1	Š.		TOC:	N/A
			i 🖇		200		SECTOR SECTION	
Date 9/17/1953	Saud 12-1/2" Dete & Cris to 565"; Set 9-5/3" crs @ set 7" crs @ same w/ 100 st crrs. Drill 6" hote to TI	145' & count w/ 50 to cost. Or lad 9' hate to 1933 & D @ 2007'.					Ortolla of Partieration	
10/25/1950		Loin 1930-1007 and perforated how 1957-67 and	3				PROFESSION STREET	л)
	Classed but to 10. Initial By of 5-1/2" and to 1957; 1957; Rin w/ 2-3/8" and to 2000'. Rin w/ put 10/19/1953	Irvin 1930-1007 and perforshed from 1957-67 and inp & prod equits. Made 10 bbb in 24 has on	, su se		SCANAGE.			
10/20/1913 11/1/1979	We'l shut-in, Holding for future persoprisent.							
3/20/1979	Bradentaged was pired to surface w/ a valve in stal		13	•	X 3			
am/riega	Durns 90000 10/40 sand, PU to let und seite, RIH 500', her der, POH w/ the RUMO, Well h TA'd.	& tag sand @ 1655'. Domp 10 are ont on sand, PU to	1		3			
9/2/1994			4		80%			
					8		Acht ex Freceura Jres	intent Repails
			8		39 23		9/20/1953	1,957-2,000' shat with 205 qts nitro-glycerin
			1		25,206		*	**************************************
			Ĩ					
			1		2539			
					3			
					*			
			9		\$ 5			
			8		Š.			Tuking Ontall
		***************************************	8				. Aplmis ·	Perkulacien :
			g		STATE OF THE PARTY			20/8
			1 8		XX		Pki Depih	
			3					
			33 16		\$			Red Detell (top to bottom)
			1		*		Ppon.	Description
			S. S		300			
-			3		2			
			*	1	or and			
ļ			8	1	8			·
*************			Control Control	1	Ď.		Exmission Units	
£			1] _	23		-	-
 		The second secon	1 1	1	2			
ļ. —	the second secon	2 char	l. 🖁	1	2 12 P.A.			
					and topp	rd @ 1645'		
ļ					20 te cont	on top at sand		
			1		2 7 200	•	Itale Strer	6.
			i -	1	ser@ \$931	5'	Prod Cit:	\$-1/1", 17#
— —			i]			Capetty (hbi/irl:	Í
	1		l	[Cement Blend	nonz
			l				TOC	1
			I				Dupin	5000,
1			ŀ	Sand 	1960,196	8!	l	
	A STATE OF THE STA	7 77 77 78 79 79			53× F-10		I	
					•		**************************************	
			Ī]	3250-140	14"		•
			1	L				
J				Th				
<u> </u>			ľ	T20: 7,000°	Open Holi	nem 1915'-2000'		
	The state of the s							
*****			,					

position solitors social	Turner A #34 Localon: 1050 FHL 738 F(L. 1; 173 R: 315 Sec. 18	11	Proposed		Well Marner	Turner A 828
position solitors social	Localon: 1650 FML 748 F(L. F: 173 R: 31E Sec. 18	11	Proposed			
eciliona book: provy: bunty: t/Jongs: t/Si Calic	1050 FML 748 FEL T: 178 FE 31E Sec: 18	11	Proposed			
eciliona book: provy: bunty: t/Jongs: t/Si Calic	1050 FML 748 FEL T: 178 FE 31E Sec: 18	44				30-015-05232
ctions cels: cels: conty: vions: click: click:			Velibore Diagram	n	Spud Date:	9/27/1951
sck: Invery: I		-	TOWNS MILE AND A STATE OF THE ASSESSMENT OF THE	=	WID Update:	9/24/2013, L. Willbants
reay: winty: Viong: Idj Gi Calc	NAME OF THE OWNER OWNER OF THE OWNER OWNE	%1 (I SECRETARION I	lë	Francisco	THE PARTY OF THE P
Viens: nisi -Gi Cale				 	Hole Stie:	17-1/7
Gi Co'c	Įddy ·		100	1 2	SHITL SEED	9-5/47, 97#, 4-55
Gi Calc		- \$11		ž	Comem Blenck	5/3 t.X
Gi Ca'c	Nun Crestury Jackson Clevetors	31	148888	Ř.	Deptitu	R2.
HGI Calc	174'				TOC:	NA
GI Ca'c	1	- 3H		Circ 1900s con to suif	Hole Start	
		- 8H		9-3/8", 204	Int Case	7°, 204, 855
w/log?		_ X		N 10 365	Street.	1 12001533
		. Т				
extra Persone	menta:	l ä			Coment Stand:	50 sis
		l \$				
	<u> </u>	Į.	1 18		Returniz	
		1 🐉			LOC:	N/A
	CALLED CONTROL OF THE	1 ₹				
te .		l li	1			·
17/1953	3pud 13-1/2" hole & drid to 565') Set 9-5/6" cs4 Ø 565' & critid m/ 30 cs cmit. Delled 9" hole to 1913 &	. 8	1 9			
	let 7" cig @ rams w/ 100 is cont. Del3 6" bole to 70 @ 2007".		j (8		Ortalia of Partorni	ions
/26/1053	1957-2000 that with 2CS gas. Naro-presets Desired out to 10. bistar to 475-07 cag for first 1970-2007 and performing from 1917-67 field	*				•
Ţ	Change out to 1th witch to 45-17 cag for keer from 1919-2000 and perforated from 1917-47 bed	基	1			
inchine.	1987-1997: \$16 w/ 2-3/8" the 10 2000; Sixt w/ pump & crod egito, Made 10 bbits in 28 his on 30/29/1993	9	y 18			
	10/25/1553 Well shytile. Holding for lighting development.	2	j lã			
29/1979	desidenceed was piped to installe w/ a valve in stalled for pressure checks in accordance w/ OCO	3				
	Dump 5000x 20/40 sand. PU to let sand settle, Rift & tag sand @ 1645", Dump 30 sas erm on sand, PU to	\$	1 18			
3/1994	SOOT, Regider, POH w/ the ROWO, Well is TA'S.	ä				
1		SHEEZSHAG				
		\$3 \$3			add peligings It	verment Details
	Plug & Abendon Procedures	1 2				e i i i i i i i i i i i i i i i i i i i
	NH w/ the Top the Q 1110 -/-, the MU; Spot 30ts cmt Q 1160, WOC A tre	ä	19		1441/44	1,957-2,000 that with 105 que sico-giyestin
	Peri 7" cag Ø 510°, Circ crist an curriere inside & out w/ appears 100ps cres.	1 3	1 18			•
	Cut off with head and install der hode marker,	- §				
		\$				
		ã				
		縈	i lä			
		8	7 18			
		1 8	1 18			
		Į,	i li		- سبن	
		Į.	1 18		Icinta	Yubing Detail (Contriction
		1 8			*************	7.1/8*
		1 8	1 1			1.717
		Į.	1		Pr Pensa	
		l 🕺				
		1 8		Spot ≯0ss cm @ 1340		
		1	BETSERN SOUTHER		Roda	Rod (lejali (top je bottom)
		核				Description .
		1 8	1 13			
		₽ ₽	1 13			······································
		8	1 6		i	
		3	1 13			
		1 %	1 18			
		1	13		Existence Motor	
		3	1 13			
		8] - 13		-	
		8	1 13			
		, å] [1			
		. 🐧				
إنتنا	the state of the second of the second of the second second of the second		****	A CONTRACTOR	- سو پيت	* * * * * * * * * * * * * * * * * * *
		8	ROSSORENCE.	Tay 024 @ 1530" +/-		
		🏂		30 is unit on top of set send tagged @ 1665	75	
		8		saun rattan fi. 107).	Picto Mant	1
		≃	1	7", 20#, set @ 1985"	Prod Sec	5-L/2*, 17#
		1	1	· Ammitans B. 1845	Cepecity (http://tip:	~ m = 1 410
		1			Carnera Eleveli	#pn#
		1	1		Returnet	
		l	[TOC	
		1			Depth	2007
			3420	1960-1961	1	
r recoverable	THE CONTRACTOR OF THE PROPERTY	7 . T. T	- W.	C. come utilities in come.		. •
723] "']	•	l	
		l				
		ŀ	1	1990'-1994'		
		l	[]			
		l	TD: 2,000*			
		l	sen eváva	Open Hole from 1915'-	toner	
		1		Abelianna athu 1813.	****	
		-				

·

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

Requirements for dry hole markers in Prairie Chicken Habitat <u>Well Identification Markers</u> Conditions of Approval (COA)

The BLM Carlsbad Field Office (CFO) Conditions of Approval (COA) have required that ground level dry hole markers be placed on wells within the Lesser Prairie Chicken habitat area. Onshore Order 2.III.G.10 allows for surface caps to be installed at the base of the cellar of a minimum of 3 feet below the restored ground level. Therefore, these markers shall be set a minimum of 3 feet below the restored ground level. All markers shall be identified by GPS coordinates.

The dry hole markers will be to the following specifications. The operator will construct the markers as follows:

- 1. A steel plate 1/4 inch thick shall be placed on the wellbore, welded in place and with a weep hole.
- 2. Aluminum data plates may be bolted to the steel plate with minimum ¼ inch bolts and locking nuts or self tapping fine threaded screws. A minimum of one in each corner is to be installed on each plate.
- 3. An 8 inch x 8 inch aluminum plate, which is 12 gauge or .080 sign material (1/8 inch aluminum plate may be used in place of the .080 plate) with the required information for that well stamped or engraved in a minimum 3/8 inch tall letter or number.
- 4. The following information will be stamped or engraved on the 8 inch X 8 inch aluminum plate in the following order.
 - a. First row: Operator's name
 - b. Second row: Well name and number
 - c. Third row: Legal location to include ¼ ¼, Section, Township, and range. If the legal location cannot be placed on one row it can be split into two rows with the ¼ ¼ (example: 1980 FNL 1980 FWL) being on the top row.
 - d. Fourth row: Lease Number and API number.
 - i. Example marker plate: (attached)

Notification to NMOCD of this marker type will be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground level dry hole marker was installed and GPS coordinates recorded as required in the COAs from the BLM.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Inspection & Enforcement

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Mike Burton Environmental Protection Specialist 575-234-2226

Jeffery-Robertson Natural Resource Specialist 575-234-2230

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Doug Hoag Civil Engineering Technician 575-234-5979

Linda Denniston Environmental Protection Specialist 575-234-5974

Solomon Hughes Natural Resource Specialist 575-234-5951

Permitting

Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Tanner Nygren Natural Resource Specialist 575-234-5975

Amanda Lynch Natural Resource Specialist 575-234-5922

Legion Brumley Environmental Protection Specialist 575-234-5957

Realty, Compliance

Randy Pair Environmental Protection Specialist 575-234-6240