	UNITED STATES		D Artesia	FORM APPROVED OMB No. 1004-0135
	ARTMENT OF THE INT			Expines July 31, 1996 5. Lease Serial No.
	NOTICES AND REPORTS		,	NMLC 067849
Do not use this	form for proposals to	drill or reenter		6. If Indian, Allottee or Tribe Name
abandoned well.	Use Form 3160-3 (APD)	for such proposa	ls.	
SUBMIT IN TRIPL	ICATE – Other instruc	ctions on revers	se side	7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well X Oil Well Gas Well	Other			8. Well Name and No.
2. Name of Operator			EAGLE 34 D FEDERAL #72	
LIME ROCK RESOURCES	and the second	21 Dhone No (inch	de marca cadal	9. API Well No.
3a. Address c/o Mike Pippin I 3104 N. Sullivan, Farmington	1	3b. Phone No. (inclu 505-327-4573	ide area coae)	30-015-41216 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec.,	· · · · · · · · · · · · · · · · · · ·		<u></u>	Red Lake: Glorieta-Yeso NE (96836)
990' FNL & 990' FWL Unit [AND
Sec. 34, T17S, R27E				Eddy County, New Mexico
12. CHECK APPROPRIATE BO	X(ES) TO INDICATE NATU	URE OF NOTICE, R	EPORT, OR O	THER DATA
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	Acidize [Deepen Fracture Treat	Production	n (Start/Resume) 🔲 Water Shut-Off
Subsequent Report	Casing Repair [Change Plans	New Construction Plug and Abandon	Recomple	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Dis	-
If the proposal is to deepen directional Attach the Bond under which the work Following completion of the involved op	ly or recomplete horizontally, give sub will be performed or provide the Bo perations. If the operation results in bandonment Notices shall be filed only	ubsurface locations and mea- kond No, on file with BLM a multiple completion or r	asured and true verti M/BIA. Required su recompletion in a ne	oposed work and approximate duration thereof ical depths of all pertinent markers and zones, ubsequent reports shall be filed within 30 days aw interval, a Form 3160-4 shall be filed once a, have been completed, and the operator has
If the proposal is to deepen directional Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp	ly or recomplete horizontally, give sut will be performed or provide the Bc perations. If the operation results in a bandonment Notices shall be filed onl ection.) Drilled 12-1/4" hole to 436	ubsurface locations and mea kond No on file with BLN a multiple completion or r nly after all requirements, 60'. Set 8-5/8" 24	asured and true verti MBIA. Required su recompletion in a ner including reclamation # J-55 csg @	ical depths of all pertinent markers and zones, ubsequent reports shall be filed within 30 days sw interval, a Form 3160-4 shall be filed once a, have been completed, and the operator has 0 427'. Cmted w/330 sx (444 cf) ci "C"
If the proposal is to deepen directionall Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp Spudded well on 12/4/13. E cmt w/0.25# C/F. Circ 80 st Drilled 7-7/8" hole to TD470 w/lead 300 sx (579 cf) 35:65	ly or recomplete horizontally, give sut will be performed or provide the Bc perations. If the operation results in : bandonment Notices shall be filed onlive control of the performance of the file on the pit. On 12/8/13, 05' on 12/10/13. Ran ope 5 poz "C" cmt w/5% PF-4 % PF-13, 0.2% PF-65, 0 essure test 5-1/2" csg du	 absurface locations and measured hold Na on file with BLN a multiple completion or raily after all requirements, 50'. Set 8-5/8" 24; 50, pressure tested 51, pressure tested 52, pressure tested 54, 6% PF-20, 0. 51, 125# PF-29, & 0. 51, 125# PF-29, & 0. 	asured and rue verti M/BIA. Required su recompletion in a ne including reclamation # J-55 csg @ I 8-5/8" csg tc : 5-1/2" 17# J- 125# PF-29, 0.4# PF-46 (operations.	ical depths of all pertinent markers and zones, ubsequent reports shall be filed within 30 days sw interval, a Form 3160-4 shall be filed once a, have been completed, and the operator has 0 427'. Cmted w/330 sx (444 cf) ci "C"
If the proposal is to deepen directional Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp Spudded well on 12/4/13. E cmt w/0.25# C/F. Circ 80 s: Drilled 7-7/8" hole to TD470 w/lead 300 sx (579 cf) 35:65 sx (838 cf) cl "C" cmt w/0.56 rig on 12/11/13. Plan to pre	ly or recomplete horizontally, give sut will be performed or provide the Bo perations. Bit the operation results in : bandooment Notices shall be filed onlection.) Drilled 12-1/4" hole to 436 x cmt to pit. On 12/8/13, 05' on 12/10/13. Ran ope 5 poz "C" cmt w/5% PF-4 % PF-13, 0.2% PF-65, 0 essure test 5-1/2" csg du	ubsurface locations and mea kond No on file with BLN a multiple completion or r nly after all requirements, 60'. Set 8-5/8" 24 6, pressure tested en hole logs. Set 44, 6% PF-20, 0. 0.125# PF-29, & 0	aured and rue verti M/BIA. Required su recompletion in a ne including reclamation # J-55 csg @ I 8-5/8" csg to 5-1/2" 17# J- 125# PF-29, 0.4# PF-46 operations. Cf #CORE //	 ical depths of all pertinent markers and zones, absequent reports shall be filed within 30 days we interval, a Form 3160-4 shall be filed once a, have been completed, and the operator has 2.427'. Cmted w/330 sx (444 cf) cl "C" to 1500 psi for 30 min-OK. -55 production csg @ 4696'. Cmted 0.4# PF-46, & 5# PF-42 & tailed w/625 Circ 122 sx cmt to pit. Released drilling
If the proposal is to deepen directional Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp Spudded well on 12/4/13. E cmt w/0.25# C/F. Circ 80 st Drilled 7-7/8" hole to TD470 w/lead 300 sx (579 cf) 35:65 sx (838 cf) cl "C" cmt w/0.55 rig on 12/11/13. Plan to pres	ly or recomplete horizontally, give sut will be performed or provide the Bc perations. If the operation results in : bandooment Notices shall be filed onli ection.) Drilled 12-1/4" hole to 430 x cmt to pit. On 12/8/13, 05' on 12/10/13. Ran ope 5 poz "C" cmt w/5% PF-4 % PF-13, 0.2% PF-65, 0 essure test 5-1/2" csg du	absurface locations and measure kond Na on file with BLN a multiple completion or r nly after all requirements. 60'. Set 8-5/8" 24: 6, pressure tested 9, pressure te	aured and rue verti M/BIA. Required su recompletion in a ne including reclamation # J-55 csg @ I 8-5/8" csg tc : 5-1/2" 17# J- .125# PF-29, .0.4# PF-46 coperations. CL NECORD //	ical depths of all pertinent markers and zones, absequent reports shall be filed within 30 days winterval, a Form 3160-4 shall be filed once a, have been completed, and the operator has 0.427'. Cmted w/330 sx (444 cf) cl "C" 0.1500 psi for 30 min-OK. -55 production csg @ 4696'. Cmted 0.4# PF-46, & 5# PF-42 & tailed w/625 Circ 122 sx cmt to pit. Released drilling RECEIVED JAN 15 2014
If the proposal is to deepen directional Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp Spudded well on 12/4/13. E cmt w/0.25# C/F. Circ 80 s: Drilled 7-7/8" hole to TD470 w/lead 300 sx (579 cf) 35:65 sx (838 cf) cl "C" cmt w/0.56 rig on 12/11/13. Plan to pres 14. Thereby certify that the foregoin Name (<i>Printed/Typed</i>) Mike	ly or recomplete horizontally, give sut will be performed or provide the Bo perations. Bit the operation results in : bandooment Notices shall be filed onlection.) Drilled 12-1/4" hole to 436 x cmt to pit. On 12/8/13, 05' on 12/10/13. Ran ope 5 poz "C" cmt w/5% PF-4 % PF-13, 0.2% PF-65, 0 essure test 5-1/2" csg du	burface locations and measure kond Na on file with BLN a multiple completion or r nly after all requirements, 60'. Set 8-5/8" 24 b, pressure tested en hole logs. Set 44, 6% PF-20, 0. 0.125# PF-29, & 0 0.125# PF-29, & 0 0 0.125# PF-29, & 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	aured and rue verti M/BIA. Required su recompletion in a ne including reclamation # J-55 csg @ I 8-5/8" csg tc : 5-1/2" 17# J- .125# PF-29, .0.4# PF-46 coperations. CL NECORD //	 ical depths of all pertinent markers and zones, absequent reports shall be filed within 30 days we interval, a Form 3160-4 shall be filed once a, have been completed, and the operator has 2.427'. Cmted w/330 sx (444 cf) cl "C" to 1500 psi for 30 min-OK. -55 production csg @ 4696'. Cmted 0.4# PF-46, & 5# PF-42 & tailed w/625 Circ 122 sx cmt to pit. Released drilling
If the proposal is to deepen directional Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp Spudded well on 12/4/13. E cmt w/0.25# C/F. Circ 80 st Drilled 7-7/8" hole to TD470 w/lead 300 sx (579 cf) 35:65 sx (838 cf) cl "C" cmt w/0.55 rig on 12/11/13. Plan to pres	ly or recomplete horizontally, give sut will be performed or provide the Bo perations. Bit the operation results in : bandooment Notices shall be filed onlection.) Drilled 12-1/4" hole to 436 x cmt to pit. On 12/8/13, 05' on 12/10/13. Ran ope 5 poz "C" cmt w/5% PF-4 % PF-13, 0.2% PF-65, 0 essure test 5-1/2" csg du Ig is true and correct Pippin	burface locations and mea kond Na on file with BLN a multiple completion or r nly after all requirements, 60'. Set 8-5/8" 24 b, pressure tested en hole logs. Set 44, 6% PF-20, 0. 0.125# PF-29, & 0 uring completion of 20 (K)	aured and rue verti M/BIA. Required su recompletion in a ne including reclamation # J-55 csg @ I 8-5/8" csg tc : 5-1/2" 17# J- .125# PF-29, .0.4# PF-46 (operations. CC NEE 20 // CD Petrolet	ical depths of all pertinent markers and zones, absequent reports shall be filed within 30 days winterval, a Form 3160-4 shall be filed once a, have been completed, and the operator has 0.427'. Cmted w/330 sx (444 cf) cl "C" 0.1500 psi for 30 min-OK. -55 production csg @ 4696'. Cmted 0.4# PF-46, & 5# PF-42 & tailed w/625 Circ 122 sx cmt to pit. Released drilling RECEIVED JAN 15 2014
If the proposal is to deepen directionall Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp Spudded well on 12/4/13. E cmt w/0.25# C/F. Circ 80 s: Drilled 7-7/8" hole to TD470 w/lead 300 sx (579 cf) 35:65 sx (838 cf) cl "C" cmt w/0.55 rig on 12/11/13. Plan to pre 14. I hereby certify that the foregoin Name (<i>Printed/Typed</i>) Mike Signature	ly or recomplete horizontally, give sut will be performed or provide the Bo perations. Bit the operation results in : bandonment Notices shall be filed onl ection.) Drilled 12-1/4" hole to 430 x cmt to pit. On 12/8/13, 05' on 12/10/13. Ran ope 5 poz "C" cmt w/5% PF-4 % PF-13, 0.2% PF-65, 0 essure test 5-1/2" csg du C/2 Ig is true and correct Pippin	burface locations and measure kond Na on file with BLN a multiple completion or r nly after all requirements, 60'. Set 8-5/8" 24 b, pressure tested en hole logs. Set 44, 6% PF-20, 0. 0.125# PF-29, & 0 0.125# PF-29, & 0 0 0.125# PF-29, & 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	aured and rue verti M/BIA. Required su recompletion in a ne including reclamation # J-55 csg @ 1 8-5/8" csg to 5-1/2" 17# J- 125# PF-29, 0.4# PF-46 operations. Cf if @ 28 d // CD Petrolet Dec	ial depths of all pertinent markers and zones, absequent reports shall be filed within 30 days winterval, a Form 3160-4 shall be filed once a, have been completed and the operator has 0.427'. Cmted w/330 sx (444 cf) cl "C" 0.1500 psi for 30 min-OK. -55 production csg @ 4696'. Cmted 0.4# PF-46, & 5# PF-42 & tailed w/625 Circ 122 sx cmt to pit. Released drilling ISTORY IN 15 2014 UM Engineer MARCE ARTESIA
If the proposal is to deepen directionall Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp Spudded well on 12/4/13. E cmt w/0.25# C/F. Circ 80 s: Drilled 7-7/8" hole to TD470 w/lead 300 sx (579 cf) 35:65 sx (838 cf) cl "C" cmt w/0.55 rig on 12/11/13. Plan to pre 14. I hereby certify that the foregoin Name (<i>Printed/Typed</i>) Mike Signature	ly or recomplete horizontally, give sut will be performed or provide the Bo perations. Bit the operation results in : bandonment Notices shall be filed onl ection.) Drilled 12-1/4" hole to 430 x cmt to pit. On 12/8/13, 05' on 12/10/13. Ran ope 5 poz "C" cmt w/5% PF-4 % PF-13, 0.2% PF-65, 0 essure test 5-1/2" csg du C/2 Ig is true and correct Pippin	burface locations and measure and Na on file with BLN a multiple completion or r nly after all requirements. 60'. Set 8-5/8" 24: 6, pressure tested en hole logs. Set 44, 6% PF-20, 0. 0.125# PF-29, & 0 uring completion of COMPLETING Title Date	aured and rue verti M/BIA. Required su recompletion in a ne including reclamation # J-55 csg @ 1 8-5/8" csg to 5-1/2" 17# J- 125# PF-29, 0.4# PF-46 operations. Cf if @ 2.20 // CD Petrolet Dec	ial depths of all pertinent markers and zones, absequent reports shall be filed within 30 days winterval, a Form 3160-4 shall be filed once a, have been completed, and the operator has 0.427'. Cmted w/330 sx (444 cf) cl "C" 0.1500 psi for 30 min-OK. -55 production csg @ 4696'. Cmted 0.4# PF-46, & 5# PF-42 & tailed w/625 Circ 122 sx cmt to pit. Released drilling IST State Sta
If the proposal is to deepen directionall Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp Spudded well on 12/4/13. E cmt w/0.25# C/F. Circ 80 s: Drilled 7-7/8" hole to TD470 w/lead 300 sx (579 cf) 35:65 sx (838 cf) cl "C" cmt w/0.56 rig on 12/11/13. Plan to pre 14. I hereby certify that the foregoin Name (<i>Printed/Typed</i>) Mike Signature Multiple Approved by	ly or recomplete horizontally, give sut will be performed or provide the Bo perations. If the operation results in : bandooment Notices shall be filed onlection.) Drilled 12-1/4" hole to 436 x cmt to pit. On 12/8/13, 05' on 12/10/13. Ran ope 5 poz "C" cmt w/5% PF-4% % PF-13, 0.2% PF-65, 0 essure test 5-1/2" csg du We with the test 5-1/2" csg du THIS SPACE d Approval of this notice does not w uitable title to those rights in the subj	absurface locations and measure and the locations and measure and the completion or r and the completion or r and the completion or r and the completion or r and the logs. Set 44, 6% PF-20, 0. 0.125# PF-29, & C 20	aured and rue verti M/BIA. Required su recompletion in a ne including reclamation # J-55 csg @ 1 8-5/8" csg to 5-1/2" 17# J- 125# PF-29, 0.4# PF-46 operations. Cf if @ 2.20 // CD Petrolet Dec	ial depths of all pertinent markers and zones, absequent reports shall be filed within 30 days winterval, a Form 3160-4 shall be filed once a, have been completed and the operator has 0.427'. Cmted w/330 sx (444 cf) cl "C" 0.1500 psi for 30 min-OK. -55 production csg @ 4696'. Cmted 0.4# PF-46, & 5# PF-42 & tailed w/625 Circ 122 sx cmt to pit. Released drilling ISTORY IN 15 2014 UM Engine PARTESIA UM Engine PARTESIA
If the proposal is to deepen directionall Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp Spudded well on 12/4/13. E cmt w/0.25# C/F. Circ 80 s: Drilled 7-7/8" hole to TD470 w/lead 300 sx (579 cf) 35:64 sx (838 cf) cl "C" cmt w/0.56 rig on 12/11/13. Plan to pre 14. I hereby certify that the foregoin Name (<i>Printed/Typed</i>) Mike Signature Multiple Conditions of approval, if any, are attached certify that the applicant holds legal or equ which would entitle the applicant to condu	ly or recomplete horizontally, give sut will be performed or provide the Bo perations. If the operation results in : bandoament Notices shall be filed onlection.) Drilled 12-1/4" hole to 430 x cmt to pit. On 12/8/13, 05' on 12/10/13. Ran ope 5 poz "C" cmt w/5% PF-4% % PF-13, 0.2% PF-65, 0 bessure test 5-1/2" csg du CR ag is true and correct Pippin CAR Approval of this notice does not w uitable title to those rights in the subj ct operations thereon.	absurface locations and measure and Na on file with BLN a multiple completion or r all requirements. 30'. Set 8-5/8" 24: 30'. Set	aured and rue verti M/BIA. Required su recompletion in a ne including reclamation # J-55 csg @ I 8-5/8" csg to 5-1/2" 17# J- 125# PF-29, 0.4# PF-46 operations. C/ NO 200 // Petroled Dec R STATE USE	ial depths of all pertinent markers and zones, absequent reports shall be filed within 30 days winterval, a Form 3160-4 shall be filed once a, have been completed, and the operator has 0.427'. Cmted w/330 sx (444 cf) cl "C" 0.1500 psi for 30 min-OK. -55 production csg @ 4696'. Cmted 0.4# PF-46, & 5# PF-42 & tailed w/625 Circ 122 sx cmt to pit. Released drilling IST State Sta
If the proposal is to deepen directionall Atach the Bond under which the work Following completion of the involved op Testing has been completed. Final At determined that the site is ready for final insp Spudded well on 12/4/13. E cmt w/0.25# C/F. Circ 80 s: Drilled 7-7/8" hole to TD470 w/lead 300 sx (579 cf) 35:64 sx (838 cf) cl "C" cmt w/0.56 rig on 12/11/13. Plan to pre 14. I hereby certify that the foregoin Name (<i>Printed/Typed</i>) Mike Signature Multiple Conditions of approval, if any, are attached certify that the applicant holds legal or equ which would entitle the applicant to condu	ly or recomplete horizontally, give sut will be performed or provide the Bo perations. If the operation results in : bandoament Notices shall be filed onlection.) Drilled 12-1/4" hole to 430 x cmt to pit. On 12/8/13, 05' on 12/10/13. Ran ope 5 poz "C" cmt w/5% PF-4% % PF-13, 0.2% PF-65, 0 bessure test 5-1/2" csg du CR ag is true and correct Pippin CAR Approval of this notice does not w uitable title to those rights in the subj ct operations thereon.	absurface locations and measure and Na on file with BLN a multiple completion or r all requirements. 30'. Set 8-5/8" 24: 30'. Set	aured and rue verti M/BIA. Required su recompletion in a ne including reclamation # J-55 csg @ I 8-5/8" csg to 5-1/2" 17# J- 125# PF-29, 0.4# PF-46 operations. C/ NO 200 // Petroled Dec R STATE USE	ial depths of all pertinent markers and zones, absequent reports shall be filed within 30 days winterval, a Form 3160-4 shall be filed once a, have been completed, and the operator has 0.427'. Cmted w/330 sx (444 cf) cl "C" 0.1500 psi for 30 min-OK. -55 production csg @ 4696'. Cmted 0.4# PF-46, & 5# PF-42 & tailed w/625 Circ 122 sx cmt to pit. Released drilling ISTREELIVED JAN 15-2014 um Engineer 12, 2013. D FUX KELUKL cember 12, 2013. D FUX KELUKL Date JAN 1 1 2014