

Occidental Oil & Gas Corp – Permian Primary – North NM/Terrell RMT

Well: Rogers 23 #5		API: 30-015-40859	
State: New Mexico	County: Eddy	T18S R26E, Sec 23	2310' FNL & 1650' FEL
Field: Rogers	TD: 4,038'	PBTD: 3,974'	KB: 3,324' ASL
Casing Size:	Grade/Weight:	Depth:	Cement:
8-5/8"	J-55 / 24#	916'	590 sx, 236 sx circ'd to surf
5-1/2"	L-80 BTC / 17#	4,038'	880 sx, 211 sx circ'd to surf

Surf Csg: 8-5/8" 24# J-55
Cement: 590 sx, 236 sx circ'd to surf

KB: 3,324' ASL



Surf Csg @ 916'

Stage 1	3,839	3,840
	3,844	3,845
	3,858	3,860
	3,869	3,870
	3,886	3,887
	3,897	3,898
	3,908	3,909
	3,963	3,965
Stage 2	3,673	3,674
	3,694	3,695
	3,724	3,726
	3,780	3,782
	3,793	3,794
	3,801	3,802
	3,808	3,810
Stage 3	3301	3302
	3313	3314
	3325	3326
	3339	3340
	3366	3367
	3379	3380
	3392	3393
	3414	3415
	3424	3425
	3487	3488
	3518	3519
Stage 4	3040	3041
	3060	3061
	3091	3092
	3115	3116
	3124	3125
	3140	3141
	3191	3192
	3221	3223
	3260	3261

Top Glorieta @ 2,682'

Top Paddock @ 2,840'

Top Blinebry @ 3,358'

PBTD @ 3,974'

Prod Csg: 5-1/2" 17# L-80 BTC
Cement: 880 sx, 211 sx circ'd to surf

Prod Csg @ 4,038'
TD @ 4,038'