



API / UTM	Surface Legal Location	Field Name	License No.	State/Province	Well Configuration Type
3003907472	029N-005W-032-M	MV		NEW MEXICO	Vertical
Ground Elevation (ft)	Original KBURT Elevation (ft)	KB-Ground Distance (ft)	KB-Casing Fringe Distance (ft)	KB-Tubing Hanger Distance (ft)	
6,490.00	6,503.00	13.00		6,503.00	

Formation Tops	MD (ftKB)	Vertical schematic (actual)	
	11.5		
	222.8		
	224.7	1; Surface; 10 3/4 in; 10.192 in; 11.5 ftKB; 224.7 ftKB	Surface Casing Cement; 11.5-224.7; 9/14/1957; Cemented w/200 sxs w/2% CaCl. Circulated to Surface.
	225.1		
OJO ALA...	2,655.0		
	2,775.9		
KIRTLAND	2,815.9	Tubing; 2 3/8 in; 4.70 lb/ft; J-55; 11.5 ftKB; 5,657.5 ftKB	
FRUITLA...	3,125.0		
PICTUR...	3,279.9		
LEWIS	3,455.1		
	3,555.2		
	3,557.4		
	3,595.4		
	3,600.1	2; Intermediate1; 7 5/8 in; 6.969 in; 11.5 ftKB; 3,600.0 ftKB	Intermediate Casing Cement; 2,776.0-3,600.0; 9/24/1957; Cemented w/150 sxs w/8% gel & 50 sxs regular. TOC 2775.98' using 75% eff. calc.
	4,205.0		Acid Wash; 11/6/1998; Acidize Lewis w/1000 gal. of 15% HCL & additives.
	4,210.2	Lewis; 4,209.0-4,620.0; 11/6/1998	Hyd Frac-Foam N2; 11/10/1998; Frac'd Lewis w/78,036 gal of 60q N2 foam consisting of 28,514 gal of 30# X-Link gel & 725,000 SCF N2 gas.
	4,617.1		
	4,620.1		
	5,155.2		
CLIFF H...	5,205.1		
MENEFEE	5,275.5		
	5,321.5	Menefee; 5,362.0-5,535.0; 11/5/1998	Acid Wash; 11/5/1998; Acidized Menefee w/1260 gal of 15% HCL & additives.
	5,535.1	Mesaverde; 5,198.0-5,734.0; 10/16/1957	Hyd Frac-Waterbase; 10/16/1957; Frac'd w/120,000 gal water.
POINT L...	5,557.9		
	5,657.5	Pump Seating Nipple; 2 3/8 in; 4.70 lb/ft; J-55; 5,657.5 ftKB; 5,659.5 ftKB	
	5,659.4	Expendable Check; 2 3/8 in; 4.70 lb/ft; J-55; 5,659.5 ftKB; 5,660.0 ftKB	
	5,660.1		
	5,733.9		
	5,793.0	PSTD; 5,793.0	Auto cement plug; 5,793.0-5,800.0; 9/30/1957; Automatically created cement plug from the casing cement because it had a tagged depth.
	5,797.5		
	5,799.9	3; Production1; 5 1/2 in; 4.950 in; 11.5 ftKB; 5,800.0 ftKB	Production Casing Cement; 4,210.2-5,800.0; 9/30/1957; Cemented w/150 sxs regular. TOC 4210.18 using 75% eff. calc.