

Submit 1 Copy To Appropriate District Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources
ARTESIA DISTRICT
DEC 15 2014
RECEIVED
OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103
 Revised July 18, 2013

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		WELL API NO. 30-015-42726 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> 6. State Oil & Gas Lease No.
2. Name of Operator LRE OPERATING, LLC		7. Lease Name or Unit Agreement Name STALEY STATE
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401		8. Well Number #29
4. Well Location Unit Letter <u>O</u> : <u>505</u> feet from the <u>South</u> line and <u>2140</u> feet from the <u>East</u> line Section <u>30</u> Township <u>17-S</u> Range <u>28-E</u> NMPM <u>Eddy</u> County		9. OGRID Number 281994
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3639' GL		10. Pool name or Wildcat Red Lake, Glorieta-Yeso NE (96836)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE
 CLOSED-LOOP SYSTEM
 OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER: Completion

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
 SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On 12/1/14 PT 5-1/2" csg to 4000 psi-OK. Perfed lower Yeso @ 4648', 59', 72', 85', 90', 4703', 14', 30', 40', 52', 60', 68', 80', 90', 4800', 14', 28', 38', 48', 58', 66', 80', 88', 96', 4906', 16', 32', 42', 54', 68' w/1-0.41" spf. Total 30 holes. On 12/5/14, treated w/1499 gal 7.5% HCL acid. Fraced Yeso w/29,324# 100 mesh & 239,047# 40/70 Arizona sand in slick water. Set 5-1/2" CBP @ 4570' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 4118', 29', 50', 60', 73', 86', 4204', 14', 22', 35', 46', 60', 70', 80', 90', 4303', 16', 27', 40', 56', 66', 78', 86', 94', 4412', 22', 30', 39', 46', 56' w/1-0.41" spf. Total 30 holes. Treated w/1529 gal 7.5% HCL acid & fraced w/30,191# 100 mesh & 236,644# 40/70 Arizona sand in slick water.

Set 5-1/2" CBP @ 4060' & PT CBP & 5-1/2" csg to 3500 psi-OK. Perfed Yeso @ 3684', 94', 3702', 10', 25', 36', 43', 65', 78', 92', 3804', 17', 31', 43', 58', 64', 72', 88', 98' 3916', 27' 38', 46', 56', 62', 76', 91', 98', 4008' w/1-0.41" spf. Total 29 holes. Treated w/1532 gal 7.5% HCL acid & fraced w/30,591# 100 mesh & 234,002# 40/70 Arizona sand in slick water.

On 12/6/14, MIRUSU. CO after frac, drilled out CBPs @ 4060', & 4570', & CO to PBTD5018'. On 12/11/14, landed ESP on 2-7/8" 6.5# J-55 tbg @ 3521'. Released completion rig on 12/12/14.

Spud Date: 11/22/14

Drilling Rig Release Date: 11/29/14

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 12/12/14

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573

For State Use Only
 APPROVED BY: AR Dade TITLE Dist. AS Lewis DATE 12/19/14
 Conditions of Approval (if any):