

NM OIL CONSERVATION

JAN 12 2015

RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-005-60988

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

LG-4354

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other P&A

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter M : 810 feet from the South line and 660 feet from the West line

Section 17 Township 7S Range 25E NMPM Chaves County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3806' GR

7. Lease Name or Unit Agreement Name
Cocklebur RD State

8. Well Number

1

9. OGRID Number

025575

10. Pool name or Wildcat

Pecos Slope; Abo

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/22/14 - Pumped 30 bbls brine. NU BOP.

12/23/14 - RIH with GR/JB to 3700'. Set a 4-1/2" CIBP at 3682'. Loaded hole with 20 bbls brine.

12/29/14 - Tagged CIBP. Loaded hole with plugging mud. Spotted 25 sx Class "C" cement on top of CIBP.

12/30/14 - Perforated at 1477'. Squeezed 115 sx Class "C" cement. Displaced cement to 1100'.

1/5/15 - Tagged plug at 1015'. Perforated at 856'. Pumped 25 sx Class "C" Neat cement. Displaced to 756'.

1/6/15 - Tagged plug at 715'. Perforated 4 holes at 60'. Pumped cement and circulated. Did not set up. Pumped 30 sx Class "C" Neat cement and circulated out 8-5/8" x 5-1/2".

1/7/15 - Dug out cellar and cut off wellhead. Installed dry hole marker. Filled cellar. **WELL IS PLUGGED AND ABANDONED.**

Approved for plugging of well bore only.

Liability under bond is retained pending receipt

C-103 (Subsequent Report of Well Plugging)

which may be found at OCD Web Page under

www.cmrnd.state.nm.us/oed

Accepted for record

NMS NMOCD 2/16/15

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Reporting Supervisor DATE January 9, 2015Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: [Signature] TITLE [Signature] DATE 2/16/15

Conditions of Approval (if any):

Submit Subsequent C-103