

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED
OMB NO. 1004-0135
Expires: July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.**SUBMIT IN TRIPLICATE - Other instructions on reverse side.**

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		5. Lease Serial No. NMNM033775
2. Name of Operator MEWBOURNE OIL COMPANY		6. If Indian, Allottee or Tribe Name
3a. Address P O BOX 5270 HOBBS, NM 88241		7. If Unit or CA/Agreement, Name and/or No. NMNM133874
3b. Phone No. (include area code) Ph: 575-393-5905		8. Well Name and No. URSA 27 B2IL FED COM 1H
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sec 26 T18S R30E NWSW 1425FSL 903FWL 32.425426 N Lat, 103.565381 W Lon		9. API Well No. 30-015-42526-00-X1
		10. Field and Pool, or Exploratory LEO
		11. County or Parish, and State EDDY COUNTY, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Deepen
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Fracture Treat
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Plug and Abandon
	<input type="checkbox"/> Plug Back
	<input type="checkbox"/> Production (Start/Resume)
	<input type="checkbox"/> Reclamation
	<input type="checkbox"/> Recomplete
	<input type="checkbox"/> Temporarily Abandon
	<input type="checkbox"/> Water Disposal
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Well Integrity
	<input checked="" type="checkbox"/> Other Well Spud

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

08/12/14 Spud 17 1/2" hole. TD hole @ 380'. Ran 380' of 13 3/8" 48# H40 ST&C csg. Cmt w/400 lbs of Class C w/2% CaCl₂. Mixed @ 14.8#/g w/1.34 yd. Plug down @ 10:00 P.M. 08/12/14. Circ 159 sks of csg to the pit. At 3:00 A.M. 08/14/14, tested csg to 1250# for 30 mins, held OK. Drilled out with 12 1/4" bit.

Chart & Schematic attached.

Bond on file: NM1693 nationwide & NMB000919

800 2/11/15
Accepted for record
NMOCNATIONAL OIL CONSERVATION
ARTESIA DISTRICT
FEB 2 2015
RECEIVED

14. I hereby certify that the foregoing is true and correct.	
Electronic Submission #257323 verified by the BLM Well Information System For MEWBOURNE OIL COMPANY, sent to the Carlsbad Committed to AFMSS for processing by DEBORAH HAM on 01/15/2015 (15DMH03889F)	
Name (Printed/Typed) JACKIE LATHAN	Title AUTHORIZED REPRESENTATIVE
Signature (Electronic Submission)	Date 08/18/2014
THIS SPACE FOR FEDERAL OR STATE OFFICE USE	
BUREAU OF LAND MANAGEMENT CARLSBAD FIELD OFFICE	
Approved By	Title
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	
Office	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED ****

MAN WELDING SERVICES, INC.

Company Mowbourne Date 8-13-14

Lease 1159 27 BZIL Feat. Co. 14 County Eddy Co. N.M.

Drilling Contractor Patterson #41 Plug & Drill Pipe Size 12" C22 4 1/2 x 11

Accumulator Pressure: 3000 Manifold Pressure: 1550 Annular Pressure: 1375

Accumulator Function Test - OO&GO#2

To Check - USABLE FLUID IN THE NITROGEN BOTTLES (III.A.2.c.i. or ii or iii)

- o Make sure all rams and annular are open and if applicable HCR is closed.
- o Ensure accumulator is pumped up to working pressure! (Shut off all pumps)
- 1. Open HCR Valve. (If applicable).
- 2. Close annular.
- ~~N/A 3. Close all pipe rams~~
- ~~N/A 4. Open one set of the pipe rams to simulate closing the blind ram.~~
- 5. For 3 ram stacks, open the annular to achieve the 50+ % safety factor. (5M and greater systems).
- 6. Record remaining pressure 2200 psi. Test Fails if pressure is lower than required.
 - o a. (950 psi for a 1500 psi system) b. (1200 psi for a 2000 & 3000 psi system)
- 7. If annular is closed, open it at this time and close HCR.

To Check - PRECHARGE ON BOTTLES OR SPHERICAL (III.A.2.d.)

- o Start with manifold pressure at, or above, maximum acceptable pre-charge pressure:
 - a. (800 psi for a 1500 psi system) b. (1100 psi for 2000 and 3000 psi system)
- 1. Open bleed line to the tank, slowly. (gauge needle will drop at the lowest bottle pressure)
- 2. Close bleed line. Barely bump electric pump and see what pressure the needle jumps up to.
- 3. Record pressure drop 1000 psi. Test fails if pressure drops below minimum.
- o Minimum: a. (700 psi for a 1500 psi system) b. (900 psi for a 2000 & 3000 psi system)

To Check - THE CAPACITY OF THE ACCUMULATOR PUMPS (III.A.2.f.)


- o Isolate the accumulator bottles or spherical from the pumps & manifold.
- o Open the bleed off valve to the tank, (manifold psi should go to 0 psi) close bleed valve.
- 1. Open the HCR valve, (if applicable)
- 2. Close annular
- 3. With pumps only, time how long it takes to regain the required manifold pressure.
- 4. Record elapsed time 39 sec. Test fails if it takes over 2 minutes.
 - o a. (950 psi for a 1500 psi system) b. (1200 psi for a 2000 & 3000 psi system)



Pg. 1 of 1

Required BOP: _____ Installed BOP: _____

*** Check Valve Must Be Open/Disabled To Test Kill Line Valves ***

[illegible]


24 HR CHART

MIDNIGHT

96 MIN CLOCK

CHART 1053

PRINTED IN U.S.A.



Newport

Graphic Controls

URSA 27 BZIL Feet
Count/H

Eddy Co.
N.H.


Pa. Hous.
E. 41

DATE 8-13-74

BR B 0-5000-8
CHART #1

CHART 2 of 3

24 HR CHART
NOON



PRINTED IN U.S.A.

PRINTED IN U.S.A. 6 PM 5

