Form 3160-5 (August 2007)

UNITED STATES AND OIL CONSERVATION

UNITED STATES AND OIL CONSERVATION

ARTESIA O CIB CARTESIA

ARTESIA O CIB CARTESIA

DEPARTMENT OF THE INTERIORAR 0 2 2015

BUREAU OF LAND MANAGEMENT

IDRY NOTICES AND OF THE INTERIORAR 1 2 2015

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

5. Lease Serial No. NMLC-029426B

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter and
Abandoned well Use Form 3160-3 (APD) for such proposals

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2.						7. If Unit of CA/Agreement, Name and/or No.			
1. Type of Well						8. Well Name and No.			
Oil Well Gas Well Other							DERAL 361	1 < 308711>	<u> </u>
2. Name of Operator  APACHE CORPORATION <873>					9. API We 30-015	ll No. 5-42141		ř	
3. Address 3b. Phone No. (inc				(include ar	ea Code)	10. Field a	nd Pool or E	xploratory Area	. :
303 VE	432-818-1000 / 432-818-1168			FREN; GLORIETA YESO <26770>					
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					-	11. County	or Parish, S	tate !	
LOT M, SEC 3, T 17S, R 31E, 970' FSL & 537' FWL						EDDY COU	NTY, NM		:-
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA.									
TYPE OF SUBMISSION TYPE OF ACTI						N '	!	<u> </u>	, ,,
□ Notice of Intent       □ Acidize         □ Alter Casing       □ Casing Repair         □ Change Plans       □ Convert to Injection			New Co	Production (Start/Resume)  Water Shut-Off  Well Integrity  Well Integrity  Water Shut-Off  Well Integrity  Other  DRILLINGIOPS:ICA  & CEMENT-REPOR					
Attached the Bond to following completion	under which the on of the invol- npleted. Final site is ready fo	onal or recomplete horizonte work will be performed oved operations. If the opera Abandonment Notices must rinal inspection.  7/14/2014 SPUD;	r provide the Bond tion results in a mu	No. on file with Itiple completion	n BLM/BIA. Req on or recompletion	uired subseque in a new inte	ent reports must rval, a Form 31	be filed within 30 da 60-4 must be filed on	ays ice
7/14/2014	DRILLED 51'	TO 655'; TD SURFACE			,	;		To Married To American	· .
CIRC; TOH T/ RUN 13.375" CASING; CIRC HOLE CLEAN F/ CSG; NOTIFIED BLM									·
•							1	1	<b>;</b> ·
7/14/2014	SURFACE CS	ACE CSG 13.375" HOLE17.5", H-40, 48# SET 655'; FC @620'; RAN 8 CENTRALIZERS;						3/2/15	
	CMT WITH:	TH: 710 SX, CLASS C (14.8 PPG, 1.34 YLD)				( 1)		Jo VITTEOCIO	3
CIRC 230									
SURFACE CSG PRESSURE TEST: 1200 PSI/30 MIN –OK  REPORT CONTINUED ON PAGE 2.									
14. I hereby certify that the foregoing is true and correct.						AC(	CEPTED	FOR RECO	₹D
Name (Printed/Typed)  MICHELLE COOPER				Title DRILLING TEC					
	Much	111 1			RILLING TECH		FEB 2	5 2015	
Signature	m	<del></del>			0/16/2014		1 1 1 2	7 2013	_
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								am	
Approved by				Title		BI	CARLSBAD	ND MANAGEMENT FIELD OFFICE	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.									į
Title 18 LI>S C Section	1001 and Title	43 U.S.C. Section 1212 m	ake it a crime for an	v person know	ingly and willfully	to make to a	ny department o	r agency of the Unite	-d

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## **CROW FEDERAL 36H End of Well Sundry**

7/15-7/18 DRILL OUT CMT & SHOE TRACK; START DRLG INTERMEDIATE

DRL F/655'-3498'; TD; TOH FOR CSG

7/18/2014 <u>INTERMEDIATE CSG 9.625, HOLE 12.250 J55, 36# SET @ 3498' FC @3455'; 25 CENTRALIZERS; CIRC</u>

(LEAD) 840 SX CLASS C, 12.90 PPG, 1.92 YLD, (TAIL) 570 SX CLASS C, 14.8 WT, 1.3 YLD

CIRC 284 SX

7/18/2014 INTERMEDIATE CSG PRESSURE TEST 1200 PSI/ 30 MIN- OK

7/20-7/29 DRILL OUT CMT & SHOE TRACK; START DRLG PRODUCTION

DRLG F/3498' - 11061'; TD

8/03/2014 PRODUCTION CSG 7.0, HOLE 8.750, L80,29# SET @11034' FC @ 10,555'; 30 CENTRALIZERS; CIRC

(LEAD) 500 SX CLASS C, 12.60 PPG, 2.6 YLD,

(TAIL) 350 SX CLASS C, 13. WT, 1.4 YLD

CIRC 218 SX

PRODUCTION CSG PRESSURE TEST 2500 PSI/ 30 MIN- OK

8/4/2014 RIG RELEASED