NO. OF COPIES RECEIVED 3	Form C+103	
DISTRIBUTION	Supersedes Old	
SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65	
FILE		
U.S.G.S. PECEIVED	5a. Indicate Type of Lease	
	State Fee X	
	5. State Cil 6 Gas Lease No.	
DEC 26 1978		
SUNDRY NOTICES AND REFORTS ON WELLS		
	7. Unit Agreement Name	
Name of Cherdion	8. Farm of Lease Name	
Amoco Production Company 🗸	Teledyne 8	
. Address of Operator	9. Well No.	
P.O. Drawer "A", Levelland, Texas 79336		
i. Location of Well	10. Field and Fool, or Wildcat	
UNIT LETTER K 1980 FEET FROM THE South LINE AND 2180 FEET FROM	Wildcat Morrow	
UNIT LETTER FEET FROM THE LINE AND FEET FROM		
THE West LINE, SECTION 8 TOWNSHIP 23-S RANGE 29-E NMPM.		
w, -		
15. Elevation (Show whether DF, RT, GR, etc.) 2969.5 GR	12. County Eddy	
Check Appropriate Box To Indicate Nature of Notice, Report or Oth NOTICE OF INTENTION TO:		
PERFORM REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON	ALTERING CASING	
TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	F	
TEMPORARILY ABANDON	F	
TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	F	
TEMPORARILY ABANDON	PLUG AND A BANDONMENT	
TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	PLUG AND A BANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4"	PLUG AND ABANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CABINE CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) see RULE 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4" 40.5# K-55 ST & C casir Cemented with 1950 sx Howcolite plus 5#/sx Gilsonite, 1/4# Flocele/sx.	PLUG AND ABANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CABINE CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) see Rule 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4" 40.5# K-55 ST & C casir Cemented with 1950 sx Howcolite plus 5#/sx Gilsonite, 1/4# Flocele/sx, and 200 sx Class C plus 2% CACL, Circulated 184 sx PD 2:30 pm 12-8-75	PLUG AND ABANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CABINE CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) see RULE 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4" 40.5# K-55 ST & C casir Cemented with 1950 sx Howcolite plus 5#/sx Gilsonite, 1/4# Flocele/sx.	PLUG AND ABANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4" 40.5# K-55 ST & C casir Cemented with 1950 sx Howcolite plus 5#/sx Gilsonite, 1/4# Flocele/sx, and 200 sx Class C plus 2% CACL. Circulated 184 sx.PD 2:30 p.m. 12-8-7 hours. Test casing 1000# for 30 minutes. Test OK. Reduced hole to 9	PLUG AND ABANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4" 40.5# K-55 ST & C casir Cemented with 1950 sx Howcolite plus 5#/sx Gilsonite, 1/4# Flocele/sx, and 200 sx Class C plus 2% CACL. Circulated 184 sx.PD 2:30 p.m. 12-8-7 hours. Test casing 1000# for 30 minutes. Test OK. Reduced hole to 9	PLUG AND ABANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4" 40.5# K-55 ST & C casir Cemented with 1950 sx Howcolite plus 5#/sx Gilsonite, 1/4# Flocele/sx, and 200 sx Class C plus 2% CACL. Circulated 184 sx.PD 2:30 p.m. 12-8-7 hours. Test casing 1000# for 30 minutes. Test OK. Reduced hole to 9	PLUG AND ABANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4" 40.5# K-55 ST & C casir Cemented with 1950 sx Howcolite plus 5#/sx Gilsonite, 1/4# Flocele/sx, and 200 sx Class C plus 2% CACL. Circulated 184 sx.PD 2:30 p.m. 12-8-7 hours. Test casing 1000# for 30 minutes. Test OK. Reduced hole to 9	PLUG AND ABANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4" 40.5# K-55 ST & C casir Cemented with 1950 sx Howcolite plus 5#/sx Gilsonite, 1/4# Flocele/sx, and 200 sx Class C plus 2% CACL. Circulated 184 sx.PD 2:30 p.m. 12-8-7 hours. Test casing 1000# for 30 minutes. Test OK. Reduced hole to 9	PLUG AND ABANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4" 40.5# K-55 ST & C casir Cemented with 1950 sx Howcolite plus 5#/sx Gilsonite, 1/4# Flocele/sx, and 200 sx Class C plus 2% CACL. Circulated 184 sx.PD 2:30 p.m. 12-8-7 hours. Test casing 1000# for 30 minutes. Test OK. Reduced hole to 9	PLUG AND ABANDONMENT	
TEMPORARILY ABANDON Commence DRILLING OPNS. PULL OR ALTER CASING CHANGE PLANS OTHER OTHER 17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703. On 12-8-78, drilled to TD 2793' and ran 10 3/4" 40.5# K-55 ST & C casir Cemented with 1950 sx Howcolite plus 5#/sx Gilsonite, 1/4# Flocele/sx, and 200 sx Class C plus 2% CACL. Circulated 184 sx.PD 2:30 p.m. 12-8-7 hours. Test casing 1000# for 30 minutes. Test OK. Reduced hole to 9	PLUG AND ABANDONMENT	

 \therefore , I hereby certify that the information above is true and complete to the best of my knowledge and belief.

VILNED Nemis Erano	Assist.Admin.Analyst	DATE _	12-20-78
AVER ON U. a. Greenet	MILL SUPERVISOR DISTRICT II	DATE	DEC 2 7 1978
CONDITIONS OF APPROVAL, IF ANYI			

•

0& 4 NMOCC 1-Susp 1-Houston 1-DE

-