

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-005-63059
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2982
7. Lease Name or Unit Agreement Name Quincy AMQ State
8. Well Number 14
9. OGRID Number 025575
10. Pool name or Wildcat Acme San Andres, Southeast

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐ RECEIVED

2. Name of Operator
Yates Petroleum Corporation

DEC - 9 2005

3. Address of Operator
105 S. 4th Street, Artesia, NM 88210

4. Well Location
Unit Letter N : 990 feet from the South line and 2310 feet from the West line
Section 12 Township 8S Range 27E NMPM Chaves County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3939'GR

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDON ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Yates Petroleum Corporation plans to plug and abandon this well as follows:

1. RU safety equipment as needed.
2. Set a 5-1/2" CIBP at 2103' with 35' cement on top.
3. Circulate hole with 9.5# mud.
4. TIH to 1630' and spot 100' (25 sx) cement plug inside casing.
5. Shoot squeeze holes at 530'.
6. Spot 50 sx cement in and out of casing from 530'-430'. Tag plug.
7. Shoot squeeze holes at 60'.
8. Circulate 20 sx cement in and out of casing to surface. Tag plug.
9. Cut off wellhead and install dry hole marker.

NOTE: Yates Petroleum Corporation will use steel pits and no earth pits

Notify OCD 24 hrs. prior to
any work done.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE December 7, 2005

Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471

For State Use Only


APPROVED BY: Phil Hansen TITLE Field Eng DATE 12/14/05

Conditions of Approval (if any):

WELL NAME: Quincy Arroyo #14 FIELD AREA: SE Acme
 LOCATION: 990' FSL & 2310' FWL - Sec 12-85-27E, Chaves Co, NM
 GL: 3939' ZERO: 6' AGL: 3945'
 KB: 3945' ORIG. DRLG./COMPL. DATE: 8/95
 COMMENTS: _____

CASING PROGRAM:

SIZE/WT./GR./CONN.	DEPTH SET
8 5/8" 24# J-55 @ 470'	
5 1/2" 15.5# J-55 @ 2219'	



Before

TOPs

San Andres 1580'

- SKETCH NOT TO SCALE -

REVISED: _____

WELL NAME: Quincy Arroyo #14

FIELD AREA: SE Acme

LOCATION: 990' FSL & 2310' FWL - Sec 12-85-27E, Chaves Co, NM


GL: 3939' ZERO: 6' AGL: 3945'

KB: 3945' ORIG. DRLG./COMPL. DATE: 8/95

COMMENTS: _____

CASING PROGRAM:

SIZE/WT./GR./CONN.	DEPTH SET
8 5/8" 24# J-55 @ 470'	
5 1/2" 15.5# J-55 @ 2219'	



60' Surface Plug
In & Out of Casing
12 1/4" hole

100' Plug Intout
of casing 530' - 430'
8 5/8" @ 470'
cmt 250sx
circ 60sx

TOC

7 7/8" hole

100' Plug In Casing
1,630' - 1,530'

CIBP @ 2,103' w/35' cmt on top

San Andres Perf's
2153' - 2206' (54 holes)

FC @ 2214'

5 1/2" @ 2219'
cmt 300sx

After

TOPs

San Andres 1,580'

- SKETCH NOT TO SCALE -

REVISED: _____