

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-015-34423

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator  
Gruy Petroleum Management Co.

3. Address of Operator  
PO Box 140907; Irving, TX 75014-0907

4. Well Location

Unit Letter A : 660 feet from the North line and 660 feet from the East line  
Section 2 Township 25S Range 25E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3554' GR

Pit or Below-grade Tank Application X or Closure ☐

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ P AND A ☐  
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

01-25-06 Spudded 17-1/2" hole. Drilled to 215'. Ran 5 jts 13-3/8" 48# H-40 ST&C casing. Cemented with 250sx Premium Plus + 2% CaCl. Circulated 41sx to steel pits. WOC 24.5 hours. Pressure tested casing to 500psi for 30 minutes.  
02-01-06 Drilled 12-1/4" hole to 3145'. Ran 78 jts 9-5/8" 40# J-55 LT&C casing to 3145'. Cemented with lead 1125sx Interfill C + 0.25# Flocele and tail 200sx Premium Plus + 1% CaCl. Circulated 119sx to steel pits. WOC 19.25 hours. Pressure tested casing to 1000psi for 30 minutes.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Natalie Krueger TITLE Regulatory Technician DATE February 16, 2006

Type or print name Natalie Krueger email address: nkrueger@cimarex.com Telephone No. 972-401-3111

For State Use Only

APPROVED BY: FOR RECORDS ONLY TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Conditions of Approval (if any):