

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-005-63786
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name SEABISQUIT
8. Well Number 002
9. OGRID Number 230387
10. Pool name or Wildcat

Pit or Below-grade Tank Application ☐ or Closure ☐
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐	RECEIVED
2. Name of Operator PARALLEL PETROLEUM CORPORATION	MAR 02 2006
3. Address of Operator 1004 N. BIG SPRING, SUITE 400, MIDLAND, TX 79701	OCU-ARTESIA
4. Well Location Unit Letter P : 400 feet from the S line and 760 feet from the E line Section 33 Township 14S Range 26E NMPM CHAVEZ County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) GR 3451	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
OTHER: ☐		OTHER: SCIENTIFIC DRILLING SURVEY ☒	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

01-30-2006: ATTACHED IS SCIENTIFIC DRILLING INTERNAIONAL'S SURVEY REPORT, JOB NUMBER 32K0106089 (2 PAGES)

02-24-2006: ATTACHED IS SCIENTIFIC DRILLING INTERNATIONAL'S PATHFINDER REPORT, JOB NUMBER J-WT-0601-0025-WTWT (4 PAGES)

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ray M. Carmichael TITLE SR PROD & REG TECHNICIAN DATE 02-28-2006

Type or print name
For State Use Only

E-mail address:

Telephone No.

FOR RECORDS ONLY

APPROVED BY: _____ TITLE _____ DATE MAR 02 2006

Conditions of Approval (if any):



Scientific Drilling International Survey Report

Company: PARALLEL PETROLEUM
Field: Wildcat
Site: Chaves County, NM
Well: Seabiscuit #2
Wellpath: VH - Job #32K0106089

Date: 2006-01-30 **Time:** 10:01:14 **Page:** 1
Co-ordinate(NE) Reference: Site: Chaves County, NM, Grid North
Vertical (TVD) Reference: SITE 0.0
Section (VS) Reference: Well (0.00N,0.00E,164.17Azi)
Survey Calculation Method: Minimum Curvature **Db:** Sybase

Survey: 01/29/06 **Start Date:** 2006-01-30
Company: Scientific Drilling Internatio **Engineer:** Gonzales/Madrid
Tool: Keeper;Keeper Gyro **Tied-to:** From Surface

Survey

MD ft	Incl deg	Azim deg	TVD ft	VS ft	N/S ft	E/W ft	DLS deg/100ft	ClsD ft	ClsA deg
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.52	54.90	100.00	-0.15	0.26	0.37	0.52	0.45	54.90
200.00	0.96	50.99	199.99	-0.63	1.05	1.39	0.44	1.74	53.02
300.00	1.03	48.92	299.97	-1.34	2.17	2.72	0.08	3.48	51.47
400.00	0.75	62.34	399.96	-1.86	3.06	3.98	0.35	5.02	52.43
500.00	0.66	75.63	499.96	-1.98	3.51	5.12	0.19	6.20	55.56
600.00	0.78	77.75	599.95	-1.92	3.80	6.34	0.12	7.39	59.09
700.00	0.81	95.90	699.94	-1.62	3.87	7.71	0.25	8.62	63.36
800.00	1.14	163.08	799.93	-0.36	2.84	8.70	1.11	9.15	71.90
900.00	1.17	166.47	899.91	1.65	0.90	9.23	0.07	9.27	84.44
1000.00	1.29	203.95	999.88	3.54	-1.12	9.01	0.80	9.08	97.10
1100.00	1.54	195.91	1099.85	5.55	-3.44	8.19	0.32	8.88	112.82
1200.00	1.39	190.60	1199.82	7.77	-5.93	7.59	0.20	9.63	127.98
1300.00	1.32	191.21	1299.79	9.89	-8.25	7.15	0.07	10.92	139.10
1400.00	1.38	194.96	1399.77	11.95	-10.54	6.61	0.11	12.45	147.91
1500.00	1.28	188.36	1499.74	14.00	-12.81	6.14	0.18	14.21	154.40
1600.00	1.25	184.04	1599.71	16.05	-15.00	5.90	0.10	16.12	158.54
1700.00	1.23	181.05	1699.69	18.10	-17.17	5.80	0.07	18.12	161.32
1800.00	1.24	179.66	1799.67	20.17	-19.32	5.79	0.03	20.17	163.32
1900.00	1.15	176.56	1899.65	22.19	-21.40	5.86	0.11	22.19	164.70
2000.00	1.13	177.97	1999.63	24.13	-23.39	5.95	0.03	24.14	165.72
2100.00	1.01	177.08	2099.61	25.95	-25.26	6.03	0.12	25.97	166.57
2200.00	1.12	179.89	2199.59	27.74	-27.12	6.08	0.12	27.79	167.36
2300.00	0.93	181.76	2299.58	29.46	-28.90	6.06	0.19	29.53	168.17
2400.00	0.84	189.33	2399.56	30.90	-30.44	5.91	0.15	31.01	169.01
2500.00	0.71	192.62	2499.55	32.10	-31.77	5.66	0.14	32.27	169.90
2600.00	0.53	198.33	2599.55	33.03	-32.81	5.38	0.19	33.25	170.69
2700.00	0.50	195.64	2699.54	33.79	-33.67	5.11	0.04	34.05	171.36
2800.00	0.53	210.93	2799.54	34.48	-34.49	4.76	0.14	34.81	172.14
2900.00	0.49	226.91	2899.54	34.99	-35.17	4.21	0.15	35.43	173.18
3000.00	0.49	237.53	2999.53	35.31	-35.70	3.54	0.09	35.87	174.34
3100.00	0.56	235.30	3099.53	35.59	-36.20	2.77	0.07	36.31	175.62
3200.00	0.56	240.22	3199.52	35.86	-36.72	1.95	0.05	36.78	176.97
3300.00	0.65	243.75	3299.52	36.08	-37.22	1.01	0.10	37.23	178.44
3400.00	0.68	231.38	3399.51	36.42	-37.84	0.04	0.15	37.84	179.94
3500.00	0.82	238.39	3499.50	36.84	-38.59	-1.03	0.17	38.60	181.53
3600.00	0.61	239.69	3599.50	37.17	-39.23	-2.10	0.21	39.29	183.06
3700.00	0.57	235.63	3699.49	37.46	-39.78	-2.97	0.06	39.89	184.27
3800.00	0.51	217.71	3799.49	37.88	-40.41	-3.65	0.18	40.58	185.17
3900.00	0.45	202.75	3899.48	38.45	-41.13	-4.08	0.14	41.33	185.66
4000.00	0.55	131.05	3999.48	39.16	-41.80	-3.87	0.59	41.98	185.29
4100.00	0.61	115.85	4099.47	39.92	-42.35	-3.03	0.16	42.46	184.09
4200.00	0.81	115.28	4199.47	40.74	-42.88	-1.91	0.20	42.93	182.55
4300.00	1.17	100.26	4299.45	41.65	-43.37	-0.26	0.44	43.37	180.35
4400.00	1.16	111.34	4399.43	42.71	-43.92	1.68	0.23	43.95	177.81
4500.00	1.03	119.67	4499.41	43.96	-44.73	3.41	0.21	44.86	175.64
4600.00	0.93	122.46	4599.40	45.21	-45.61	4.87	0.11	45.87	173.90
4700.00	0.98	123.56	4699.38	46.47	-46.52	6.27	0.05	46.94	172.32
4800.00	0.92	142.66	4799.37	47.86	-47.63	7.47	0.32	48.21	171.09



Scientific
Drilling

Scientific Drilling International

Survey Report

Company: PARALLEL PETROLEUM
Field: Wildcat
Site: Chaves County, NM
Well: Seabiscuit #2
Wellpath: VH - Job #32K0106089

Date: 2006-01-30 Time: 10:01:14 Page: 2
Co-ordinate(NE) Reference: Site: Chaves County, NM, Grid North
Vertical (TVD) Reference: SITE 0.0
Section (VS) Reference: Well (0.00N,0.00E,164.17Azi)
Survey Calculation Method: Minimum Curvature Db: Sybase

Survey

MD ft	Incl deg	Azim deg	TVD ft	VS ft	N/S ft	E/W ft	DLS deg/100ft	ClsD ft	ClsA deg
4900.00	1.07	136.83	4899.36	49.44	-48.95	8.60	0.18	49.70	170.04
5000.00	1.27	126.98	4999.33	51.15	-50.30	10.12	0.28	51.31	168.62
5100.00	1.07	124.53	5099.31	52.75	-51.49	11.77	0.21	52.82	167.12
5200.00	0.75	126.81	5199.30	53.99	-52.42	13.07	0.32	54.02	166.00
5300.00	0.80	126.14	5299.29	55.06	-53.22	14.15	0.05	55.07	165.11
5400.00	0.64	139.45	5399.28	56.12	-54.06	15.08	0.23	56.12	164.41
5450.00	0.64	139.99	5449.28	56.63	-54.48	15.44	0.01	56.63	164.17

Pathfinder

Survey Report

Page 1
Job No: J-WT-0601-0025-WTWT
Date: 2/24/2006
Time: 9:34 am
Wellpath ID: 06010025
Date Created: 1/31/2006
Last Revision: 2/24/2006

Calculated using the Minimum Curvature Method
Computed using PDS VER2.2.6
Vertical Section Plane: 360.00 deg.

Survey Reference: WELLHEAD
Vertical Section Reference: WELLHEAD
Closure Reference: WELLHEAD
TVD Reference: WELLHEAD

Parallel Petroleum
Seabiscuit #2
Patriot #1
Chaves County, New Mexico
Sec 33-T14S-R26E
JWT-0601-0025-WTWT

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	Course Length (ft)	TVD (ft)	Vertical Section (ft)	T O T A L Rectangular Offsets (ft) (ft)		Closure Dist. Dir. (ft) (deg.)	DLS (dg/100ft)
Tie From Scientific Drilling Gyro Survey									
4900.00	1.10	136.80	0.00	4899.36	-48.97	48.97 S	8.61 E	49.72@170.03	0.00
First PathFindr MWD Survey									
4926.00	0.79	50.30	26.00	4925.36	-49.04	49.04 S	8.92 E	49.84@169.69	5.06
4957.00	2.55	14.44	31.00	4956.34	-48.23	48.23 S	9.26 E	49.11@169.14	6.34
4989.00	5.80	8.82	32.00	4988.25	-45.95	45.95 S	9.68 E	46.95@168.10	10.22
5020.00	9.32	8.02	31.00	5018.98	-41.91	41.91 S	10.27 E	43.15@166.23	11.36
5051.00	13.45	7.32	31.00	5049.36	-35.85	35.85 S	11.08 E	37.52@162.82	13.33
5083.00	18.03	6.09	32.00	5080.16	-27.23	27.23 S	12.08 E	29.79@156.07	14.35
5114.00	22.95	4.60	31.00	5109.19	-16.42	16.42 S	13.08 E	20.99@141.48	15.96
5145.00	28.58	3.72	31.00	5137.09	-2.99	2.99 S	14.04 E	14.36@102.02	18.20
5177.00	34.12	2.66	32.00	5164.41	13.63	13.63 N	14.96 E	20.23@ 47.66	17.40
5208.00	39.75	359.85	31.00	5189.18	32.24	32.24 N	15.33 E	35.70@ 25.44	18.96
5240.00	45.11	358.01	32.00	5212.79	53.81	53.81 N	14.91 E	55.84@ 15.49	17.19
5271.00	50.30	0.73	31.00	5233.65	76.73	76.73 N	14.68 E	78.12@ 10.83	17.95
5302.00	55.84	0.12	31.00	5252.27	101.50	101.50 N	14.86 E	102.58@ 8.33	17.94
5334.00	61.64	359.59	32.00	5268.87	128.84	128.84 N	14.79 E	129.69@ 6.55	18.18
5366.00	66.39	359.50	32.00	5282.88	157.60	157.60 N	14.56 E	158.27@ 5.28	14.85
5397.00	70.96	359.94	31.00	5294.15	186.47	186.47 N	14.42 E	187.03@ 4.42	14.80
5429.00	74.74	359.76	32.00	5303.59	217.04	217.04 N	14.34 E	217.51@ 3.78	11.82
5460.00	76.41	359.76	31.00	5311.31	247.06	247.06 N	14.22 E	247.47@ 3.29	5.39
5491.00	79.14	359.76	31.00	5317.87	277.36	277.36 N	14.09 E	277.71@ 2.91	8.81
5523.00	80.46	359.68	32.00	5323.54	308.85	308.85 N	13.93 E	309.16@ 2.58	4.13
5554.00	82.31	359.50	31.00	5328.18	339.50	339.50 N	13.71 E	339.77@ 2.31	6.00
5586.00	84.77	359.68	32.00	5331.78	371.29	371.29 N	13.49 E	371.54@ 2.08	7.71
5617.00	88.37	359.76	31.00	5333.64	402.23	402.23 N	13.34 E	402.45@ 1.90	11.62
5648.00	90.66	359.85	31.00	5333.90	433.23	433.23 N	13.23 E	433.43@ 1.75	7.39
5680.00	91.36	359.41	32.00	5333.34	465.22	465.22 N	13.02 E	465.40@ 1.60	2.58
5711.00	91.63	359.32	31.00	5332.53	496.21	496.21 N	12.68 E	496.37@ 1.46	0.92
5733.00	91.45	359.15	22.00	5331.94	518.20	518.20 N	12.39 E	518.35@ 1.37	1.13
5765.00	91.98	359.15	32.00	5330.98	550.18	550.18 N	11.91 E	550.31@ 1.24	1.66
5796.00	92.42	359.59	31.00	5329.79	581.16	581.16 N	11.57 E	581.27@ 1.14	2.01
5827.00	91.71	359.24	31.00	5328.67	612.13	612.13 N	11.26 E	612.24@ 1.05	2.55
5859.00	90.84	358.97	32.00	5327.96	644.12	644.12 N	10.76 E	644.21@ 0.96	2.85
5890.00	89.96	358.62	31.00	5327.74	675.11	675.11 N	10.10 E	675.19@ 0.86	3.05

Pathfinder Survey Report

Page 2
Date: 2/24/2006
Wellpath ID: 06010025

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	Course Length (ft)	TVD (ft)	Vertical Section (ft)	T O T A L Rectangular Offsets (ft)		Closure Dist. (ft)	Dir. (deg.)	DLS (dg/100ft)
5922.00	89.96	358.53	32.00	5327.77	707.10	707.10 N	9.31 E	707.17@	0.75	0.28
5953.00	90.22	358.18	31.00	5327.72	738.09	738.09 N	8.42 E	738.14@	0.65	1.41
5984.00	90.13	357.74	31.00	5327.62	769.07	769.07 N	7.31 E	769.11@	0.54	1.45
6016.00	90.22	357.74	32.00	5327.52	801.05	801.05 N	6.05 E	801.07@	0.43	0.28
6047.00	90.48	357.65	31.00	5327.33	832.02	832.02 N	4.81 E	832.03@	0.33	0.89
6079.00	90.57	358.18	32.00	5327.04	864.00	864.00 N	3.64 E	864.01@	0.24	1.68
6110.00	90.66	358.53	31.00	5326.71	894.98	894.98 N	2.75 E	894.99@	0.18	1.17
6142.00	90.04	359.06	32.00	5326.51	926.98	926.98 N	2.08 E	926.98@	0.13	2.55
6173.00	89.87	359.15	31.00	5326.54	957.97	957.97 N	1.59 E	957.97@	0.10	0.62
6204.00	90.04	359.32	31.00	5326.56	988.97	988.97 N	1.18 E	988.97@	0.07	0.78
6236.00	89.96	359.15	32.00	5326.56	1020.97	1020.97 N	0.75 E	1020.97@	0.04	0.59
6267.00	90.04	359.32	31.00	5326.56	1051.96	1051.96 N	0.34 E	1051.96@	0.02	0.61
6299.00	90.31	359.94	32.00	5326.46	1083.96	1083.96 N	0.13 E	1083.96@	0.01	2.11
6330.00	90.04	1.35	31.00	5326.37	1114.96	1114.96 N	0.48 E	1114.96@	0.02	4.63
6362.00	90.40	1.70	32.00	5326.25	1146.95	1146.95 N	1.33 E	1146.95@	0.07	1.57
6393.00	90.31	1.87	31.00	5326.06	1177.93	1177.93 N	2.30 E	1177.93@	0.11	0.62
6424.00	90.40	1.52	31.00	5325.86	1208.92	1208.92 N	3.22 E	1208.92@	0.15	1.17
6456.00	90.48	1.43	32.00	5325.62	1240.91	1240.91 N	4.04 E	1240.91@	0.19	0.38
6488.00	90.40	1.35	32.00	5325.37	1272.90	1272.90 N	4.82 E	1272.90@	0.22	0.35
6520.00	90.48	1.08	32.00	5325.13	1304.89	1304.89 N	5.49 E	1304.90@	0.24	0.88
6552.00	90.48	0.91	32.00	5324.86	1336.88	1336.88 N	6.05 E	1336.90@	0.26	0.53
6583.00	90.75	0.91	31.00	5324.53	1367.88	1367.88 N	6.54 E	1367.89@	0.27	0.87
6615.00	90.84	1.17	32.00	5324.08	1399.87	1399.87 N	7.12 E	1399.89@	0.29	0.86
6647.00	90.66	0.82	32.00	5323.66	1431.86	1431.86 N	7.68 E	1431.88@	0.31	1.23
6679.00	90.40	0.47	32.00	5323.37	1463.86	1463.86 N	8.04 E	1463.88@	0.31	1.36
6711.00	90.48	0.64	32.00	5323.12	1495.85	1495.85 N	8.35 E	1495.88@	0.32	0.59
6742.00	90.31	0.29	31.00	5322.91	1526.85	1526.85 N	8.60 E	1526.88@	0.32	1.26
6774.00	89.87	359.85	32.00	5322.86	1558.85	1558.85 N	8.64 E	1558.88@	0.32	1.94
6806.00	89.34	359.24	32.00	5323.08	1590.85	1590.85 N	8.39 E	1590.87@	0.30	2.53
6838.00	89.16	359.06	32.00	5323.50	1622.84	1622.84 N	7.91 E	1622.86@	0.28	0.80
6870.00	89.52	359.24	32.00	5323.87	1654.84	1654.84 N	7.44 E	1654.85@	0.26	1.26
6901.00	89.08	358.88	31.00	5324.24	1685.83	1685.83 N	6.93 E	1685.85@	0.24	1.83
6933.00	89.16	359.24	32.00	5324.74	1717.82	1717.82 N	6.40 E	1717.83@	0.21	1.15
6965.00	90.13	359.76	32.00	5324.93	1749.82	1749.82 N	6.12 E	1749.83@	0.20	3.44
6997.00	90.40	359.85	32.00	5324.79	1781.82	1781.82 N	6.01 E	1781.83@	0.19	0.89
7028.00	90.92	0.03	31.00	5324.43	1812.82	1812.82 N	5.98 E	1812.83@	0.19	1.78
7060.00	91.10	0.12	32.00	5323.87	1844.81	1844.81 N	6.02 E	1844.82@	0.19	0.63
7092.00	91.28	359.94	32.00	5323.20	1876.81	1876.81 N	6.04 E	1876.82@	0.18	0.80
7124.00	91.36	0.12	32.00	5322.46	1908.80	1908.80 N	6.06 E	1908.81@	0.18	0.62
7156.00	90.84	0.73	32.00	5321.85	1940.79	1940.79 N	6.30 E	1940.80@	0.19	2.50
7187.00	90.84	0.47	31.00	5321.40	1971.79	1971.79 N	6.62 E	1971.80@	0.19	0.84
7219.00	90.84	0.47	32.00	5320.93	2003.78	2003.78 N	6.88 E	2003.79@	0.20	0.00
7251.00	91.19	0.73	32.00	5320.36	2035.77	2035.77 N	7.22 E	2035.79@	0.20	1.36
7283.00	91.45	0.64	32.00	5319.62	2067.76	2067.76 N	7.60 E	2067.78@	0.21	0.86
7314.00	91.01	0.99	31.00	5318.96	2098.75	2098.75 N	8.04 E	2098.77@	0.22	1.81
7346.00	90.84	1.17	32.00	5318.44	2130.74	2130.74 N	8.64 E	2130.76@	0.23	0.77
7377.00	90.66	0.91	31.00	5318.03	2161.73	2161.73 N	9.21 E	2161.75@	0.24	1.02
7409.00	90.40	0.73	32.00	5317.74	2193.73	2193.73 N	9.66 E	2193.75@	0.25	0.99

Pathfinder Survey Report

Page 3
Date: 2/24/2006
Wellpath ID: 06010025

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	Course Length (ft)	TVD (ft)	Vertical Section (ft)	T O T A L Rectangular (ft)	Offsets (ft)	Closure Dist. (ft)	Dir. (deg.)	DLS (dg/100ft)
7441.00	90.31	0.64	32.00	5317.54	2225.73	2225.73 N	10.05 E	2225.75@	0.26	0.40
7473.00	90.40	0.55	32.00	5317.34	2257.72	2257.72 N	10.38 E	2257.75@	0.26	0.40
7504.00	90.66	0.55	31.00	5317.05	2288.72	2288.72 N	10.68 E	2288.75@	0.27	0.84
7536.00	90.66	0.38	32.00	5316.69	2320.72	2320.72 N	10.94 E	2320.74@	0.27	0.53
7568.00	90.84	0.55	32.00	5316.27	2352.71	2352.71 N	11.20 E	2352.74@	0.27	0.77
7600.00	90.92	0.55	32.00	5315.78	2384.71	2384.71 N	11.50 E	2384.74@	0.28	0.25
7631.00	90.66	0.47	31.00	5315.35	2415.71	2415.71 N	11.78 E	2415.73@	0.28	0.88
7663.00	90.66	0.29	32.00	5314.98	2447.70	2447.70 N	11.99 E	2447.73@	0.28	0.56
7695.00	90.66	0.29	32.00	5314.61	2479.70	2479.70 N	12.15 E	2479.73@	0.28	0.00
7727.00	89.96	0.03	32.00	5314.44	2511.70	2511.70 N	12.24 E	2511.73@	0.28	2.33
7759.00	89.69	359.85	32.00	5314.54	2543.70	2543.70 N	12.21 E	2543.73@	0.28	1.01
7790.00	90.66	0.12	31.00	5314.44	2574.70	2574.70 N	12.20 E	2574.73@	0.27	3.25
7822.00	91.10	0.38	32.00	5313.95	2606.69	2606.69 N	12.34 E	2606.72@	0.27	1.60
7854.00	91.28	0.12	32.00	5313.28	2638.69	2638.69 N	12.48 E	2638.72@	0.27	0.99
7886.00	90.04	359.41	32.00	5312.92	2670.68	2670.68 N	12.35 E	2670.71@	0.26	4.47
7917.00	89.96	359.24	31.00	5312.92	2701.68	2701.68 N	11.98 E	2701.71@	0.25	0.61
7949.00	89.96	358.97	32.00	5312.94	2733.68	2733.68 N	11.48 E	2733.70@	0.24	0.84
7981.00	90.04	359.06	32.00	5312.94	2765.67	2765.67 N	10.93 E	2765.69@	0.23	0.38
8013.00	90.40	359.15	32.00	5312.81	2797.67	2797.67 N	10.43 E	2797.69@	0.21	1.16
8040.00	90.92	359.32	27.00	5312.50	2824.66	2824.66 N	10.07 E	2824.68@	0.20	2.03
8076.00	89.96	359.50	36.00	5312.23	2860.66	2860.66 N	9.70 E	2860.68@	0.19	2.71
8107.00	89.87	359.59	31.00	5312.27	2891.66	2891.66 N	9.46 E	2891.68@	0.19	0.41
8139.00	89.43	359.94	32.00	5312.47	2923.66	2923.66 N	9.33 E	2923.67@	0.18	1.76
8170.00	89.34	359.41	31.00	5312.80	2954.66	2954.66 N	9.15 E	2954.67@	0.18	1.73
8202.00	88.90	359.24	32.00	5313.29	2986.65	2986.65 N	8.77 E	2986.66@	0.17	1.47
8234.00	89.25	359.24	32.00	5313.81	3018.64	3018.64 N	8.35 E	3018.66@	0.16	1.09
8266.00	89.87	359.15	32.00	5314.06	3050.64	3050.64 N	7.90 E	3050.65@	0.15	1.96
8298.00	90.48	359.41	32.00	5313.96	3082.64	3082.64 N	7.50 E	3082.65@	0.14	2.07
8329.00	90.66	359.15	31.00	5313.65	3113.63	3113.63 N	7.11 E	3113.64@	0.13	1.02
8361.00	90.84	358.88	32.00	5313.23	3145.63	3145.63 N	6.56 E	3145.63@	0.12	1.01
8393.00	91.19	358.97	32.00	5312.66	3177.61	3177.61 N	5.96 E	3177.62@	0.11	1.13
8425.00	90.48	358.97	32.00	5312.20	3209.61	3209.61 N	5.38 E	3209.61@	0.10	2.22
8457.00	90.13	358.80	32.00	5312.03	3241.60	3241.60 N	4.76 E	3241.60@	0.08	1.22
8488.00	90.22	358.71	31.00	5311.93	3272.59	3272.59 N	4.09 E	3272.59@	0.07	0.41
8520.00	89.87	359.32	32.00	5311.91	3304.59	3304.59 N	3.54 E	3304.59@	0.06	2.20
8552.00	90.04	359.15	32.00	5311.93	3336.58	3336.58 N	3.11 E	3336.58@	0.05	0.75
8584.00	90.48	359.15	32.00	5311.79	3368.58	3368.58 N	2.63 E	3368.58@	0.04	1.38
8616.00	90.92	359.59	32.00	5311.40	3400.58	3400.58 N	2.28 E	3400.58@	0.04	1.94
8648.00	91.19	359.85	32.00	5310.81	3432.57	3432.57 N	2.13 E	3432.57@	0.04	1.17
8679.00	90.48	359.94	31.00	5310.35	3463.57	3463.57 N	2.07 E	3463.57@	0.03	2.31
8711.00	90.31	359.85	32.00	5310.13	3495.56	3495.56 N	2.01 E	3495.57@	0.03	0.60
8743.00	90.92	359.94	32.00	5309.79	3527.56	3527.56 N	1.95 E	3527.56@	0.03	1.93
8775.00	91.36	0.29	32.00	5309.15	3559.56	3559.56 N	2.02 E	3559.56@	0.03	1.76
8807.00	91.01	0.82	32.00	5308.49	3591.55	3591.55 N	2.33 E	3591.55@	0.04	1.98
8838.00	91.19	0.73	31.00	5307.90	3622.54	3622.54 N	2.74 E	3622.54@	0.04	0.65
8870.00	90.13	0.82	32.00	5307.53	3654.53	3654.53 N	3.18 E	3654.53@	0.05	3.32
8902.00	89.43	0.91	32.00	5307.65	3686.53	3686.53 N	3.66 E	3686.53@	0.06	2.21
8933.00	89.16	0.20	31.00	5308.03	3717.53	3717.53 N	3.96 E	3717.53@	0.06	2.45

Pathfinder Survey Report

Page 4
Date: 2/24/2006
Wellpath ID: 06010025

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	Course Length (ft)	TVD (ft)	Vertical Section (ft)	T O T A L Rectangular Offsets (ft)	Closure Dist. (ft)	Dir. (deg.)	DLS (dg/100ft)
8965.00	89.25	0.03	32.00	5308.48	3749.52	3749.52 N	4.02 E	3749.52@	0.06
8997.00	89.87	0.12	32.00	5308.72	3781.52	3781.52 N	4.07 E	3781.52@	0.06
9029.00	90.57	0.29	32.00	5308.60	3813.52	3813.52 N	4.18 E	3813.52@	0.06
9060.00	90.66	0.29	31.00	5308.27	3844.52	3844.52 N	4.34 E	3844.52@	0.06
9092.00	90.84	0.03	32.00	5307.85	3876.52	3876.52 N	4.43 E	3876.52@	0.07
9124.00	90.66	359.76	32.00	5307.43	3908.51	3908.51 N	4.37 E	3908.51@	0.06
9156.00	90.48	359.59	32.00	5307.11	3940.51	3940.51 N	4.19 E	3940.51@	0.06
9187.00	90.13	359.06	31.00	5306.95	3971.51	3971.51 N	3.82 E	3971.51@	0.06
9219.00	89.87	358.71	32.00	5306.95	4003.50	4003.50 N	3.20 E	4003.50@	0.05
9251.00	89.60	358.18	32.00	5307.09	4035.49	4035.49 N	2.33 E	4035.49@	0.03
9282.00	89.87	358.53	31.00	5307.24	4066.48	4066.48 N	1.44 E	4066.48@	0.02
9314.00	89.96	358.62	32.00	5307.28	4098.47	4098.47 N	0.65 E	4098.47@	0.01
9345.00	90.04	358.27	31.00	5307.28	4129.45	4129.45 N	0.20W	4129.45@360.00	1.16
9377.00	89.87	358.01	32.00	5307.31	4161.44	4161.44 N	1.23W	4161.44@359.98	0.97
Projection To The Bit 9426.00	89.87	358.01	49.00	5307.42	4210.41	4210.41 N	2.94W	4210.41@359.96	0.00