

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
OMB NO. 1004-0135  
Expires: July 31, 2010

**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*

**Carlsbad Field Office**  
**OCD Artesia**

5. Lease Serial No.  
NMLC061581

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

8. Well Name and No.  
FULLER 13 24 B2LM FED COM 1H

9. API Well No.  
30-015-43009-00-X1

10. Field and Pool, or Exploratory  
WILDCAT

11. County or Parish, and State  
EDDY COUNTY, NM

**SUBMIT IN TRIPLICATE - Other instructions on reverse side.**

1. Type of Well  
 Oil Well  Gas Well  Other

2. Name of Operator  
MEWBOURNE OIL COMPANY  
Contact: JACKIE LATHAN  
E-Mail: jlathan@mewbourne.com

3a. Address  
P O BOX 5270  
HOBBS, NM 88241

3b. Phone No. (include area code)  
Ph: 575-393-5905

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
Sec 13 T26S R29E NWSW 2620FSL 330FWL  
32.041598 N Lat, 103.944007 W Lon

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input checked="" type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

Mewbourne Oil Co. has would like to make the following change to the approved casing design:

Deepen 13 3/8" surface casing from 625' to 720'.

13 3/8" surface casing:

Depth: 0' to 720' (TD). 13 3/8" 48# H40 STC.

Lead w/ 350 sks Class C (35:65:4) w/ yield 2.12 cuft/sk @ 12.5 ppg. Tail w/ 200 sks Class C w/ yield 1.34 cuft/sk @ 14.8 ppg. TOC @ 0'. Volume calculated w/ 100% excess.

See attachment for additional information.

**NM OIL CONSERVATION**  
ARTESIA DISTRICT

DEC 07 2015

RECEIVED

UPD 12/17/15  
Accepted for record  
NMLC06

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #325145 verified by the BLM Well Information System  
For MEWBOURNE OIL COMPANY, sent to the Carlsbad  
Committed to AFMSS for processing by TEUNGKU KRUENG on 12/02/2015 (16TMK0007SE)

Name (Printed/Typed) ANDREW W TAYLOR Title ENGINEER

Signature (Electronic Submission) Date 12/02/2015

**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved By TEUNGKU MUCHLIS KRUENG Title PETROLEUM ENGINEER Date 12/02/2015

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Carlsbad

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Mewbourne Oil Company, Fuller 13/24 B2LM Fed Com #1H

Sec 13, T26S, R29E

SL: 2620' FSL & 330' FWL, Sec 13

BHL: 330' FSL & 330' FWL, Sec 24

2. Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0'	720'	13.375"	48	H40	STC	1.98	4.62	9.32
12.25"	0'	3010'	9.625"	36	J55	LTC	1.29	2.25	4.18
8.75"	0'	8420'	7"	26	P110	LTC	1.78	2.27	2.91
8.75"	8420'	9170'	7"	26	P110	BTC	1.69	2.15	42.56
6.125"	8420'	16350'	4.5"	13.5	P110	LTC	2.31	2.68	3.15
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 <sup>rd</sup> string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 <sup>nd</sup> string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Fuller 13/24 B2LM Fed Com #1H

Sec 13, T26S, R29E

SL: 2620' FSL & 330' FWL, Sec 13

BHL: 330' FSL & 330' FWL, Sec 24

**3. Cementing Program**

Casing	# Sks	Wt. lb/gal	Yld ft <sup>3</sup> /sack	H <sub>2</sub> O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	350	12.5	2.12	11	10	Lead: Class C (35:65:4) w/ Bentonite + CaCl <sub>2</sub> + LCM + Fluid Loss + Extender
	200	14.8	1.34	6.3	5	Tail: Class C + 2% CaCl <sub>2</sub>
Inter.	430	12.5	2.12	11	10	Lead: Class C (35:65:4) w/ Bentonite + CaCl <sub>2</sub> + LCM + Fluid Loss + Extender
	200	14.8	1.34	6.3	5	Tail: Class C + 0.2% CaCl <sub>2</sub>
Prod.	340	12.5	2.12	11	10	Lead: Class C (35:65:4) w/ Bentonite + CaCl <sub>2</sub> + LCM + Fluid Loss + Extender
	400	15.6	1.18	5.2	5	Tail: Class H w/ Fluid Loss + Retarder + Antifoam
Liner	320	11.2	2.97	18	16	Class C (60:40:0)+4% MPA5+1.2% BA10A+10#/sk BA90+5%A10+0.65%ASA301+1.5%SMS+1.2%R21

DV tool depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

Casing String	TOC	% Excess
Surface	0'	100%
Intermediate	0'	25%
Production	2810'	25%
Liner	8420'	25%