Submit I Copy To Appropriate Diffe OIL CONSERVATION Office	E
	Form C-103 Revised July 18, 2013
District 1 – (575) 393-6161 Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240 $\wedge$ DR $\cap$ 6 2016	WELL API NO.
District II – (575) 748-1283 811 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION	30-015-23097
District III ~ (505) 334-6178	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460 Santa Fe, NM 87505	STATE     FEE       6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	o. State off te ous hease No.
87505 SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	Bryan ME
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	8. Well Number
1. Type of Well: Oil Well 🔲 Gas Well 🗌 Other P&A	1
2. Name of Operator	9. OGRID Number
Yates Petroleum Corporation 3. Address of Operator	025575 10. Pool name or Wildcat
105 South Fourth Street, Artesia, NM 88210	Atoka-Yeso
4. Well Location	
Unit Letter <u>F</u> : <u>1650</u> feet from the <u>North</u> line and <u>2310</u> feet from the <u>West</u> line	
Section 33 Township 18S Range 26E	NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3381'GR	the state of the s
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
	•
	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK       PLUG AND ABANDON       REMEDIAL WORK       ALTERING CASING         TEMPORARILY ABANDON       CHANGE PLANS       COMMENCE DRILLING OPNS.       P AND A	
OTHER: OT	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of	
proposed completion or recompletion.	
· . · ·	
3/28/16 – NU BOP. Latched on to RBP and TOOH.	
3/29/16 – RIH with GR/JB to 2614'. Set a 4-1/2" CIBP at 2614'. Tagged CIBP. Loaded hole. Tested casing to 500 psi. Spotted 25 sx	
Class "C" cement on top. Calc TO C 2070'. Spotted 28 sx Class "C" cement at 1208'. WOC. Tagged at 830'. ND BOP.	
3/30/16 – Perforated 4 holes at 300'. Pumped 60 bbls brine down 4-1/2" casing. No circulation out 7" x 4-1/2" valve. Pumped 60 sx cement up to surface. No circulation. Dug out cellar with backhoe. 7" casing was rotted out all the way around. Cut off wellhead. 4-	
1/2" and 7" were standing full of cement. Installed dry hole marker. Filled cellar. <u>WELL IS PLUGGED AND ABANDONED.</u>	
Approved for plugging of well bore only.	
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Weil Plugging)	
which may be found at OCD Web Page under	
Forms, www.cmnrd.state.nm.us/ocd.	
	• . •
	······
Spud Date: Rig Release Date:	
	······································
I hereby certify that the information above is true and complete to the best of my knowledge	and helief
SIGNATURE ( Ana) furne TITLE Regulatory Reporting Supervisor DATE April 4, 2016	
Type or print name <u>Tina Huerta</u> E-mail address: <u>tinah@yatespetroleum.com</u> PHONE: <u>575-748-4168</u>	
For State Use Only	
APPROVED BY: Mabet 1 had TITLE COMPLIANCE OFFICER DATE 4/6/2016	
APPROVED BY: <b><i>flavel</i></b> <u><i>Flavel</i></u> TITLE <b><i>COMPLIANCE</i> <b>OFFICE</b> DATE <b>7/6/40/6</b> Conditions of Approval (if any):</b>	