

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: SHUGART 25 FED COM #2		Field: SHUGART; MORROW	
Location: 1250' FNL & 660' FWL; SEC 25-T18S-R31E		County: EDDY	State: NM
Elevation: 3693' KB; 3678' GL; 15' KB to GL		Spud Date: 7/6/01	Compl Date: 12/20/01
API#: 30-015-31758	Prepared by: Ronnie Slack	Date: 3/8/16	Rev:

CURRENT WELLBORE

17-1/2" hole

13-3/8", 48#, H40, STC, @ 791'

Cemented w/775 Sx. Cement to surface

12-1/4" hole

8-5/8", 32#, K55, LTC, @ 4289'

Cemented w/1750 Sx. Cement to surface

TOC @ 4,642'-CBL (10/13/15)

BONE SPRING-3RD

9,746' - 9,756' 3 spf (10/15/15)

DV Tool @ 9794'

2-7/8", 6.5#, L80 production tbgs. (2/3/16)

TAC @ 9,387' (2/3/16)

SN @ 9,713'

EOT @ 9,983'

Tagged TOC @ 11,134'. (10/12/15)

Spot 17 sx CI H @ 11,219'. (10/10/15)

Tagged TOC @ 11,219'. (10/10/15)

Spot 45 sx CI H @ 11,315'. (10/9/15)

Tagged TOC @ 11,315'. (10/9/15)

Spot 30 sx CI H @ 11,585'. (10/8/15)

Capped w/35" cmt. Tagged @ 11,585'. (10/7/15)

CIBP @ 11,620'. (10/6/15)

MORROW (9/11/01)

11670' - 11674'

11834' - 11838'

11874' - 11877'

11922' - 11926'

11948' - 11951'

11953' - 11957'

11960' - 11962'

11966' - 11974'

12038' - 12042'

11/01: Acidized w/19.5K gals 7.5% HCl, fraced w/43K gals + 50K # 20/40

7-7/8" Hole

5-1/2", 17# & 20#, L80, LT&C, @ 12,175'

Cemented w/1750 Sx. TOC @ 4642' CBL-10/13/15

12,090' PBTD

12,178' TD