NM OIL CONSERVATION

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico **Energy Minerals and Natural Resources**

Oil Conservation Division 1220 South St. Francis Dr.

ARTESIA DISTRICT Form C-141 JAN 0 2 2019 AB Revised August 8, 2011

Submit 1 Copy to appropriate District Office in accordance with 19.15.29 NMAC.

RECEIVED

Santa Fe, NM 87505 **Release Notification and Corrective Action**

1140		15434	7			OPERAT	COR		🛛 Initia	l Report		Final Report	
Name of Co				3440284		Contact	Karolina Blan	ey					
Address 5315 Buena Vista Dr.						Telephone No. 970 589 0743							
Facility Nan	ne: Pinnac	le 36-32H	Facility Type: Well Pad										
Surface Owner: State Mineral Owner: S						State		API No. 30- 015-41587					
				LOCA	TION	OF REI	FASE	•					
Unit Letter	Section	Township	Range	Feet from the		South Line	Feet from the	East/We	est Line	County			
С	36	228	28E	150	FNL		1700	FWL		Eddy			
Latitude: 32.355955527N Longitude: -104.043666686W													
NATURE OF RELEASE													
Type of Release. Oil							Volume of Release: 8 Bbls Volume				: 0 Bl	ols	
Source of Release							Date and Hour of Occurrence Date and				Hour of Discovery		
Flare Stack							12/21/2016 12/21/2016 – 10:00 hrs M7					1T	
Was Immediate Notice Given? ☐ Yes ☐ No ☒ Not Required							If YES, To Whom? NMOCD Heather Patterson, Crystal Weaver & Michael Bratcher, SLO Amber						
Groves													
By Whom? Karolina Blaney						Date and Hour: 12/21/16–15:00 hrs MT							
Was a Watercourse Reached? ☐ Yes ☒ No						If YES, Volume Impacting the Watercourse. N/A							
If a Watercourse was Impacted, Describe Fully.* N/A													
		•	•										
Describe Cause of Problem and Remedial Action Taken.*													
The spill was caused by equipment failure; dumps on the heater treater were not working properly which resulted in oil spraying out of the flare stack.													
Describe Area Affected and Cleanup Action Taken.*													
The spill mig	rated off lo	cation for app	roximatel	y 40-50 yards sout	hwest of	f the well pad	l. After receiving	SLO's ar	proval, th	e impacted	soil of	ff location	
				led for chlorides,									
Spills, and Re	eleases. Fur	ther remediat	ion will be	based on the anal	ytical re	sults.							
				is true and compl									
				nd/or file certain re									
public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability													
should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other													
federal, state,					opon ac	oes not renev	e the operator of i	сороною	ing for co	ompilance v	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	y outer	
						OIL CONSERVATION DIVISION							
Kamlina Blaney Signature:													
					Approved by Environifiental Specialistic Dranden								
Printed Name	: Karolina	Blaney									. 1		
Title: Enviro	nmental Sp	ecialist				Approval Dat	e: 114117	E	xpiration l	Date: N/	<u> </u>		
E-mail Addre	ss: Karolii	na.blanev@wi	oxenergy.c	om		Conditions of	Approv 4 l:						
Date: 1/2/2017 Phone: 970-589-0743						See attached Attached Attached							
Attach Additional Sheets If Necessary												100 100	
-			•									ary-401	

Operator/Responsible Party,

The OCD has received the form C-141 you provided on 1/z/17 regarding an unauthorized release. The information contained on that form has been entered into our incident database and remediation case number $\frac{1}{2}$ has been assigned. Please refer to this case number in all future correspondence.

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete <u>division-approved corrective action</u> for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District 2 office in for submitted to the occupance of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

- Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.
- Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.
- Nominal detection limits for field and laboratory analyses must be provided.
- Composite sampling is not generally allowed.
- Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

- •Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.
- If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method 8260 full list), total dissolved solids, pH, major anions and cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.
- Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold

OCD Environmental Bureau Chief 1220 South St. Francis Drive Santa Fe, New Mexico 87505 505-476-3465 jim.griswold@state.nm.us