



PRODIRECTIONAL



NM OIL CONSERVATION
ARTESIA DISTRICT

JUN 09 2017

RECEIVED

Warren Fed Com 25-23S-27E RB #203H

Eddy County, NM

30-015-43827

April 17, 2017

Job No. LNM5134217

ORIGINAL

Survey Completion Report



PRODIRECTIONAL

Survey Certification Letter

April 17, 2017



Operator Name: Matador Resources
Well Name: Warren Fed Com 25-23S-27E RB # 203H
County/Parish: Eddy County,
State: NM
Rig Name: Patterson 274
Job Number: LNM5134217

This is to certify the surveys performed on the referenced well by Professional Directional Ent., Inc. are true and correct MWD Surveys, data provided as follows:

Surveyor	Surveyed Depths	Projection to Bit	Dates Performed	Type of Survey
ProDirectional	171' MD – 14,049' MD	14,106' MD	03/01/17 – 03/25/17	MWD-OWSG

Sincerely,

Mike Coats
Well Planning
Professional Directional

850 Conroe Park West Drive | Conroe, TX 77303 | Phone: 936.441.7266

prodirectional.com



Matador Resources
Eddy County, NM
Warren Fed Com 25-23S-27E RB
203H
OH

Survey: ProDirectional

Survey Report

17 April, 2017





ProDirectional Survey Report



Company: Matador Resources
Project: Eddy County, NM
Site: Warren Fed Com 25-23S-27E RB
Well: 203H
Wellbore: OH
Design: MWD-171'-14049', Proj. 14106'

Local Co-ordinate Reference:
TVD Reference: Rig @ 3145.00usft (GL:3,116" + KB:29' (P274))
MD Reference: Rig @ 3145.00usft (GL:3,116" + KB:29' (P274))
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: WellPlanner1

Well 203H

Project	Eddy County, NM		System Datum:	Mean Sea Level
Map System:	US State Plane 1927 (Exact solution)			
Geo Datum:	NAD 1927 (NADCON CONUS)			
Map Zone:	New Mexico East 3001			

Site	Warren Fed Com 25-23S-27E RB			
Site Position:				
From:	Map	0.00 usft	Northings: 461,716.00 usft Eastings: 558,988.00 usft	Latitude: 32° 16' 9.228 N Longitude: 104° 8' 32.952 W
Position Uncertainty:			Slot Radius: 13-3/16 "	Grid Convergence: 0.10 °

Well	203H			
Well Position	+N/-S	0.00 usft	Northings: 461,776.00 usft Eastings: 559,028.00 usft	Latitude: 32° 16' 9.821 N Longitude: 104° 8' 32.485 W
Position Uncertainty	+E/-W	0.00 usft	Wellhead Elevation: usft	Ground Level: 3,116.00 usft

Wellbore	OH			
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)
	HDGM	2/7/2017	7.42	60.10
				Field Strength (nT) 48,142.40

Design	MWD-171'-14049', Proj. 14106'			
Audit Notes:				
Version:	1.0	Phase:	ACTUAL	
Vertical Section:		Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)
		0.00	0.00	0.00
			Direction (°)	0.13

Survey Program	From (usft)	To (usft)	Date	Survey (Wellbore)	Tool Name	Description
	171.00	14,106.00	3/27/2017	Survey #1 (OH)	MWD - OWSG	MWD - OWSG



ProDirectional Survey Report



Company: Matador Resources
Project: Eddy County, NM
Site: Warren Fed Com 25-23S-27E RB
Well: 203H
Wellbore: OH
Design: MWD-171'-14049', Proj. 14106'

Local Co-ordinate Reference: Well 203H
TVD Reference: Rig @ 3145.00usft (GL:3,116" + KB:29' (P274))
MD Reference: Rig @ 3145.00usft (GL:3,116" + KB:29' (P274))
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: WellPlanner1

Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	V. Sec (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)	Northing (usft)	Easting (usft)
Pro MWD First Survey: 171' MD										
232.00	0.70	152.70	231.99	-1.70	-1.70	-1.70	0.00	0.00	461,776.00	559,028.00
294.00	0.80	177.40	293.98	-2.47	-2.47	-2.47	0.64	1.19	461,774.99	559,028.64
359.00	0.20	139.50	358.98	-3.01	-3.01	-3.01	1.03	1.99	461,774.30	559,029.03
422.00	0.30	178.90	421.98	-3.26	-3.26	-3.26	1.23	2.76	461,773.53	559,029.23
495.00	0.30	184.50	494.98	-3.64	-3.64	-3.64	1.32	3.29	461,772.99	559,029.32
607.00	0.30	137.50	606.98	-4.15	-4.15	-4.15	1.40	3.55	461,772.74	559,029.40
700.00	0.30	134.10	699.98	-4.49	-4.50	-4.50	1.38	3.89	461,772.36	559,029.38
792.00	0.60	127.70	791.97	-4.95	-4.96	-4.96	1.56	4.43	461,771.85	559,029.56
881.00	2.50	167.90	880.94	-7.14	-7.14	-7.14	1.90	4.88	461,771.50	559,029.90
977.00	5.20	171.80	976.71	-13.49	-13.50	-13.50	2.45	5.53	461,771.04	559,030.45
1,072.00	5.80	171.10	1,071.28	-22.49	-22.50	-22.50	3.23	7.84	461,768.86	559,031.23
1,167.00	5.10	172.10	1,165.85	-31.41	-31.43	-31.43	4.29	14.16	461,762.50	559,032.29
1,358.00	4.30	171.30	1,356.20	-46.89	-46.91	-46.91	5.65	23.20	461,753.50	559,033.65
1,549.00	3.00	182.50	1,546.81	-58.96	-58.98	-58.98	6.97	32.19	461,744.57	559,034.97
1,739.00	3.20	156.20	1,736.54	-68.78	-68.80	-68.80	9.22	47.81	461,729.09	559,037.22
1,930.00	3.90	174.80	1,927.18	-80.12	-80.15	-80.15	10.08	59.84	461,717.02	559,038.08
2,121.00	4.40	175.40	2,117.68	-93.89	-93.92	-93.92	12.01	69.84	461,707.20	559,040.01
2,311.00	3.70	187.90	2,307.21	-107.23	-107.26	-107.26	14.75	81.50	461,695.85	559,042.75
2,451.00	3.30	188.40	2,446.95	-115.69	-115.72	-115.72	15.92	95.26	461,682.08	559,043.92
2,596.00	3.50	186.30	2,591.69	-124.22	-124.25	-124.25	15.66	108.40	461,668.74	559,043.66
2,787.00	3.40	187.00	2,782.35	-135.64	-135.67	-135.67	14.46	116.62	461,660.28	559,042.46
2,977.00	3.60	180.80	2,971.99	-147.20	-147.22	-147.22	13.36	124.97	461,651.75	559,041.36
3,168.00	3.40	181.10	3,162.64	-158.86	-158.88	-158.88	12.03	136.20	461,640.33	559,040.03
3,359.00	3.40	180.10	3,353.30	-170.18	-170.21	-170.21	11.26	147.65	461,628.78	559,039.26
							11.07	159.27	461,617.12	559,039.07
							10.95	170.56	461,605.79	559,038.95



ProDirectional

Survey Report



Company: Matador Resources
Project: Eddy County, NM
Site: Warren Fed Com 25-23S-27E RB
Well: 203H
Wellbore: OH
Design: MWD-171'-14049', Proj. 14106"

Local Co-ordinate Reference: Well 203H
TVD Reference: Rlg @ 3145.00usft (GL:3,116" + KB:29' (P274))
MD Reference: Rlg @ 3145.00usft (GL:3,116" + KB:29' (P274))
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: WellPlanner1

Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	V. Sec (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)	Northing (usft)	Easting (usft)
3,550.00	3.40	184.10	3,543.96	-181.50	-181.52	10.53	181.83	176.68	461,594.48	559,038.53
3,740.00	2.90	187.00	3,733.68	-191.89	-191.91	9.55	192.15	177.15	461,584.09	559,037.55
3,930.00	2.90	188.70	3,923.43	-201.41	-201.43	8.23	201.60	177.66	461,574.57	559,036.23
4,121.00	2.20	98.40	4,114.31	-206.72	-206.75	11.13	207.05	176.92	461,569.25	559,039.13
4,311.00	2.10	110.00	4,304.17	-208.43	-208.47	18.01	209.25	175.06	461,567.53	559,046.01
4,502.00	0.20	173.00	4,495.13	-209.95	-210.00	21.34	211.08	174.20	461,566.00	559,049.34
4,693.00	0.50	157.80	4,686.12	-211.05	-211.10	21.69	212.21	174.13	461,564.90	559,049.69
4,884.00	0.60	137.70	4,877.12	-212.56	-212.61	22.68	213.82	173.91	461,563.39	559,050.68
5,074.00	0.70	179.30	5,067.10	-214.45	-214.51	23.37	215.78	173.78	461,561.49	559,051.37
5,265.00	2.00	327.40	5,258.07	-212.82	-212.87	21.58	213.96	174.21	461,563.13	559,049.58
5,455.00	1.80	304.60	5,447.97	-208.34	-208.38	17.34	209.10	175.24	461,567.62	559,045.34
5,646.00	1.50	284.00	5,638.89	-206.04	-206.07	12.45	206.45	176.54	461,569.93	559,040.45
5,837.00	1.70	260.80	5,829.82	-205.90	-205.92	7.22	206.05	177.99	461,570.08	559,035.22
6,028.00	1.70	227.60	6,020.74	-208.28	-208.28	2.33	208.29	179.36	461,567.72	559,030.33
6,219.00	0.80	198.60	6,211.69	-211.46	-211.46	-0.18	211.46	180.05	461,564.54	559,027.82
6,409.00	1.20	94.70	6,401.68	-212.87	-212.88	1.38	212.88	179.63	461,563.12	559,029.38
6,599.00	1.90	115.10	6,591.61	-214.36	-214.38	6.21	214.47	178.34	461,561.62	559,034.21
6,790.00	0.80	116.70	6,782.55	-216.29	-216.32	10.27	216.56	177.28	461,559.68	559,038.27
6,980.00	0.80	126.20	6,972.53	-217.67	-217.70	12.53	218.06	176.71	461,558.30	559,040.53
7,170.00	1.40	235.40	7,162.51	-219.77	-219.80	11.69	220.11	176.96	461,556.20	559,039.69
7,360.00	3.30	221.20	7,352.34	-225.22	-225.23	6.17	225.32	178.43	461,550.77	559,034.17
7,551.00	1.10	70.40	7,543.26	-228.74	-228.75	4.28	228.79	178.93	461,547.25	559,032.28
7,741.00	1.20	64.20	7,733.22	-227.26	-227.28	7.79	227.41	178.04	461,548.72	559,035.79
7,932.00	0.80	4.60	7,924.19	-225.05	-225.08	9.70	225.29	177.53	461,550.92	559,037.70
8,123.00	1.00	333.80	8,115.17	-222.23	-222.25	9.07	222.44	177.66	461,553.75	559,037.07
8,313.00	1.00	301.90	8,305.14	-219.87	-219.89	6.93	220.00	178.20	461,556.11	559,034.93
8,503.00	1.00	147.80	8,495.13	-220.40	-220.42	6.40	220.51	178.34	461,555.58	559,034.40



ProDirectional Survey Report



Company: Matador Resources
Project: Eddy County, NM
Site: Warren Fed Com 25-23S-27E RB
Well: 203H
Wellbore: OH
Design: MWD-171-14049', Proj. 14106'

Local Co-ordinate Reference:
TVD Reference:
MD Reference:
North Reference:
Survey Calculation Method:
Database:

Well 203H
Rig @ 3145.00usft (GL:3,116" + KB:29' (P274))
Rig @ 3145.00usft (GL:3,116" + KB:29' (P274))
Grid
Minimum Curvature
WellPlanner1

Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	V. Sec (usft)	N/S (usft)	E/W (usft)	Closure Distance (usft)	Closure Azimuth (°)	Northing (usft)	Easting (usft)	
8,599.00	1.20	117.60	8,591.12	-221.57	-221.59	7.74	221.73	178.00	461,554.41	559,035.74	
8,699.00	0.80	131.20	8,691.10	-222.51	-222.54	9.19	222.73	177.63	461,553.46	559,037.19	
8,795.00	10.60	347.10	8,786.59	-214.33	-214.34	7.72	214.48	177.94	461,561.66	559,035.72	
8,843.00	17.00	359.70	8,833.19	-202.99	-203.01	6.70	203.12	178.11	461,572.99	559,034.70	
8,890.00	20.00	359.70	8,877.75	-188.08	-188.10	6.62	188.21	177.98	461,587.90	559,034.62	
8,938.00	23.10	356.30	8,922.39	-170.47	-170.49	5.97	170.59	177.99	461,605.51	559,033.97	
8,985.00	26.20	358.10	8,965.11	-150.90	-150.91	5.03	151.00	178.09	461,625.09	559,033.03	
9,033.00	29.60	0.70	9,007.52	-128.45	-128.46	4.82	128.55	177.85	461,647.54	559,032.82	
9,081.00	35.50	0.00	9,047.96	-102.64	-102.65	4.97	102.77	177.23	461,673.35	559,032.97	
9,129.00	39.10	357.50	9,086.14	-73.57	-73.58	4.31	73.70	176.65	461,702.42	559,032.31	
9,176.00	44.00	357.50	9,121.31	-42.44	-42.44	2.95	42.55	176.03	461,733.56	559,030.95	
9,224.00	49.20	358.40	9,154.28	-7.60	-7.60	1.71	7.79	167.30	461,768.40	559,029.71	
9,271.00	50.60	358.80	9,184.55	28.34	28.34	0.84	28.35	1.69	461,804.34	559,028.84	
9,319.00	52.00	0.20	9,214.56	65.80	65.79	0.51	65.80	0.45	461,841.79	559,028.51	
9,366.00	55.00	1.20	9,242.51	103.57	103.57	0.98	103.57	0.54	461,879.57	559,028.98	
9,414.00	58.90	3.90	9,268.69	143.75	143.75	2.79	143.77	1.11	461,919.75	559,030.79	
9,461.00	62.30	5.10	9,291.76	184.57	184.56	6.01	184.66	1.87	461,960.56	559,034.01	
9,508.00	69.00	4.40	9,311.54	228.14	228.11	9.62	228.32	2.42	462,004.11	559,037.62	
9,527.00	71.66	3.98	9,317.60	245.04	245.02	10.86	245.26	2.54	462,021.02	559,038.86	
HL Xing: 9527 MD											
9,557.00	76.10	3.30	9,325.92	273.80	273.77	12.69	274.07	2.65	462,049.77	559,040.69	
9,658.00	81.40	2.90	9,345.62	372.69	372.65	18.04	373.09	2.77	462,148.65	559,046.04	
9,752.00	83.70	3.50	9,357.81	465.76	465.71	23.24	466.29	2.86	462,241.71	559,051.24	
9,846.00	90.90	359.90	9,362.24	559.54	559.48	26.02	560.09	2.66	462,335.48	559,054.02	
9,941.00	91.20	359.60	9,360.49	654.52	654.47	25.60	654.97	2.24	462,430.47	559,053.60	
10,035.00	91.10	359.50	9,358.61	748.50	748.44	24.86	748.86	1.90	462,524.44	559,052.86	
10,129.00	91.70	359.90	9,356.31	842.47	842.41	24.37	842.77	1.66	462,618.41	559,052.37	



ProDirectional Survey Report



Company: Matador Resources
Project: Eddy County, NM
Site: Warren Fed Com 25-23S-27E RB
Well: 203H
Wellbore: OH
Design: MWD-171'-14049', Proj. 14106'

Local Co-ordinate Reference: Well 203H
TVD Reference: Rig @ 3145.00usft (GL:3.116" + KB:29' (P274))
MD Reference: Rig @ 3145.00usft (GL:3.116" + KB:29' (P274))
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: WellPlanner1

Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	V. Sec (usft)	N/S (usft)	EW (usft)	Closure Distance (usft)	Closure Azimuth (°)	Northing (usft)	Easting (usft)
10,223.00	90.40	359.00	9,354.59	936.44	936.39	23.47	936.69	1.44	462,712.39	559,051.47
10,318.00	89.30	359.10	9,354.84	1,031.42	1,031.38	21.90	1,031.61	1.22	462,807.38	559,049.90
10,412.00	88.20	358.90	9,356.89	1,125.38	1,125.34	20.25	1,125.52	1.03	462,901.34	559,048.25
10,507.00	91.20	359.40	9,357.39	1,220.36	1,220.32	18.85	1,220.46	0.88	462,996.32	559,046.85
10,601.00	91.20	359.30	9,355.42	1,314.33	1,314.29	17.78	1,314.41	0.78	463,090.29	559,045.78
10,696.00	92.10	0.30	9,352.68	1,409.28	1,409.25	17.45	1,409.35	0.71	463,185.25	559,045.45
10,790.00	91.80	2.00	9,349.48	1,503.21	1,503.17	19.33	1,503.29	0.74	463,279.17	559,047.33
10,884.00	89.10	1.60	9,348.74	1,597.16	1,597.11	22.29	1,597.27	0.80	463,373.11	559,050.29
10,979.00	89.80	4.90	9,349.66	1,692.00	1,691.94	27.67	1,692.17	0.94	463,467.94	559,055.67
11,073.00	89.10	5.10	9,350.56	1,785.66	1,785.58	35.86	1,785.94	1.15	463,561.58	559,063.86
11,168.00	90.30	5.60	9,351.06	1,880.26	1,880.16	44.72	1,880.69	1.36	463,656.16	559,072.72
11,263.00	89.70	4.90	9,351.06	1,974.88	1,974.76	53.41	1,975.48	1.55	463,750.76	559,081.41
11,357.00	89.60	3.90	9,351.63	2,068.61	2,068.48	60.62	2,069.37	1.68	463,844.48	559,088.62
11,451.00	89.40	1.60	9,352.45	2,162.51	2,162.36	65.13	2,163.34	1.73	463,938.36	559,093.13
11,546.00	89.90	0.60	9,353.03	2,257.49	2,257.34	66.96	2,258.34	1.70	464,033.34	559,094.96
11,641.00	89.60	359.00	9,353.45	2,352.48	2,352.34	66.63	2,353.28	1.62	464,128.34	559,094.63
11,735.00	89.50	359.30	9,354.18	2,446.47	2,446.32	65.23	2,447.19	1.53	464,222.32	559,093.23
11,829.00	89.60	359.00	9,354.92	2,540.45	2,540.31	63.84	2,541.11	1.44	464,316.31	559,091.84
11,924.00	89.00	357.80	9,356.08	2,635.40	2,635.27	61.18	2,635.98	1.33	464,411.27	559,089.18
12,018.00	89.30	358.20	9,357.48	2,729.32	2,729.20	57.90	2,729.81	1.22	464,505.20	559,085.90
12,113.00	89.40	357.50	9,358.56	2,824.24	2,824.12	54.34	2,824.65	1.10	464,600.12	559,082.34
12,207.00	91.90	358.40	9,357.49	2,918.16	2,918.05	50.98	2,918.49	1.00	464,694.05	559,078.98
12,302.00	89.20	358.20	9,356.58	3,013.10	3,012.99	48.16	3,013.38	0.92	464,788.99	559,076.16
12,397.00	92.40	359.80	9,355.25	3,108.05	3,107.95	46.50	3,108.30	0.86	464,883.95	559,074.50
12,491.00	89.70	359.10	9,353.53	3,202.02	3,201.93	45.60	3,202.25	0.82	464,977.93	559,073.60
12,586.00	88.70	358.40	9,354.86	3,296.98	3,296.89	43.53	3,297.18	0.76	465,072.89	559,071.53
12,680.00	88.50	358.40	9,357.15	3,390.91	3,390.83	40.90	3,391.07	0.69	465,166.83	559,068.90



ProDirectional Survey Report



Company: Matador Resources
Project: Eddy County, NM
Site: Warren Fed Com 25-23S-27E RB
Well: 203H
Wellbore: OH
Design: MWD-171'-14049', Proj. 14106'

Local Co-ordinate Reference: Well 203H
TVD Reference: Rig @ 3145.00usft (GL:3.116" + KB:29' (P274))
MD Reference: Rig @ 3145.00usft (GL:3.116" + KB:29' (P274))
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: WellPlanner1

Survey									
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	V. Sec (usft)	N/S (usft)	EW (usft)	Closure Distance (usft)	Closure Azimuth (°)	Easting (usft)
12,775.00	92.10	359.70	9,356.65	3,485.88	3,485.79	39.33	3,486.02	0.65	465,261.79
12,869.00	90.60	358.10	9,354.44	3,579.82	3,579.75	37.53	3,579.94	0.60	465,355.75
12,964.00	88.50	358.40	9,355.19	3,674.76	3,674.69	34.62	3,674.86	0.54	465,450.69
13,058.00	89.00	358.30	9,357.24	3,768.69	3,768.63	31.92	3,768.77	0.49	465,544.63
13,152.00	88.80	357.90	9,359.04	3,862.62	3,862.56	28.80	3,862.67	0.43	465,638.56
13,246.00	89.10	357.80	9,360.76	3,956.53	3,956.48	25.28	3,956.56	0.37	465,732.48
13,341.00	90.10	358.40	9,361.43	4,051.46	4,051.42	22.13	4,051.48	0.31	465,827.42
13,435.00	91.40	359.30	9,360.20	4,145.43	4,145.39	20.24	4,145.44	0.28	465,921.39
13,530.00	90.50	359.80	9,358.62	4,240.41	4,240.38	19.49	4,240.42	0.26	466,016.38
13,624.00	87.60	359.90	9,360.18	4,334.39	4,334.35	19.25	4,334.40	0.25	466,110.35
13,718.00	87.50	0.30	9,364.20	4,428.30	4,428.27	19.41	4,428.31	0.25	466,204.27
13,813.00	87.90	0.50	9,368.01	4,523.22	4,523.19	20.07	4,523.23	0.25	466,299.19
13,907.00	88.30	1.10	9,371.13	4,617.16	4,617.13	21.39	4,617.18	0.27	466,393.13
14,001.00	87.40	0.70	9,374.65	4,711.09	4,711.05	22.86	4,711.10	0.28	466,487.05
14,016.00	87.43	0.70	9,375.33	4,726.07	4,726.03	23.05	4,726.09	0.28	466,502.03
HL XING: 14016' MD									
14,049.00	87.50	0.70	9,376.79	4,759.04	4,759.00	23.45	4,759.05	0.28	466,535.00
Last Survey: 14049' MD, 9376.79' TVD									
14,106.00	87.50	0.70	9,379.28	4,815.98	4,815.94	24.14	4,816.00	0.29	466,591.94
PTB: 14106' MD, 9379.28' TVD									



ProDirectional Survey Report



Company: Matador Resources
Project: Eddy County, NM
Site: Warren Fed Corn 25-23S-27E RB
Well: 203H
Wellbore: OH
Design: MWD-171'-14049', Proj. 14106'

Local Co-ordinate Reference:
TVD Reference:
MD Reference:
North Reference:
Survey Calculation Method:
Database:

Well 203H
Rig @ 3145.00usft (GL:3,116" + KB:29' (P274))
Rig @ 3145.00usft (GL:3,116" + KB:29' (P274))
Grid
Minimum Curvature
WellPlanner1

Design Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
171.00	170.99	-1.01	0.64	Pro MWD First Survey: 171' MD
9,527.00	9,317.60	245.02	10.86	HL Xing: 9527' MD
14,016.00	9,375.33	4,726.03	23.05	HL XING: 14016' MD
14,049.00	9,376.79	4,759.00	23.45	Last Survey: 14049' MD, 9376.79' TVD
14,106.00	9,379.28	4,815.94	24.14	PTB: 14106' MD, 9379.28' TVD