Submit 3 Copies To Appropriate District Office District I	State of New Mexico Energy, Minerals and Natural Resources			Form C-103 Revised March 25, 1999 WELL API NO.	
1625 N. French Dr., Hobbs, NM 88240 District II				30-015-34589	
811 South First, Artesia, NM 88210	OIL CONSERVATION DIVISION			5. Indicate Type of	of Lease
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.			T	FEE
District IV	Santa Fe, NM 8/303			6. State Oil & G	
1220 S. St. Francis Dr., Santa Fe, NM 87505	87505 St. Francis Dr., Santa Fe, NM				
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)				7. Lease Name or Unit Agreement Name: Wisetail State Com	
1. Type of Well:					
Oil Well Gas Well X	Other	R	ECEIVED		
2. Name of Operator			EOCIVET.	8. Well No.	
Yates Drilling Company			PR 0 7 2006	1	
3. Address of Operator		UU	n-wu i Eale	9. Pool name or	
105 South 4th St., Artesia,	NM 88210		الروه هويتين	Wildcat Cheste	er
4. Well Location					
Unit Letter A: 660' feet from the North line and 990' feet from the East line					
Section 24	Township 18S	Range		IMPM Eddy	County
	10. Elevation (Show w			:.)	
3595' GL					
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
NOTICE OF IN	TENTION TO:	 	SUB	SEQUENT REI	1
PERFORM REMEDIAL WORK	PLUG AND ABANDON		REMEDIAL WOR		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS			LLING OPNS. X	ABANDONMENT
PULL OR ALTER CASING	MULTIPLE COMPLETION		CASING TEST AN CEMENT JOB	ND X	
OTHER:			OTHER: Spud		X
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.					
Spud 17 ½" hole, 4/1/2006, 7:00 AM TD 430'. Ran 9 jts. 13 3/8" 48# H40 ST&C, set at 393.54'. Texas Pattern Guide shoe set at 393.54' and Insert Float set at 360.42'. Cemented with 200 sxs BJ Lite, 65:35:6 + 2% CaCl2 + ½# celloflake (yld 1.98, wt 12.6#). Tailed in with 200 sxs Class "C" + 2% CaCl2 (yld 1.34, wt 14.8#). Circulated 110 sxs to pit. Centralizers on joint 1,3,5,7. Plugged down at 12:00 AM, 4/2/2006. Did not bump plug, floats held OK. Reduced hole to 12 ½" and resumed drilling at 2:00 PM, 4/4/2006. (NMOCD notified spud, running csg and cement, NMOCD did not witness)					
4					
I hereby certify that the information above is true and complete to the best of my knowledge and belief.					
SIGNATURE Kare	Lushun: TITLE_	Opera	tions Tech	DATE <u>4/5/200</u>	<u>06</u>
Type or print name Karen J. Leishman Telephone No. 505-748-8463					
(This space for State use)			•		ADD 4 0 0000
FOR	RECORDS ONLY				APR 1 0 2006
APPPROVED BY Conditions of approval, if any:		TITLE_			_DATE