District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico State of New Mexico RTFSIA DISTRICT Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

RECEIVED

| GAS CAPTURE PLAN | | | | | | | |
|--|---|--|---|---|--|--|---|
| Date:03-08-18 ✓ Original Operator & OGRID No.: Mewbourne Oil Company - 14744 ☐ Amended - Reason for Amendment: | | | | | | | |
| | is Gas Capture Plan out w completion (new drill, | | | | reduce we | ll/production | facility flaring/venting for |
| | te: Form C-129 must be sub ell(s)/Production Facili | | - | ding 60 days a | llowed by Rul | e (Subsection A | of 19.15.18.12 NMAC). |
| | e well(s) that will be loc | | | are shown in | the table bel | ow. | |
| | Well Name | API | Well Location (ULSTR) | Footages | Expected MCF/D | Flared or Vented | Comments |
| | Yardbirds 2 W2DM Fee #2H | 30-015 44803 | D 2-24S-28E | 205' FNL 660' FWL | 0 | NA | Online after frac |
| | YARDBIRDS 2 W0DM FEE #1H | 30-015 | D 2-24S-28E | 205' FNL & 610' FWL | 0 | NA. | ONLINE AFTER FRAC |
| pla C: 30 (pe be cor Th | nce. The gas produced restwood low/h oo 'of pipeline to ceriodically) to Crestwo drilled in the foreseeab | fo a production from production from production pressure connect the factor of the fac | n facility after fl- tion facility is de gathering systen cility to low/high drilling, completio addition, Mewbo drilling and com- plant located in Se | edicated to _n located in pressure gas on and estimate ourne Oil Completion scheme29 _, Two | Crestweet description of the control | County, New em. Mewboruction date for from these | Mexico. It will require urne Oil Company provides or wells that are scheduled to have periodic wells will be processed at County, New Mexico. |
| | | t/completion | operations, well(s |) will be prod | duced to tem | nporary produ | action tanks and gas will be |

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on __Crestwood___ system at that time. Based on current information, it

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

is Operator's belief the system can take this gas upon completion of the well(s).

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines