Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

	NM OIL CONSERVATION ARTESIA DISTRICT	GAS CAPTURE PLAN				
X Original	MAR 20 2018	Operator & OGRID No.: Devon Energy Production Co., LP (6137)				
□ Amended		Date:05/22/2017				
Reason for Au	mendment RECEIVED					

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

## Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Agate PWU 21-22 62H	30-015-44116 44201	Sec.21,T19S, R29E	85 FNL 235 FEL			Agate PWU 21 CTB 1
Agate PWU 21 11H	30-015-4 <del>4120</del> 444 <b>200</b>	Sec.21,T19S, R29E	85 FNL 235 FEL			Agate PWU 21 CTB 1

## **Gathering System and Pipeline Notification**

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to <u>DCP</u> and will be connected to <u>DCP</u> low/high pressure gathering system located in <u>Eddy</u> County, New Mexico. It will require 7317' of pipeline to connect the facility to low/high pressure gathering system. <u>Devon Energy Production Co., LP</u> provides (periodically) to <u>DCP</u> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <u>Devon Energy Production Co., LP</u> and <u>DCP</u> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <u>DCP</u> Processing Plant located in <u>Sec. 19, TWN 19S, RNG 32E, Eddy</u> County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

## Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on **DCP** system at that time. Based on current information, it is **Devon Energy Production Co., LP** belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

## **Alternatives to Reduce Flaring**

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

Power Generation - On lease

• Only a portion of gas is consumed operating the generator, remainder of gas will be flared

Compressed Natural Gas – On lease

• Gas flared would be minimal, but might be uneconomical to operate when gas volume declines NGL Removal – On lease

o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines