## MM OIL CONSERVATION

ARTESIA DISTRICT

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources MAR 3 1 2018

Form C-141 Revised April 3, 2017

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Submit I Copy to appropriate District Office in accordance with 19.15.29 NMAC.

Release Notification and Corrective Action													
MABI	8093	OPERA'	RATOR 🛛 Ini			al Report		Final Report					
							Contact Hubert Perry						
···							Telephone No. 575-748-3371 Facility Type Oil						
Surface Owner State Mineral Owner S							State API No. 30-015-38476						
				·		OF RE	1	1		T			
Unit Letter A	Section 32	Township 19S	Range 29E	Feet from the	North/	South Line	Feet from the	East/\	West Line	County Eddy			
Latitude_32.623526													
NATURE OF RELEASE													
Type of Release Oil & Produced Water							Volume of Release 17 bbls of Oil & 73 bbls of Produced Water Volume Recovered 15 bbls of produced water						
Source of Release Heater Treater											nd Hour of Discovery 17, 2018 10:30 AM MST		
Was Immediate Notice Given?							If YES, To Whom?						
☐ Yes ☐ No ☐ Not Required						SLO-Tammy Honea							
By Whom? Brett Fulks- EHS Professional						Date and Hour March 18, 2018 10:20 AM  If YES, Volume Impacting the Watercourse.							
Was a Watercourse Reached?  ☐ Yes ☑ No						N/A							
If a Watercourse was Impacted, Describe Fully.*													
N/A													
Describe Cause of Problem and Remedial Action Taken.*													
The fire tube gasket on the heater treater failed causing a release of oil and produced water. The heater treater was immediately shut off to prevent farther release.													
	Describe Area Affected and Cleanup Action Taken.*  Approximately 17 bbls of oil and 73 bbls of produced water was released from the heater treater. A vacuum truck was dispatched and recovered												
approximately 15 bbls of oil. An Environmental contractor will be contacted to assist with delineation and remediation efforts.													
I hereby cert	ify that the	information gi	ven above	e is true and comp	lete to the	he best of my	knowledge and u	ındersta	and that pur	suant to NM	OCD	rules and	
				nd/or file certain i									
public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health													
or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.													
reactur, state	, or rocal ra	unaror rog.					OIL CON	SERV	VATION	DIVISIO	ON		
Signature: Michael Shoemaker													
						Approved by Environmental Specialist & Security							
Printed Nam	e: Michael	Shoemaker					41				11		
Title: Envir	onmental Pr	rofessional				Approval Da	te: 4-2/1	8	Expiration	Date:	IIH		
E-mail Address: mike.shoemaker@dvn.com						Conditions of Approval:							
Date: 03/31/18 Phone: 575.748.3371						See attached 2RP-4688							

<sup>\*</sup> Attach Additional Sheets If Necessary

Operator/Responsible Party,

The OCD has received the form C-141 you provided on 3/31/2018 regarding an unauthorized release. The information contained on that form has been entered into our incident database and remediation case number has been assigned. Please refer to this case number in all future correspondence.

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete <u>division-approved corrective action</u> for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District 2 office in ARTESIA on or before 4/30/2018. If and when the release characterization workplan is approved, there will be an associated deadline for submittal of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

- Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C<sub>6</sub> thru C<sub>36</sub>), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.
- Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C<sub>6</sub> thru C<sub>36</sub>), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.
- Nominal detection limits for field and laboratory analyses must be provided.
- Composite sampling is not generally allowed.
- Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

- •Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.
- If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method 8260 full list), total dissolved solids, pH, major anions and cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.
- Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold

OCD Environmental Bureau Chief
1220 South St. Francis Drive
Santa Fe, New Mexico 87505
505-476-3465
jim.griswold@state.nm.us