District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NM OIL CONSERVATION ARTESIA DISTRICT

CAS	CA	PTURE	DI.AN

MAY 08 2018

Date	5/08/2018						RECEIVED	
X C	Original		Operator	& OGRID N	lo.: Percus	sion Petroleur	n Operating, LLC (371755)_
	Amended - Reason for	Amendment:_						_
new Note	completion (new drill: Form C-129 must be suit	, recomplete to bmitted and appr Gas	o new zone, re-fra roved prior to excee a Transporter Process	c) activity.			facility flaring/venting of 19.15.18.12 NMAC).	fo
Wel	ll(s)/Production Facili	ty – Name of	<u>facility</u>					
The	well(s) that will be lo	cated at the pro	duction facility a	re shown in	the table bel	ow		
	Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments	
	Red Lake 32 St #2H	3001544948	P-32-17S-27E	292S x 155E	100	F	New FL length shown	
					Ì]	1	

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Frontier Field Serv. and will be connected to Frontier Field Serv. low/high pressure gathering system located in <u>Eddy</u> County, New Mexico. It will require <u>1273</u> of pipeline to connect the facility to low/high pressure gathering system. Perussion provides (periodically) to <u>Gas Transporter</u> a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, <u>Operator</u> and <u>Gas Transporter</u> have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <u>Gas Transporter</u> Processing Plant located in Sec. <u>9</u>, Twn. <u>17S</u>, Rng. <u>26E</u>, <u>Eddy</u> County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Gas Transporter</u> system at that time. Based on current information, it is <u>Operator's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines