<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NM OIL CONSERVATION ARTESIA DISTRICT

MAY 10 2018

GAS CAPTURE PLAN 5-7-18 Date: RECEIVED Operator & OGRID No.: Mewbourne Oil Company - 14744 □ Original ☐ Amended - Reason for Amendment:_ This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity. Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC). Well(s)/Production Facility - Name of facility The well(s) that will be located at the production facility are shown in the table below. Comments Flared or Expected Well Location Footages Well Name Vented MCF/D (ULSTR) ONLINE AFTER FRAC D 11-19S-28E 300 FNI & 205 FWI Bourbon Red 11 B2DA State Com #1H 30-015-44952 Gathering System and Pipeline Notification Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in and will be connected to low/high pressure gathering system located in LEA County, New Mexico. It will require of pipeline to connect the facility to low/high pressure gathering system. Mewbourne Oil Company provides a drilling, completion and estimated first production date for wells that are scheduled to (periodically) to Targa have periodic be drilled in the foreseeable future. In addition, Mewbourne Oil Company and Tarqa conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Processing Plant located in Sec. 28, Twn. 21s, Rng. 37E, Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures. Flowback Strategy After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on _____ system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - O Gas flared would be minimal, but might be uneconomical to operate when gas volume declines

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that

- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines