
BU SUNDRY I Do not use this abandoned web	EPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT NOTICES AND REPORTS ON WELLS his form for proposals to drill or to re-enter an ell. Use form 3160-3 (APD) for such proposal			sia 2018 RTESIA O	OMB NO. Expires: Jan 5. Lease Serial No. NMLC029342E 6. If Indian, Allottee or	FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018 5. Lease Serial No. NMLC029342E 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No.	
SUBMIT IN 1	RIPLICATE - Other inst	ructions on pa	age 2				
1. Type of Well					8. Well Name and No. THUNDER ROAD FED 8		
Contact: ABIGAIL MONTGOMERY COG OPERATING LLC Contact: ABIGAIL MONTGOMERY E-Mail: Abbym@bcmandassociates.com					9. API Well No. 30-015-36280-00-S1		
3a. Address 3b. Phone No. (include area code) 600 W ILLINOIS AVENUE Ph: 432-580-7161					10. Field and Pool or Exploratory Area LOCO HILLS-PADDOCK		
MIDLAND, TX 79701 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)					11. County or Parish, State		
Sec 20 T17S R30E SENW 1675FNL 2310FEL					EDDY COUNTY, NM		
12. CHECK THE A	PPROPRIATE BOX(ES)	TO INDICAT	E NATURE O	F NOTICE	, REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION						
	Acidize				ction (Start/Resume)	Water Shut-Off	
Notice of Intent	Alter Casing				nation	 Well Integrity Other 	
Subsequent Report			Construction Record Record Abandon Temp		prarily Abandon		
Final Abandonment Notice	Convert to Injection Plug			U Water Disposal			
13. Describe Proposed or Completed Op If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involve testing has been completed. Final A determined that the site is ready for	ork will be performed or provid d operations. If the operation r bandonment Notices must be find	e the Bond No. on esults in a multiple iled only after all r	file with BLM/BL completion or rec equirements, inclu	A. Required s ompletion in ding reclamat	subsequent reports must be a new interval, a Form 316 ion, have been completed	filed within 30 days 0-4 must be filed once and the operator has	
determined that the site is ready for 1. Set 5 1/2" CIBP @ 4235'. 2. Spot 25 sx cmt @ 2850-26 3. Spot 30 sx cmt @ 1200-93 4. Spot 30 sx cmt @ 576-300 5. Spot 15 sx cmt @ 60'-Surf 6. Cut off well head, verify cr							
Accepted for record	N PROCEDURE Ched	PROCEDURE CONDITIONS OF APPROVAL					
Below around	level dig	hole	Mark	er r	equired		
14. I hereby certify that the foregoing Control Name (Printed/Typed) ABIGAIL	Electronic Submission For COG ommitted to AFMSS for pro			on 04/11/20			
Name (1 runeur 1ypeu) Abron a							
Signature (Electroni	c Submission)		Date 04/09		USE		
	THIS SPACE I	FOR FEDER/	AL OR STATE		USE	11.71.18	
Approved By Jamas D. Comos			Title Ser	st. F	ET	9-21-18 Date	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Carlsbad				
Title ISUSC. Section 1001 and Title States any false, fictitious or fraudule	42 U.S.C. Section 1212 make i	it a crime for any p s as to any matter v	erson knowingly a vithin its jurisdictio	nd willfully t on.	o make to any department	or agency of the United	
(Instructions on page 2) ** BLM RE	EVISED ** BLM REVIS	ED ** BLM R	EVISED ** BI	LM REVIS	ED ** BLM REVIS	ED **	

Thunder Road Federal #8



TD 5900'

PBTD 5865'

circ.

82 sx

32.8227501 -103.9931183

Field

GL: KB:

Loco Hills

1

Thunder Road Federal #8 Loco Hills Field Well ID Info: 5. Spot 15 sx cmt @ 60'-Surface Location: API No: 30-015-36280 Spud Date: 7/26/2008 Footage: 1675 FNL & 2310 FE Section: 20 Township 17S 8-5/8" 24# J55 STC Csg: 30E Range 352' Set @ County: Eddy Cement w/ 325 sx Elevations: circ. 111 sxx GL 3655 KB: Pumping Unit: Unit Size: Unknown Speed: Unknown 4. Spot 30 sx cmt @ 576-300' WOC & Tag (T/Salt & 8 5/8" Shoe) L T/Salt 526 B/Salt 9567985 72/ 3. Spot 30 sx cmt @ 1200-935' (Yates & B/Salt 1462 7R 2064 Qu DY7 @ 3550 2. Spot 25 sx cmt @ 2850-2650' (San Andres) 2799 SA 4207 Col 1. Set 5 1/2" CIBP @ 4235'. Circ hole w/ MLF. Pressure test csg. Spot 25 sx cmt @ 4235-4035' 4281 Paddock 4283' - 4684' Yesd 2000 gal 15% HCI Blinebry: 5075' - 5460' L 2000 gal 15% HCI 5-1/2" 15.5# J55 LTC Csg: 5893 Depth: ~ Cement w/ 1650 sx TD 5900' circ. 82 sx PBTD 5865

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Below Ground Level Cap (Lesser Prairie-Chicken Habitat)</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¹/₄ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.

8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

<u>Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:</u> From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Appropriate time for submittal would be when filing the Appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos

Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Henryetta Price Environmental Protection Specialist 575-234-5951

Shelly Tucker Environmental Protection Specialist 575-234-5979

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612