

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department

Submit Original
to Appropriate
District Office

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

**NM OIL CONSERVATION
ARTESIA DISTRICT**

AUG 17 2018

GAS CAPTURE PLAN

Date: 9/28/17

RECEIVED

☒ Original

Operator & OGRID No.: BOPCO, LP [260737]

☐ Amended - Reason for Amendment: _____

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility: Brushy Draw 30 & 31 Federal CTB

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Brushy Draw 30 Fed 102H		M-30-25S-30E	330' FSL & 1175' FWL	2530	Flared/Sold	
Brushy Draw 30 Fed 122H 30-015 45190		M-30-25S-30E	330' FSL & 1205' FWL	3960	Flared/Sold	
Brushy Draw 30 Fed 703H		M-30-25S-30E	330' FSL & 1145' FWL	2530	Flared/Sold	
Brushy Draw 30 Fed 701H		M-30-25S-30E	330' FSL & 340' FWL	2530	Flared/Sold	
Brushy Draw 30 Fed 121H		M-30-25S-30E	330' FSL & 400' FWL	3960	Flared/Sold	
Brushy Draw 30 Fed 901H		M-30-25S-30E	330' FSL & 370' FWL	2300	Flared/Sold	
Brushy Draw 30 Fed 104H		N-30-25S-30E	330' FSL & 2010' FWL	2530	Flared/Sold	
Brushy Draw 30 Fed 123H		N-30-25S-30E	330' FSL & 1980' FWL	3960	Flared/Sold	
Brushy Draw 30 Fed 903H		N-30-25S-30E	330' FSL & 1950' FWL	2300	Flared/Sold	
Brushy Draw 30 Fed 106H		O-30-25S-30E	330' FSL & 1615' FWL	2530	Flared/Sold	
Brushy Draw 30 Fed 125H		O-30-25S-30E	330' FSL & 1585' FWL	3960	Flared/Sold	
Brushy Draw 30 Fed 126H		O-30-25S-30E	330' FSL & 1555' FWL	3960	Flared/Sold	
Brushy Draw 31 Fed 124H		B-31-25S-30E	223' FNL & 2344' FEL	3960	Flared/Sold	
Brushy Draw 31 Fed 905H		B-31-25S-30E	223' FNL & 2284' FEL	2300	Flared/Sold	
Brushy Draw 31 Fed 705H		B-31-25S-30E	2200' FNL & 600' FEL	2530	Flared/Sold	
Brushy Draw 31 Fed 108H		H-31-25S-30E	2200' FNL & 600' FEL	3960	Flared/Sold	
Brushy Draw 31 Fed 127H		H-31-25S-30E	2200' FNL & 660' FEL	3960	Flared/Sold	
Brushy Draw 31 Fed 128H		H-31-25S-30E	2200' FNL & 631' FEL	3960	Flared/Sold	
Brushy Draw 31 Fed 707H		H-31-25S-30E	2200' FNL & 720' FEL	2530	Flared/Sold	
Brushy Draw 31 Fed 907H		H-31-25S-30E	2200' FNL & 690' FEL	2300	Flared/Sold	



Database: EDM 5000.1 Single User Db
Company: XTO Energy
Project: Eddy County, NM (NAD-27)
Site: Brushy Draw 30 Federal
Well: #1202H
Wellbore: OH
Design: Plan #1

Local Co-ordinate Reference: Well #1202H
*TVD Reference: RKB= 27' @ 3118.00usft (Unknown)
MD Reference: RKB= 27' @ 3118.00usft (Unknown)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Design Targets

Target Name	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- hit/miss target	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)		
- Shape									
Brushy Dw 30 Fed. #1	0.00	0.00	0.00	0.00	0.00	398,300.90	626,476.20	32.094387	-103.924921
- plan hits target center									
- Point									
Brushy Dw 30 Fed. #1	0.00	0.00	10,870.00	-561.50	-211.32	397,739.40	626,264.89	32.092845	-103.925611
- plan hits target center									
- Point									
Brushy Dw 30 Fed. #1	0.00	0.00	10,870.23	-661.50	-210.80	397,639.40	626,265.40	32.092571	-103.925610
- plan hits target center									
- Point									
Brushy Dw 30 Fed. #1	0.00	0.00	10,899.70	-13,268.80	-145.70	385,032.10	626,330.50	32.057913	-103.925554
- plan misses target center by 0.17usft at 23906.92usft MD (10899.70 TVD, -13268.80 N, -145.87 E)									
- Point									
Brushy Dw 30 Fed. #1	0.00	0.00	10,900.00	-13,398.80	-145.20	384,902.10	626,331.00	32.057555	-103.925554
- plan hits target center									
- Point									

Formations

Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
750.00	750.00	Rustler			
993.00	993.00	Top Salt			
3,275.73	3,275.00	Base Salt			
3,465.85	3,465.00	Delaware			
7,230.14	7,227.00	Bone Spring			
8,201.72	8,198.00	1st Bone Spring Ss			
9,008.72	9,005.00	2nd Bone Spring Ss			
9,315.72	9,312.00	3rd Bone Spring Lm			
10,109.72	10,106.00	3rd Bone Spring Ss			
10,508.22	10,500.00	Wolfcamp			
10,674.71	10,645.00	Wolfcamp A			