

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTFORM APPROVED  
OMB NO. 1004-0137  
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**  
*Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.*5. Lease Serial No.  
NMNM120350

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.

**SUBMIT IN TRIPLICATE - Other instructions on page 2**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

8. Well Name and No.

HH SO 12 FED COM 2H

2. Name of Operator  
CHEVRON USA INCContact: LAURA BECERRA  
E-Mail: LBECERRA@CHEVRON.COM

9. API Well No.

30-015-44205-00-X1

3a. Address

ARTESIA, NM 88211-0960

3b. Phone No. (include area code)

Ph: 232-687-7850

10. Field and Pool or Exploratory Area

EDCAT

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec 12 T26S R27E SWNW 2657FNL 1294FWL  
32.055202 N Lat, 104.150261 W Lon

OCD Artesia

11. County or Parish, State

EDDY COUNTY, NM

## 12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

| TYPE OF SUBMISSION                                   | TYPE OF ACTION                                |                                               |                                                    |                                           |
|------------------------------------------------------|-----------------------------------------------|-----------------------------------------------|----------------------------------------------------|-------------------------------------------|
| <input checked="" type="checkbox"/> Notice of Intent | <input type="checkbox"/> Acidize              | <input type="checkbox"/> Deepen               | <input type="checkbox"/> Production (Start/Resume) | <input type="checkbox"/> Water Shut-Off   |
| <input type="checkbox"/> Subsequent Report           | <input type="checkbox"/> Alter Casing         | <input type="checkbox"/> Hydraulic Fracturing | <input type="checkbox"/> Reclamation               | <input type="checkbox"/> Well Integrity   |
| <input type="checkbox"/> Final Abandonment Notice    | <input type="checkbox"/> Casing Repair        | <input type="checkbox"/> New Construction     | <input type="checkbox"/> Recomplete                | <input checked="" type="checkbox"/> Other |
|                                                      | <input type="checkbox"/> Change Plans         | <input type="checkbox"/> Plug and Abandon     | <input type="checkbox"/> Temporarily Abandon       | Change to Original A                      |
|                                                      | <input type="checkbox"/> Convert to Injection | <input type="checkbox"/> Plug Back            | <input type="checkbox"/> Water Disposal            | PD                                        |

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomple horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recomple in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Chevron respectfully requests the following changes to the original approved APD.

Change BHL to 100' FSL & 660' FWL, UL: M on Sec. 12, T26S-R27E NMPM.  
Change MD from 14,952' to 9,902' ✓GC 9-17-18  
Accepted for record - NMOC

Attached you will find a revised drilling plan and certified well plat

RECEIVED

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL

SEP 14 2018

14. I hereby certify that the foregoing is true and correct.

Electronic Submission #435009 verified by the BLM Well Information System

For CHEVRON USA INC, sent to the Carlsbad

Committed to AFMSS for processing by ZOTA STEVENS on 09/13/2018 (18ZS0145SE)

Name (Printed/Typed) LAURA BECERRA

Title REGULATORY SPECIALIST

Signature (Electronic Submission)

Date 09/12/2018

## THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By ZOTA STEVENS

Title PETROLEUM ENGINEER

Date 09/13/2018

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Carlsbad

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

\*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\* BLM REVISED \*\*

RW 10-4-18

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
**District III**  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
**District IV**  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office

☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

|                                         |                                                   |                                                   |
|-----------------------------------------|---------------------------------------------------|---------------------------------------------------|
| <sup>1</sup> API Number<br>30-015-44205 | <sup>2</sup> Pool Code<br>30215                   | <sup>3</sup> Pool Name<br>Hay Hollow Bone Springs |
| <sup>4</sup> Property Code<br>315666    | <sup>5</sup> Property Name<br>HH SO 12 FED COM    |                                                   |
| <sup>7</sup> OGRID No.<br>4323          | <sup>8</sup> Operator Name<br>CHEVRON U.S.A. INC. | <sup>6</sup> Well Number<br>2H                    |
|                                         |                                                   | <sup>9</sup> Elevation<br>3189'                   |

| <sup>10</sup> Surface Location |         |          |                   |         |               |                  |               |                |        |
|--------------------------------|---------|----------|-------------------|---------|---------------|------------------|---------------|----------------|--------|
| UL or lot no.                  | Section | Township | Range             | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
| E                              | 12      | 26 SOUTH | 27 EAST, N.M.P.M. |         | 2657'         | NORTH            | 1294'         | WEST           | EDDY   |

| <sup>11</sup> Bottom Hole Location If Different From Surface |                               |                                  |                         |         |               |                  |               |                |        |
|--------------------------------------------------------------|-------------------------------|----------------------------------|-------------------------|---------|---------------|------------------|---------------|----------------|--------|
| UL or lot no.                                                | Section                       | Township                         | Range                   | Lot Idn | Feet from the | North/South line | Feet from the | East/West line | County |
| M                                                            | 12                            | 26 SOUTH                         | 27 EAST, N.M.P.M.       |         | 100'          | SOUTH            | 660'          | WEST           | EDDY   |
| <sup>12</sup> Dedicated Acres<br>80                          | <sup>13</sup> Joint or Infill | <sup>14</sup> Consolidation Code | <sup>15</sup> Order No. |         |               |                  |               |                |        |

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>A</p> <p>B</p> <p>2657'</p> <p>S 43°17'42" W<br/>907.16'</p> <p>1294'</p> <p>Proposed Producing Interval<br/>S 01°02'45" E 1,900.30'</p> <p>660'</p> <p>100'</p> <p>Proposed First Take Point</p> <p>Sec. 12</p> <p>2660'</p> <p>CORNER COORDINATES<br/>TABLE (NAD 27)<br/>A - Y=387127.27, X=556148.39<br/>B - Y=387127.91, X=557492.13<br/>C - Y=384468.90, X=556196.94<br/>D - Y=384469.58, X=557531.84<br/>E - Y=381810.53, X=556245.48<br/>F - Y=381811.24, X=557568.91</p>                                                                                                                                                                                                                           |  | <p>HH SO 12 FED COM 2H WELL</p> <p>X= 557,491<br/>Y= 384,471<br/>LAT. 32.056890 N<br/>LONG. 104.147760 W<br/>NAD 27</p> <p>X= 598,675<br/>Y= 384,528<br/>LAT. 32.057013 N<br/>LONG. 104.148251 W<br/>NAD83/86</p> <p>ELEVATION +3189' NAVD 88</p> <p>PROPOSED FIRST TAKE<br/>POINT 2000' FSL / 660' FWL</p> <p>X= 556,869<br/>Y= 383,811<br/>LAT. 32.055078 N<br/>LONG. 104.149772 W<br/>NAD 27</p> <p>X= 598,053<br/>Y= 383,868<br/>LAT. 32.055201 N<br/>LONG. 104.150263 W<br/>NAD83/86</p> <p>PROPOSED BOTTOM HOLE<br/>LOCATION</p> <p>X= 556,904<br/>Y= 381,911<br/>LAT. 32.049855 N<br/>LONG. 104.149670 W<br/>NAD 27</p> <p>X= 598,088<br/>Y= 381,968<br/>LAT. 32.049978 N<br/>LONG. 104.150161 W<br/>NAD83/86</p> |
| <p><b><sup>17</sup> OPERATOR CERTIFICATION</b></p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</p> <p><i>[Signature]</i> 9/12/2018<br/>Signature Date</p> <p>Laura Becerra<br/>Printed Name</p> <p>LBecerra@Chevron.com<br/>E-mail Address</p> |  | <p><b><sup>18</sup> SURVEYOR CERTIFICATION</b></p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p>03/01/2016<br/>Date of Survey</p> <p><i>[Signature]</i><br/>Signature and Seal of Professional Surveyor</p> <p>ROBERT L. LASTRAPES<br/>NEW MEXICO<br/>23006<br/>PROFESSIONAL SURVEYOR</p> <p>09/12/2018<br/>Certificate Number</p>                                                                                                                                                                                                            |

Rwp 10-4-18

### 1. FORMATION TOPS

The estimated tops of important geologic markers are as follows:

| FORMATION                      | SUB-SEA TVD | KBTVD   | MD     |
|--------------------------------|-------------|---------|--------|
| Castile                        |             | 505     |        |
| Lamar                          |             | 2,395   |        |
| Bell Canyon                    |             | 2,410   |        |
| Cherry Canyon                  |             | 3,208   |        |
| Brushy Canyon                  |             | 4,450   |        |
| Bone Spring / Avalon           |             | 6,299   |        |
| First Bone Spring Sand         |             | 6,888   |        |
| First Bone Spring Shale        |             | 6,914   |        |
| Second Bone Spring             |             | 7,444   |        |
| Second Bone Spring Sand Target |             | (7,830) | (9902) |

### 2. ESTIMATED DEPTH OF WATER, OIL, GAS & OTHER MINERAL BEARING FORMATIONS

The estimated depths at which the top and bottom of the anticipated water, oil, gas, or other mineral bearing formations are expected to be encountered are as follows:

| Substance                            | Formation              | Depth |
|--------------------------------------|------------------------|-------|
| Deepest Expected Base of Fresh Water |                        | 450   |
| Water                                | Castile                | 505   |
| Water                                | Cherry Canyon          | 3,208 |
| Oil/Gas                              | Brushy Canyon          | 4,450 |
| Oil/Gas                              | Bone Spring / Avalon   | 6,299 |
| Oil/Gas                              | First Bone Spring Sand | 6,888 |
| Oil/Gas                              | Second Bone Spring     | 7,444 |
| Oil/Gas                              | Third Bone Spring      | 7,830 |

All shows of fresh water and minerals will be reported and protected.

### 3. BOP EQUIPMENT

Chevron will have a minimum of a 5,000 psi rig stack (see proposed schematic) for drill out below surface casing. The Wolfcamp is not exposed until drill out of the intermediate casing, and the stack will be tested as specified in the attached testing requirements for 5K Stacks. Batch drilling of the surface, intermediate, and production will take place. A full BOP test will be performed unless approval from BLM is received otherwise. Flex choke hose will be used for all wells on the pad (see attached specs). Chevron requests a variance to use a CoFlex hose with a metal protective covering that will be utilized between the BOP and Choke manifold. Please refer to the attached testing and specification documents. BOP test will be conducted by a third party.

Chevron requests a variance to use a FMC Technologies UH-S Multibowl wellhead, which will be run through the rig floor on surface casing. BOPE will be nipped up and tested after cementing surface casing. Subsequent tests will be performed as needed, not to exceed 30 days. The field report from FMC Technologies and BOP test information will be provided in a subsequent report at the end of the well. Please see the attached wellhead schematic. An installation manual has been placed on file with the BLM office and remains unchanged from previous submittal.

#### 4. CASING PROGRAM

a. The proposed casing program will be as follows:

| Purpose      | From | To       | Hole Size | Csg Size | Weight | Grade  | Thread  | Condition |
|--------------|------|----------|-----------|----------|--------|--------|---------|-----------|
| Surface      | 0'   | 450'     | 17-1/2"   | 13-3/8"  | 54.5 # | J-55   | STC     | New       |
| Intermediate | 0'   | 2,395'   | 12-1/4"   | 9-5/8"   | 43.5 # | L-80IC | LTC     | New       |
| Production   | 0'   | (9,902') | 8-1/2"    | 5-1/2"   | 20.0 # | P-110  | TXP BTC | New       |

c. Casing design subject to revision based on geologic conditions encountered and actual formation tops.

\*\*\*A "Worst Case" casing design for wells in a particular area is used below to calculate the Casing Safety Factors. If for any reason the casing design for a particular well requires setting casing deeper than the following "worst case" design,

d. then the Casing Safety Factors will be recalculated & sent to the BLM prior to drilling.

Chevron will fill casing at a minimum of every 20 jts (840') while running for intermediate and production casing in order to maintain

e. collapse SF.

#### SF Calculations based on the following "Worst Case" casing design:

Surface Casing: 450' TVD  
Intermediate Casing: 2,395' TVD  
Production Casing: (9,902') MD (7,830') TVD

| Casing String | Min SF Burst | Min SF Collapse | Min SF Tension | Min SF Tri-Axial |
|---------------|--------------|-----------------|----------------|------------------|
| Surface       | 1.80         | 3.12            | 3.17           | 2.26             |
| Intermediate  | 1.23         | 1.28            | 1.60           | 1.50             |
| Production    | 1.15         | 1.39            | 2.19           | 1.38             |

The following worst case load cases were considered for calculation of the above Min. Safety Factors:

| Burst Design                                            | Surf | Int | Prod |
|---------------------------------------------------------|------|-----|------|
| Pressure Test- Surface, Int, Prod Csg                   | X    | X   | X    |
| P external: Mud weight above TOC, PP below              |      |     |      |
| P internal: Test psi + next section heaviest mud in csg |      |     |      |
| Displace to Gas- Surf Csg                               | X    |     |      |
| P external: Mud weight above TOC, PP below              |      |     |      |
| P internal: Dry Gas from Next Csg Point                 |      |     |      |
| Gas over mud (60/40) - Int Csg/Liner                    |      | X   |      |
| P external: Mud weight above TOC, PP below              |      |     |      |
| P internal: 60% gas over 40% mud from hole TD PP        |      |     |      |
| Stimulation (Frac) Pressures- Prod Csg                  |      |     | X    |
| P external: Mud weight above TOC, PP below              |      |     |      |
| P internal: Max inj pressure w/ heaviest injected fluid |      |     |      |
| Tubing leak- Prod Csg (packer at KOP)                   |      |     | X    |
| P external: Mud weight above TOC, PP below              |      |     |      |
| P internal: Leak just below surf, 8.45 ppg packer fluid |      |     |      |
| Collapse Design                                         | Surf | Int | Prod |
| Full Evacuation                                         | X    | X   | X    |
| P external: Mud weight gradient                         |      |     |      |
| P internal: none                                        |      |     |      |
| Cementing- Surf, Int, Prod Csg                          | X    | X   | X    |
| P external: Wet cement                                  |      |     |      |
| P internal: displacement fluid - water                  |      |     |      |
| Tension Design                                          | Surf | Int | Prod |
| 100k lb overpull                                        | X    | X   | X    |

| Slurry           | Type             | Top    | Bottom | Weight | Yield      | %Excess   | Sacks | Water  | Volume |
|------------------|------------------|--------|--------|--------|------------|-----------|-------|--------|--------|
| Surface          |                  |        | 425    | (ppg)  | (cu ft/sk) | Open Hole |       | gal/sk | bbls   |
| Tail             | Class C          | 0'     | 450'   | 14.8   | 1.34       | 50        | 488   | 6.40   | 117    |
| Intermediate Csg |                  |        |        |        |            |           |       |        |        |
| Lead             | Class C          | 0'     | 1,395' | 11.9   | 2.56       | 10        | 188   | 14.66  | 86     |
| Tail             | Class C          | 1,395' | 2,395' | 14.8   | 1.33       | 10        | 287   | 6.38   | 68     |
| Production       |                  |        |        |        |            |           |       |        |        |
| Lead             | Class C          | 2,095' | 6,299' | 11.9   | 2.46       | 10        | 430   | 14.05  | 189    |
| Lead 2           | Class C          | 6,299' | 8,902' | 13.2   | 1.85       | 10        | 354   | 9.87   | 117    |
| Tail             | Acid Sol Class H | 8,902' | 9,902' | 15     | 2.19       | 10        | 120   | 9.54   | 47     |

1. Final cement volumes will be determined by caliper.
2. Surface casing shall have at least one centralizer installed on each of the bottom three joints starting with the shoe joint.
3. Production casing will have one horizontal type centralizer on every joint for the first 1000' from TD, then every other joint to EOB, and then every third joint to KOP. Bowspring type centralizers will be run from KOP to intermediate casing. No centralizers will

| From   | To     | Type     | Weight     | Viscosity | Filtrate |
|--------|--------|----------|------------|-----------|----------|
| 0'     | 450'   | Spud Mud | 8.3 - 8.9  | 28-30     | N/C      |
| 450'   | 2,395' | WBM      | 9.0 - 10.1 | 28-31     | N/C      |
| 2,395' | 9,902' | OBM      | 8.3 - 9.5  | 10-15     | 15-25    |

A closed system will be used consisting of above ground steel tanks. All wastes accumulated during drilling operations will be contained in a portable trash cage and removed from location and deposited in an approved sanitary landfill. Sanitary wastes will be contained in a chemical porta-toilet and then hauled to an approved sanitary landfill.

All fluids and cuttings will be disposed of in accordance with New Mexico Oil Conservation Division rules and regulations.

A mud test shall be performed every 24 hours after mudding up to determine, as applicable: density, viscosity, gel strength, filtration, and pH.

Visual mud monitoring equipment shall be in place to detect volume changes indicating loss or gain of circulating fluid volume. When abnormal pressures are anticipated -- a pit volume totalizer (PVT), stroke

A weighting agent and lost circulating material (LCM) will be onsite to mitigate pressure or lost circulation as

#### 7. TESTING, LOGGING, AND CORING

The anticipated type and amount of testing, logging, and coring are as follows:

- Drill stem tests are not planned.
- The logging program will be as follows:

| TYPE    | Logs         | Interval            | Timing              |
|---------|--------------|---------------------|---------------------|
| Mudlogs | 2 man mudlog | Int Csg to TD       | Drillout of Int Csg |
| LWD     | MWD Gamma    | Int. and Prod. Hole | While Drilling      |

- Conventional whole core samples are not planned
- A directional survey will be run.

#### 8. ABNORMAL PRESSURES AND HYDROGEN SULFIDE

- No abnormal pressure or temperatures are expected. Estimated BHP is: 2,145 psi
- Hydrogen sulfide gas is not anticipated. An H2S Contingency plan is attached with this APD in the event that H2S is encountered

# PECOS DISTRICT

## DRILLING CONDITIONS OF APPROVAL

|                              |                                            |
|------------------------------|--------------------------------------------|
| <b>OPERATOR'S NAME:</b>      | <b>CHEVRON USA INC.</b>                    |
| <b>LEASE NO.:</b>            | <b>NMNM120350</b>                          |
| <b>WELL NAME &amp; NO.:</b>  | <b>HH SO 12 FED COM 2H</b>                 |
| <b>SURFACE HOLE FOOTAGE:</b> | <b>2657' FNL &amp; 1294' FWL</b>           |
| <b>BOTTOM HOLE FOOTAGE:</b>  | <b>100' FSL &amp; 660' FWL</b>             |
| <b>LOCATION:</b>             | <b>Section 12, T. 26 S., R 27 E., NMPM</b> |
| <b>COUNTY:</b>               | <b>Eddy County, New Mexico</b>             |

COA

**All previous COAs still apply expect the following:**

|                      |                                        |                                            |                               |
|----------------------|----------------------------------------|--------------------------------------------|-------------------------------|
| H2S                  | <input type="radio"/> Yes              | <input checked="" type="radio"/> No        |                               |
| Potash               | <input checked="" type="radio"/> None  | <input type="radio"/> Secretary            | <input type="radio"/> R-111-P |
| Cave/Karst Potential | <input type="radio"/> Low              | <input checked="" type="radio"/> Medium    | <input type="radio"/> High    |
| Variance             | <input type="radio"/> None             | <input checked="" type="radio"/> Flex Hose | <input type="radio"/> Other   |
| Wellhead             | <input type="radio"/> Conventional     | <input checked="" type="radio"/> Multibowl | <input type="radio"/> Both    |
| Other                | <input type="checkbox"/> 4 String Area | <input type="checkbox"/> Capitan Reef      | <input type="checkbox"/> WIPP |

### A. Hydrogen Sulfide

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

### B. CASING

1. The 13-3/8 inch surface casing shall be set at approximately 425 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface.
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
  - b. Wait on cement (WOC) time for a primary cement job will be a minimum of 8 hours or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)

- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
  - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the **9-5/8** inch intermediate casing is:
- Cement to surface. If cement does not circulate see B.1.a, c-d above. **Additional cement maybe required. Excess calculates to 9%.**
- Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.

❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings , the cement on the 3rd casing string must come to surface.

3. The minimum required fill of cement behind the **5-1/2** inch production casing is:
- Cement should tie-back at least 200 feet into previous casing string. Operator shall provide method of verification. **Additional cement maybe required. Excess calculates to -2%.**

### C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **3000 (3M) psi**.

## GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ Chaves and Roosevelt Counties  
 Call the Roswell Field Office, 2909 West Second St., Roswell NM 88201.  
 During office hours call (575) 627-0272.  
 After office hours call (575)

☒ Eddy County  
 Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,  
 (575) 361-2822



☒ Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)  
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
  - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
  - b. When the operator proposes to set surface casing with Spudder Rig
    - Notify the BLM when moving in and removing the Spudder Rig.
    - Notify the BLM when moving in the 2<sup>nd</sup> Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
    - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log (one log per well pad is acceptable) run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

#### A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCDD requirements shall be followed.

#### B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if

exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.

3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
  - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
  - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
  - b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except

the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).

- c. The tests shall be done by an independent service company utilizing a test plug. The results of the test shall be reported to the appropriate BLM office.
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- f. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes. This test shall be performed prior to the test at full stack pressure.
- g. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

#### C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

#### D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

**Waste Minimization Plan (WMP)**

In the interest of resource development, submission of additional well gas capture development plan information is deferred but may be required by the BLM Authorized Officer at a later date.

**ZS 091318**

Medium Cave Karst: two casing strings, both to circulate cement to surface.

| 13 3/8                                                    | surface csg in a | 17 1/2  | inch hole. | Design Factors |              |          | SURFACE |        |           |
|-----------------------------------------------------------|------------------|---------|------------|----------------|--------------|----------|---------|--------|-----------|
| Segment                                                   | #/ft             | Grade   | Coupling   | Joint          | Collapse     | Burst    | Length  | Weight |           |
| "A"                                                       | 54.50            | J 55    | ST&C       | 22.19          | 5.75         | 2.17     | 425     | 23,163 |           |
| "B"                                                       |                  |         |            |                |              |          | 0       | 0      |           |
| w/8.4#/g mud, 30min Sfc Csg Test psig: 1,500              |                  |         | Tail Cmt   | does           | circ to sfc. | Totals:  | 425     | 23,163 |           |
| Comparison of Proposed to Minimum Required Cement Volumes |                  |         |            |                |              |          |         |        |           |
| Hole                                                      | Annular          | 1 Stage | 1 Stage    | Min            | 1 Stage      | Drilling | Calc    | Req'd  | Min Dist  |
| Size                                                      | Volume           | Cmt Sx  | CuFt Cmt   | Cu Ft          | % Excess     | Mud Wt   | MASP    | BOPE   | Hole-Cplg |
| 17 1/2                                                    | 0.6946           | 488     | 654        | 349            | 87           | 8.90     | 730     | 2M     | 1.56      |

| 9 5/8                                                 | casing inside the |         | 13 3/8   | <u>Design Factors</u> |                      |          |        | <u>INTERMEDIATE</u> |           |
|-------------------------------------------------------|-------------------|---------|----------|-----------------------|----------------------|----------|--------|---------------------|-----------|
| Segment                                               | #/ft              | Grade   | Coupling | Joint                 | Collapse             | Burst    | Length | Weight              |           |
| "A"                                                   | 40.00             | L 80    | LT&C     | 7.59                  | 2.46                 | 1.49     | 2,395  | 95,800              |           |
| "B"                                                   |                   |         |          |                       |                      |          | 0      | 0                   |           |
| w/8.4#/g mud, 30min Sfc Csg Test psig:                |                   |         |          |                       |                      | Totals:  | 2,395  | 95,800              |           |
| The cement volume(s) are intended to achieve a top of |                   |         |          | 0                     | ft from surface or a |          | 425    | overlap.            |           |
| Hole                                                  | Annular           | 1 Stage | 1 Stage  | Min                   | 1 Stage              | Drilling | Calc   | Req'd               | Min Dist  |
| Size                                                  | Volume            | Cmt Sx  | CuFt Cmt | Cu Ft                 | % Excess             | Mud Wt   | MASP   | BOPE                | Hole-Cplg |
| 12 1/4                                                | 0.3132            | 475     | 863      | 790                   | 9                    | 10.10    | 2142   | 3M                  | 0.81      |

|                                                       |                   |         |                       |        |                      |                                 |                   |          |           |
|-------------------------------------------------------|-------------------|---------|-----------------------|--------|----------------------|---------------------------------|-------------------|----------|-----------|
| 5 1/2                                                 | casing inside the | 9 5/8   | <u>Design Factors</u> |        |                      |                                 | <u>PRODUCTION</u> |          |           |
| Segment                                               | #/ft              | Grade   | Coupling              | Joint  | Collapse             | Burst                           | Length            | Weight   |           |
| "A"                                                   | 20.00             | P 110   | TXP                   | 4.09   | 3.08                 | 3.27                            | 7,307             | 146,140  |           |
| "B"                                                   | 20.00             | P 110   | TXP                   | 8.75   | 2.53                 | 3.27                            | 2,595             | 51,900   |           |
| w/8.4#/g mud, 30min Sfc Csg Test psig: 1,608          |                   |         |                       |        |                      |                                 | Totals:           | 9,902    | 198,040   |
| B                                                     | would be:         |         |                       | 61.28  | 2.87                 | if it were a vertical wellbore. |                   |          |           |
| No Pilot Hole Planned                                 |                   | MTD     | Max VTD               | Csg VD | Curve KOP            | Dogleg°                         | Severity°         | MEOC     |           |
|                                                       |                   | 9902    | 7830                  | 7830   | 7307                 | 90                              | 9                 | 8300     |           |
| The cement volume(s) are intended to achieve a top of |                   |         |                       | 2195   | ft from surface or a |                                 | 200               | overlap. |           |
| Hole                                                  | Annular           | 1 Stage | 1 Stage               | Min    | 1 Stage              | Drilling                        | Calc              | Req'd    | Min Dist  |
| Size                                                  | Volume            | Cmt Sx  | CuFt Cmt              | Cu Ft  | % Excess             | Mud Wt                          | MASP              | BOPE     | Hole-Cplg |
| 8 3/4                                                 | 0.2526            | 904     | 1909                  | 1954   | -2                   | 9.50                            |                   |          | 1.33      |
| Class 'H' tail cmt yld > 1.20                         |                   |         |                       |        |                      |                                 |                   |          |           |