

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

S
Form C-103
Revised March 25, 1999

WELL API NO.
30-015-32527
5. Indicate Type of Lease
STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
V-1673

7. Lease Name or Unit Agreement Name:
Lost Tank AIS State

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter F : 2310 feet from the North line and 2310 feet from the West line

Section 36 Township 21S Range 31E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
3578' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: Spud, set surface and intermediate casing <input checked="" type="checkbox"/>	

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/17/03 - Spudded well at 10:00AM. Set 40' of 20" conductor and cemented to surface.

5/21/03 - Resumed drilling at 1:15 PM.

5/22/03 - Set 13-3/8" 48# casing at 865'. Cemented with 500 sx 35:65:6 "C" with additives. Tailed in with 200 sx "C" with additives. Cement circulated to surface. WOC 24 hrs. Reduced hole to 11" and resumed drilling.

5/29/03 - Set 8-5/8" 32# casing at 4220'. Cemented Stage 1: 1085 sx Halliburton Light Premium with additives and tailed in with 200 sx Halliburton Premium Plus with additives. Cement circulated to surface. Cemented Stage 2: 200 sx Halliburton Lite Premium with additives and tailed in with 100 sx Halliburton Premium Plus with additives. Cement circulated to surface. WOC 26 hrs 25 mins. Reduced hole to 7-7/8" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jina Huerta TITLE Regulatory Compliance Supervisor DATE June 4, 2003

Type or print name Jina Huerta

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY Jim W. Loom TITLE District Supervisor

DATE JUN 09 2003

Conditions of approval, if any: