District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy, Minerals and Natural Resources Department

NM OIL CONSERVATION
ARTESIA DISTRICT

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

MAR 1 5 2019

DEACHIES

Submit Original

to Appropriate

## **GAS CAPTURE PLAN**

				KECEIVED
	Operator: Apache Corporation	OGRID No:	873	Date:3/11/2019
☐ Amended	•			Date:
Reaso	n for Amendment:			

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

#### Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Palmillo 10 State Com 332H		Sec 10 T19S R28E	1030' FSL & 180' FEL	1500	Flared	Flare only in emergency
Palmillo 10 State Com 231H	30-015	Sec 10 T19S R28E	990' FSL & 180' FEL	1500	Flared	Flared only in emergency
Palmillo 10 State Com 331H		Sec 10 T19S R28E	950' FSL & 180' FEL	1500	Flared	Flared only in emergency

#### **Gathering System and Pipeline Notification**

Well(s) will be connected to a production facility after flowback operations are complete if gas transporter system is in place. The gas produced from production facility is dedicated to <a href="FRONTIER FIELD SERVICES">FRONTIER FIELD SERVICES</a>, LLC and will be connected to <a href="FRONTIER">FRONTIER's</a>
LOW pressure gathering system located in <a href="EDDY">EDDY</a> County, New Mexico. It will require <a href="500">500</a> ft of pipeline to connect the facility to <a href="LOW">LOW</a> pressure gathering system. Apache Corporation provides (periodically) to <a href="FRONTIER FIELD SERVICES">FRONTIER FIELD SERVICES</a>, LLC a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Apache Corporation and <a href="FRONTIER FIELD SERVICES">FRONTIER FIELD SERVICES</a>, LLC have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at <a href="FRONTIER'S MALJAMAR">FRONTIER'S MALJAMAR</a> Processing Plant located in <a href="Sec. 28">Sec. 28</a>, Twp 175</a>, Rng 32E, LEA County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on **FRONTIER FIELD SERVICES**, **LLC** system at that time. Based on current information, it is Apache Corporation's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

## **Alternatives to Reduce Flaring**

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - O Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines