. 🐨 L	UNITED STATES DEPARTMENT OF THE D BUREAU OF LAND MANA	NTERIOR OCDA	rtesia 5. Lease	FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018	
Do not use t	Y NOTICES AND REPO this form for proposals to	drill or to re-enter an	NMNI	M0559175	
abandoned w	vell. Use form 3160-3 (AP	D) for such proposals.		an, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2				7. If Unit or CA/Agreement, Name and/or No NMNM111025X	
1. Type of Well S Oil Well Gas Well Other			NDDU	ame and No. P UNIT 105	
2. Name of Operator EOG Y RESOURCES INC Contact: JEREMY HAASS E-Mail: jeremy_haass@eogresources.com 3a. Address 3b. Phone No. (include area contact)			9. API Well No. 30-015-26489-00-S1		
104 S 4TH STREET ARTESIA, NM 88210	3b. Phone No. (include area code) Ph: 575-748-4311	N DA	and Pool or Exploratory Area GGER DRAW-UPPER PEN		
4. Location of Well (Footage, Sec.,	T., R., M., or Survey Description)	11. Count	11. County or Parish, State	
Sec 30 T19S R25E SWNW 1980FNL 660FWL			- EDDY COU		
12. CHECK THE	APPROPRIATE BOX(ES)	TO INDICATE NATURE O	F NOTICE, REPORT	, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
□ Notice of Intent	Acidize	Deepen	Production (Start/I	Resume) 🔲 Water Shut-O	
	Alter Casing	Hydraulic Fracturing	Reclamation	🗖 Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete	Other	
Final Abandonment Notice	Change Plans	🛛 Plug and Abandon	Temporarily Aban	don	
	Convert to Injection	Plug Back	UWater Disposal		
determined that the site is ready for	r final inspection.	ed only after all requirements, includ	ing reclamation, have been	completed and the operator has	
<u>CIBP at 7650ft.</u> Set EOT at 2 <u>Calc 7468 ft.</u> 6/3/19 - Tagged TOC at 745	7650ft pumped 43 <u>bbls pluc</u> 2 ft_Load and circulated CS	of hole. <u>Set 7 inch CIBP at 76</u> gging mud and pumped 37 sx SG from 7452 ft to surface wit	Class H Cement to	RECLAMATION PROCEI	
<u>CIBP at 7650ft.</u> Set EOT at <u>Calc 7468 ft.</u> 6/3/19 - <u>Tagged TOC at 745</u> plugging mud. Pressure test	7650ft pumped 43 <u>bbls pluc</u> 2 ft. Load an <u>d circulated C:</u> ed CSG to 500 PSI for 10 r	oging mud and pumped 37 sx SG from 7452 ft to surface wit minutes and held FOT at 710	<u>Class H Čement</u> to h.280.bbls 9 ft numped 34 sx	ATTACHED	
<u>CIBP at 7650ft.</u> Set EOT at <u>Calc 7468.ft.</u> 6/3/19 - <u>Tagged TOC at 7455</u> plugging mud. Pressure test <u>Class H Cement to 6941 ft.</u>] pumped 25 sx Class C Cem	7650ft pumped 43 bbls plug 2.ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30 ent to 3165 ft.	oging mud and pumped 37 sx SG from 7452 ft to surface wit ninutes and held. EOT at 710 sx Class C Cement to 5578 ft	Class H Cement to h.280.bbls 9 ft pumped 34 sx -EOT-at.3319 ft	ATTACHED	
<u>CIBP at 7650ft.</u> Set EOT at 7 <u>Calc 7468.ft.</u> 6/3/19 - <u>Tagged TOC at 745</u> plugging mud. Pressure test <u>Class H Cement to 6941 ft.</u> <u>pumped 25 sx Class C Cem</u> 6/4/19 - EOT at 2098 ft pum Attempted injection rate into	7650ft pumped 43 bbls plug 2.ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30 ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No rate E	oging mud and pumped 37 sx SG from 7452 ft to surface wit minutes and held FOT at 710	Class H Cement to h.280.bbls 9 ft pumped 34 sx -EOT.at.3319 ft t 1246 ft. Class.C Cement	ATTACHED RECLAMAT DUE <u>12-5-1</u> 9	
<u>CIBP at 7650ft.</u> Set EOT at 7 <u>Calc 7468 ft.</u> 6/3/19 - <u>Tagged TOC at 745</u> plugging mud. Pressure test <u>Class H Cement to 6941 ft.</u> <u>pumped 25 sx Class C Cem</u> 6/4/19 - EOT at 2098 ft pum Attempted injection rate into to Calc. 1100 ft. Tagged TOU ft.	7650ft pumped 43 bbls plug 2.ft. Load and circulated C3 ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30 ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No.rate _E C at 1115 ft. Set EOT at 62	oging mud and pumped 37 sx SG from 7452 ft to surface wit ninutes and held. EOT at 710 sx Class C Cement to 5578 ft to 1944 ft. Perforated CSG at OT at 1315 ft pumped 35 sx 0	Class H Cement to h.280 bbls 9 ft pumped 34 sx - EOT at 3319 ft t 1246 ft Class C Cement ement to Calc. 472	ATTACHED	
<u>CIBP at 7650ft.</u> Set EOT at <u>Calc 7468.ft.</u> 6/3/19 - <u>Tagged TOC at 7455</u> plugging mud. Pressure test <u>Class H Cement to 6941 ft.</u> <u>pumped 25 sx Class C Cem</u> 6/4/19 - EOT at 2098 ft pum Attempted injection rate into to Calc. 1100.ft. Tagged TOC ft. 6/5/19 Tagged TOC at 493	7650ft pumped 43 bbls pluc 2.ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30 ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No rate E C at 1115 ft. Set EOT at 62 .ft. Perforated CSG at 57 ft	oging mud and pumped 37 sx SG from 7452 ft to surface wit ninutes and held. EOT at 710 sx Class C Cement to 5578 ft to 1944 ft_Perforated CSG at OL at 1315 ft pumped 35 sx C 6 ft pumped 25 sx Class C Ce	Class H Cement to h.280 bbls 9 ft pumped 34 sx - EOT at 3319 ft t 1246 ft Class C Cement ement to Calc. 472	ATTACHED RECLAMAT DUE <u>12-5-19</u> RECEIVED	
CIBP at 7650ft. Set EOT at Calc 7468.ft. 6/3/19 - Tagged TOC at 745 plugging mud. Pressure test Class H Cement to 6941 ft.] pumped 25 sx Class C Cem 6/4/19 - EOT at 2098 ft pum Attempted injection rate into to Calc. 1100 ft. Tagged TOC ft. 6/5/19 Tagged TOC at 493	7650ft pumped 43 bbls plug 2.ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30. ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No.rate_E C at 1115 ft. Set EOT at 62 ft. Perforated CSG at 57 ft is true and correct. Electronic Submission #	aging mud and pumped 37 sx SG from 7452 ft to surface with ninutes and held. EOT at 710 sx Class C Cement to 5578 ft to 1944 ft. Perforated CSG at OT at 1315 ft pumped 35 sx 7 6 ft pumped 25 sx Class C Ce Attempted injection rate into Attempted injection rate into ESOURCES NC sent to the C	Class H Cement to h 280 bbls 9 ft pumped 34 sx -EOT at 3319 ft t 1246 ft. Class C Cement ement to Calc. 472 .perfs. No	ATTACHED RECLAMAT DUE <u>12-5-19</u> RECEIVED JUN <u>2.5</u> 201	
CIBP at 7650ft. Set EOT at Calc 7468.ft. 6/3/19 - Tagged TOC at 745 plugging mud. Pressure test Class H Cement to 6941 ft.] pumped 25 sx Class C Cem 6/4/19 - EOT at 2098 ft pum Attempted injection rate into to Calc. 1100 ft. Tagged TOC ft. 6/5/19 Tagged TOC at 493	7650ft pumped 43 bbls plug 2.ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30. ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No.rate_E C at 1115 ft. Set EOT at 62 ft. Perforated CSG at 57 ft is true and correct. Electronic Submission #	aging mud and pumped 37 sx SG from 7452 ft to surface with ninutes and held. EOT at 710 sx Class C Cement to 5578 ft to 1944 ft. Perforated CSG at OT at 1315 ft pumped 35 sx 7 6 ft pumped 25 sx Class C Ce Attempted injection rate into Attempted injection rate into ESOURCES NC sent to the C	Class H Cement to h 280 bbls 9 ft pumped 34 sx -EOT at 3319 ft t 1246 ft. Class C Cement ement to Calc. 472 .perfs. No	ATTACHED RECLAMAT DUE <u>12-5-19</u> RECEIVED JUN <u>2.5</u> 201	
CIBP at 7650ft. Set EOT at Calc 7468.ft. 6/3/19 - Tagged TOC at 745 plugging mud. Pressure test Class H Cement to 6941 ft.] pumped 25 sx Class C Cem 6/4/19 - EOT at 2098 ft pum Attempted injection rate into to Calc. 1100 ft. Tagged TOC ft. 6/5/19 Tagged TOC at 493	7650ft pumped 43 bbls plug 2.ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30. ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No.rate_E C at 1115 ft. Set EOT at 62 ft. Perforated CSG at 57 ft is true and correct. Electronic Submission #	aging mud and pumped 37 sx SG from 7452 ft to surface with ninutes and held. EOT at 710 sx Class C Cement to 5578 ft to 1944 ft. Perforated CSG at OL at 1315 ft pumped 35 sx C 6 ft. pumped 25 sx Class C Ce Attempted injection rate into	Class H Cement to h 280 bbls 9 ft pumped 34 sx -EOT at 3319 ft t 1246 ft. Class C Cement ement to Calc. 472 .perfs. No	ATTACHED RECLAMAT DUE <u>12-5-19</u> RECEIVED JUN <u>2.5</u> 201	
<u>CIBP at 7650ft.</u> Set EOT at <u>Calc 7468.ft.</u> 6/3/19 - <u>Tagged TOC at 7455</u> plugging mud. Pressure test <u>Class H Cement to 6941 ft.</u>] <u>pumped 25 sx Class C Cem</u> 6/4/19 - EOT at 2098 ft pum Attempted injection rate into to Calc 1100.ft. Tagged TOC ft. 6/5/19 Tagged TOC at 493 14. I hereby certify that the foregoing Name (<i>Printed/Typed</i>) JEREM	7650ft pumped 43 bbls plug 2.ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30. ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No.rate_E C at 1115 ft. Set EOT at 62 ft. Perforated CSG at 57 ft is true and correct. Electronic Submission #	aging mud and pumped 37 sx SG from 7452 ft to surface with ninutes and held. EOT at 710 sx Class C Cement to 5578 ft to 1944 ft. Perforated CSG at OT at 1315 ft pumped 35 sx 7 6 ft pumped 25 sx Class C Ce Attempted injection rate into Attempted injection rate into ESOURCES NC sent to the C	Class H Cement to h.280.bbls 9 ft pumped 34 sx -EOT-at.3319 ft t 1246 ft. Class.C.Cement ement to Calc. 472 .perfs. No II Information System Carlsbad on 06/21/2019 [490].W0 ATORY SPECIALIST	ATTACHED RECLAMAT DUE <u>12-5-19</u> RECEIVED JUN <u>2.5</u> 201	
<u>CIBP at 7650ft.</u> Set EOT at 7 <u>Calc 7468.ft.</u> 6/3/19 - <u>Tagged TOC at 7455</u> plugging mud. Pressure test <u>Class H Cement to 6941 ft.</u>] <u>pumped 25 sx Class C Cem</u> 6/4/19 - EOT at 2098 ft pum Attempted injection rate into to Calc. 1100.ft. Tagged TOC ft. 6/5/19 Tagged TOC at 493 14. I hereby certify that the foregoing Name (<i>Printed/Typed</i>) JEREMY	7650ft pumped 43 bbls pluc 2.ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30. ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No.rate_E C at 1115 ft. Set EOT at 62 ft. Perforated CSG at 57 ft is true and correct. Electronic Submission # For EOG Y F mitted to AFMSS for process (HAASS	Agging mud and pumped 37 sx SG from 7452 ft to surface with ninutes and held. EOT at 710 sx Class C Cement to 5578 ft to 1944 ft_Perforated CSG at OI at 1315 ft pumped 35 sx C 6 ft pumped 25 sx Class C Ce Attempted injection rate into Attempted injection rate into Sing by DEBORAH MCKINNEY of Title REGUL	Class H Cement to h 280 bbls 9 ft pumped 34 sx -EOT-at 3319 ft t 1246 ft. Class C Cement ement to Calc. 472 .perfs. No Il Information System Carlsbad on 06/21/2018 (190) - 000 ATORY S PEORELAST 019 OFFICE USE	ATTACHED RECLAMAT DUE <u>12-5-19</u> RECEIVED JUN <u>2.5</u> 201 DISTRICTI-ARTESIA TED'FOR RECORD HIN <u>2.1 2019</u>	
CIBP at 7650ft. Set EOT at Calc 7468.ft. 6/3/19 - Tagged TOC at 7455 plugging mud. Pressure test Class H Cement to 6941 ft. J pumped 25 sx Class C Cem 6/4/19 - EOT at 2098 ft pum Attempted injection rate into to Calc. 1100 ft. Tagged TOC ft. 6/5/19 Tagged TOC at 493 14. I hereby certify that the foregoing Com Name (Printed/Typed) JEREMY Signature (Electronic	7650ft pumped 43 bbls pluc 2.ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30. ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No.rate_E C at 1115 ft. Set EOT at 62 ft. Perforated CSG at 57 ft is true and correct. Electronic Submission # For EOG Y F mitted to AFMSS for process (HAASS	Aging mud and pumped 37 sx SG from 7452 ft to surface with ninutes and held. EOT at 710 sx Class C Cement to 5578 ft to 1944 ft_Perforated CSG at OT at 1315 ft pumped 35 sx C 6 ft pumped 25 sx Class C Ce Attempted injection rate into a sent to the C sing by DEBORAH MCKINNEY of Title REGUL Date 06/20/2 DR FEDERAL OR STATE	Class H Cement to h.280.bbls 9 ft pumped 34 sx -EOT-at.3319 ft t 1246 ft. Class_C Cement ement to Calc. 472 .perfs. No Il Information System Carlsbad on 06/21/2018 (190) LV0 ATORY S Ptt OnetLet T 019 OFFICE USE BUREAU	ATTACHED RECLAMAT DUE 12-5-19 RECEIVED JUN 2.5 201 DISTRICTII-ARTESIA TED'FOR RECORD HIN 2.1 2019 MILLAND MANAGEMENT	
<u>CIBP at 7650ft.</u> Set EOT at 1 <u>Calc 7468.ft.</u> 6/3/19 - <u>Tagged TOC at 7455</u> plugging mud. Pressure test <u>Class H Cement to 6941 ft.</u>] <u>pumped 25 sx Class C Cem</u> 6/4/19 - EOT at 2098 ft pum Attempted injection rate into to Calc. 1100.ft. Tagged TOC ft. 6/5/19 Tagged TOC at 493 14. I hereby certify that the foregoing <u>Commanue (Printed/Typed) JEREMY</u> Signature (Electronic	7650ft pumped 43 bbls plug 2.ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30. ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No.rate. E C at 1115 ft. Set EOT at 62 .ft. Perforated CSG at 57 ft is true and correct. Electronic Submission # For EOG Y F mitted to AFMSS for process (HAASS Submission) THIS SPACE FC	Aging mud and pumped 37 sx SG from 7452 ft to surface with ninutes and held. EOT at 710 sx Class C Cement to 5578 ft to 1944 ft. Perforated CSG at OT at 1315 ft pumped 35 sx C 6 ft. pumped 25 sx Class C Ce Attempted injection rate into Sing by DEBORAH MCKINNEY of Title REGUL Date 06/20/2 DR FEDERAL OR STATE	Class H Cement to h.280.bbls 9 ft pumped 34 sx -EOT-at.3319 ft t 1246 ft. Class_C Cement ement to Calc. 472 .perfs. No Il Information System Carlsbad on 06/21/2018 (190) LV0 ATORY S Ptt OnetLet T 019 OFFICE USE BUREAU	ATTACHED RECLAMAT DUE 12-5-19 RECEIVED JUN 2.5 201 DISTRICT II-ARTESIA TED'FOR RECORD HIN 2.1 2019	
CIBP at 7650ft. Set EOT at Calc 7468.ft. 6/3/19 - Tagged TOC at 7455 plugging mud. Pressure test Class H Cement to 6941 ft. J pumped 25 sx Class C Cem 6/4/19 - EOT at 2098 ft pum Attempted injection rate into to Calc. 1100 ft. Tagged TOC ft. 6/5/19 Tagged TOC at 493 14. I hereby certify that the foregoing Com Name (Printed/Typed) JEREMY Signature (Electronic	7650ft pumped 43 bbls pluc 2 ft. Load and circulated C: ed CSG to 500 PSI for 10 r EOT at 5762 ft pumped 30 ent to 3165 ft. ped 25 sx Class C Cement perfs at 1246 ft. No.rate E C at 1115 ft. Set EOT at 62 ft. Perforated CSG at 57 ft is true and correct. Electronic Submission # For EOG Y F mitted to AFMSS for process (HAASS Submission) THIS SPACE FC med. Approval of this notice does quitable title to those rights in the duct operations thereon.	Agging mud and pumped 37 sx SG from 7452 ft to surface with ninutes and held. EOT at 7100 sx Class C Cement to 5578 ft to 1944 ft_Perforated CSG at OT at 1315 ft pumped 35 sx C 6 ft pumped 25 sx Class C Ce Attempted injection rate into Attempted injection rate into Sing by DEBORAH MCKINNEY of Title REGUL Date 06/20/2 DR FEDERAL OR STATE Not warrant or subject lease Office	Class H Cement to h 280 bbls 9 ft pumped 34 sx -EOT-at.3319 ft t 1246 ft. Class_C Cement ement to Calc. 472 .perfs_No II Information System Carlsbad on 06/21/2018 [A90]_MA ATORY SPECIAL BT 019 OFFICE USE BUREAU CAR	RECLAMAT DUE 12-5-19 RECEIVED JUN 2.5 201 DISTRICT II-ARTESIA TED FOR RECORD HIN 2.1 2019 MIN 2.1 2019 MIN 2.1 2019 MIN 2.1 2019 MIN 2.1 2019	

Additional data for EC transaction #469879 that would not fit on the form

32. Additional remarks, continued

rate. <u>Pumped 20 sx of Class C Cement and circulated to surface</u>. 6/17/19 - Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PLUGGED AND ABANDONED.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1 The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

!

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

. a

Crystal Weaver Environmental Protection Specialist 575-234-5943

Melissa Horn Environmental Protection Specialist 575-234-5951

Kelsey Wade Evnironmental Protection Specialist 575-234-5996

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612