Submit 1 Copy To Appropriate District Office State of New Mexico Form C	
District I – (575) 393-6161 Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240 SEP 2 7 2019 WELL API NO.	2013
DISTRET I - (5/3) /48-1283 OII CONSERVATION DIVISION 30-015-20113	
1000 Rio Brazos Rd. Aztec. NA Aztec. NA Estate State S	
District IV – (505) 476-3460 Santa Fe, NM 87505 1220 S. St. Francis Dr., Santa Fe, NM 87505 6. State Oil & Gas Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Na Nix Curtis BH	me
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 8. Well Number	
1. Type of Well: Oil Well ☐ Gas Well ☑ Other P&A 2 2. Name of Operator 9. OGRID Number	
EOG Resources, Inc. 7377	
3. Address of Operator 104 South Fourth Street, Artesia, NM 88210 10. Pool name or Wildcat Penasco Draw SA Yeso	
4. Well Location	
	line
Section 25 Township 18S Range 25E NMPM Eddy County 11. Elevation (Show whether DR, RKB, RT, GR, etc.)	
3452' GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON 🗭 REMEDIAL WORK ☐ ALTERING CASING	; □
TEMPORARILY ABANDON	/BK
DOWNHOLE COMMINGLE	
CLOSED-LOOP SYSTEM	_
OTHER: OTHER: OTHER: OTHER: OTHER: OTHER:	d date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of	a date
proposed completion or recompletion.	
8/21/19 – Moved in, rigged up and NUBOP. Removed production equipment. Set 4 ½" CIBP @ 1350'. Tagged CIBP @ 1350'. Pre tested CSG & CIBP to 600 psi. Held 10 minutes. Load and Circ. plugging mud. Perfed @ 1150'. Pressure tested perfs to 600 psi. Held 10 minutes.	
minutes. Set EOT @ 1346'. Spot 30 sx Class "C" Cement to Calc. 1000'.	
8/22/19 - Tagged TOC @ 976'. Set EOT @ 813'. Spot 27 sx Class "C" Cement to Calc. 547'. Perfed @ 200'. Pressure tested to 60' and held 10 minutes. Set EOT @ 260' and met 25 sy Class "C" Cement form 260'. Synford	0 psi
and held 10 minutes. Set EOT @ 260' and spot 25 sx Class "C" Cement from 260'- Surface. 9/19/19 – Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PLUGGED AND	
ABANDONED. Approved for plugging of well here only.	
Liability under bond is retained pending receipt	
of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under	
Forms, www.cmnrd.state.nm.us/ocd.	
Spud Date: Rig Release Date:	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE TITLE Regulatory Specialist DATE September 27, 2019	
Type or print name Jeremy Haass E-mail address: jeremy haass@eogresources.com PHONE: 575-748-	4311
For State Use Only	
APPROVED BY: DATE 10/1/19 Conditions of Approval (if any):	