

RECEIVED

SEP 27

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

DISTRICT IV-ARTESIA O.C.D.

WELL API NO.

30-015-26184

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other P&A

2. Name of Operator

EOG Resources, Inc.

3. Address of Operator

104 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter F : 1980 feet from the North line and 1980 feet from the West lineSection 25 Township 19S Range 24E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3626' GR

7. Lease Name or Unit Agreement Name
Parish IV Com

8. Well Number

3

9. OGRID Number

7377

10. Pool name or Wildcat

North Dagger Draw U/Penn

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/15/19 - Moved in rigged up and pulled production equipment. Set 7" CIBP @ 7620'. Tagged CIBP @ 7620'. Spot 40 sx Class "H" Cement to Calc. 7428'.

8/16/19 - Tagged TOC @ 7411'. Load and Circ. plugging mud from 7411' to surface. Pressured CSG & plug to 600 psi. Held 10 minutes. Set EOT @ 5554' spot 45 sx Class "C" Cement to Calc. 5277'.

8/19/19 - Tagged TOC @ 5294'. Set EOT @ 4068'. Spot 25 sx Class "C" Cement to Calc. 3914'. Set EOT @ 1969' spot Class "C" Cement to Calc. 1815'. Perf @ 1370'. Set packer @ 1033' pressure tested to 600 psi and held for 10 minutes. Set EOT @ 1420' and spot 35 sx Class "C" Cement to Calc. 1211'.

8/20/19 - Tagged TOC @ 1206'. Set EOT @ 552' and spot 25 sx Class "C" Cement to Calc. 398'. Perf @ 150'. Load and Circ. 50 sx Class "C" Cement down 7" CSG and up 9 5/8" CSG to surface.

9/19/19 - Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:

Approved for plugging of well bore only.
 Liability under bond is retained pending receipt
 of C-103 (Subsequent Report of Well Plugging)
 which may be found at OCD Web Page under
 Forms. www.oandd.state.nm.us/oandd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Regulatory Specialist DATE September 27, 2019Type or print name Jeremy Haass E-mail address: jeremy_haass@eogresources.com PHONE: 575-748-4311**For State Use Only**APPROVED BY: [Signature] TITLE Staff Mgr DATE 10/1/19

Conditions of Approval (If any):

28