# nm oil conservation

District I

1625 N. French Dr., Hobbs, NM 88240 District II ARTESIA DISTRICT

State of New Mexico

OCT 25E2919y, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

811 S. First St., Artesia, NM 88210

00/4 4/40

District III

1000 Rio Brazos Road, Aztec, NM 87410

RECEIVED

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

1220 S. St. Francis Dr., Santa Fe, NM 87505

## GAS CAPTURE PLAN

Date: <u>03/14/1</u>	<u>8</u>
x Original	Devon & OGRID No.: <u>Devon Energy Prod Co., LP</u> (6137)
	eason for Amendment: Submitting new APD's for Mr. Potato Head 11-14 331H, 621H, 711H, 731H, &
<u>732H.</u>	

This Gas Capture Plan outlines actions to be taken by the Devon to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

## Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared/ Vented	Comments
Mr. Potato Head 11-14 Fed Com 331H		Sec. 11, T24S, R29E	350 FNL, 1105 FWL			Mr. Potato Head 11 CTB 1
Mr. Potato Head 11-14 Fed Com 621H		Sec. 11, T24S, R29E	350 FNL, 1045 FWL			Mr. Potato Head 11 CTB 1
Mr. Potato Head 11-14 Fed Com 711H		Sec. 11, T24S, R29E	350 FNL, 1075 FWL			Mr. Potato Head 11 CTB 1
Mr. Potato Head 11-14 Fed Com 731H		Sec. 11, T24S, R29E	200 FNL, 1045 FWL			Mr. Potato Head 11 CTB 1
Mr. Potato Head 11-14 Fed Com 732H	,	Sec. 11, T24S, R29E	200 FNL, 1075 FWL			Mr. Potato Head 11 CTB 1

### Gathering System and Pipeline Notification

#### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>DCP</u> system at that time. Based on current information, it is <u>Devon's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

## Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines